



(12) **United States Patent**
Grupen et al.

(10) **Patent No.:** **US 10,733,982 B2**
(45) **Date of Patent:** **Aug. 4, 2020**

(54) **MULTI-DIRECTIONAL DIALOG**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Nicholas A. Grupen**, Sunnyvale, CA (US); **Matthew E. Austin**, Sunnyvale, CA (US); **Monica S. Ephrati**, Santa Clara, CA (US); **Kenneth H. Leung**, San Jose, CA (US); **Sebrand F. Warren**, San Francisco, CA (US); **Philip T. Williams**, Sunnyvale, CA (US); **Matthew Henderson**, San Jose, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 105 days.

(21) Appl. No.: **15/946,517**

(22) Filed: **Apr. 5, 2018**

(65) **Prior Publication Data**

US 2019/0213999 A1 Jul. 11, 2019

Related U.S. Application Data

(60) Provisional application No. 62/614,907, filed on Jan. 8, 2018.

(51) **Int. Cl.**
G10L 15/00 (2013.01)
G10L 15/18 (2013.01)
(Continued)

(52) **U.S. Cl.**
CPC **G10L 15/1815** (2013.01); **G06F 3/167** (2013.01); **G06F 16/90332** (2019.01);
(Continued)

(58) **Field of Classification Search**
USPC 704/231–257, 270–275
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,315,809 B2 1/2008 Xun
7,315,818 B2 1/2008 Stevens et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2694314 A1 8/2010
CA 2792412 A1 7/2011
(Continued)

OTHER PUBLICATIONS

Adium, “AboutAdium—Adium X—Trac”, available at <<http://web.archive.org/web/20070819113247/http://trac.adiumx.com/wiki/AboutAdium>>, retrieved on Nov. 25, 2011, 2 pages.

(Continued)


Primary Examiner — Jesse S Pullias

(74) *Attorney, Agent, or Firm* — Dentons US LLP

(57) **ABSTRACT**

Systems and processes for providing multi-directional dialog are provided. An example method includes, at an electronic device with one or more processors, receiving a first natural-language input; determining a first intent based on the first natural-language input, identifying a first dialog flow based on the first intent, outputting a natural-language output associated with the first dialog flow, receiving a second natural-language input; determining whether the second natural-language input satisfies dialog criteria associated with the first dialog flow, and in accordance with a determination that the second natural-language input satisfies the dialog criteria, outputting a second natural-language output associated with the first dialog flow.

28 Claims, 13 Drawing Sheets



- (51) **Int. Cl.**
G06F 3/16 (2006.01)
H04L 12/58 (2006.01)
G06F 16/9032 (2019.01)
H04M 3/493 (2006.01)
G06Q 10/00 (2012.01)
G06F 40/30 (2020.01)
G10L 15/22 (2006.01)
- (52) **U.S. Cl.**
CPC **G06F 40/30** (2020.01); **G06Q 10/00**
(2013.01); **G10L 15/22** (2013.01); **H04L 51/02**
(2013.01); **H04M 3/4936** (2013.01); **G10L**
15/1822 (2013.01); **G10L 2015/223** (2013.01)
- (56) **References Cited**
U.S. PATENT DOCUMENTS
- | | | | | | | | |
|-----------|----|--------|----------------------|-----------|----|---------|----------------------|
| 7,318,020 | B1 | 1/2008 | Kim | 7,427,024 | B1 | 9/2008 | Gazdzinski et al. |
| 7,319,957 | B2 | 1/2008 | Robinson et al. | 7,428,541 | B2 | 9/2008 | Houle |
| 7,321,783 | B2 | 1/2008 | Kim | 7,430,508 | B2 | 9/2008 | Williamson et al. |
| 7,322,023 | B2 | 1/2008 | Shulman et al. | 7,433,869 | B2 | 10/2008 | Gollapudi |
| 7,324,833 | B2 | 1/2008 | White et al. | 7,433,921 | B2 | 10/2008 | Ludwig et al. |
| 7,324,947 | B2 | 1/2008 | Jordan et al. | 7,436,947 | B2 | 10/2008 | Wadler et al. |
| 7,328,155 | B2 | 2/2008 | Endo et al. | 7,441,184 | B2 | 10/2008 | Frerebeau et al. |
| 7,328,250 | B2 | 2/2008 | Wang et al. | 7,443,316 | B2 | 10/2008 | Lim |
| 7,333,998 | B2 | 2/2008 | Heckerman et al. | 7,444,589 | B2 | 10/2008 | Zellner |
| 7,337,108 | B2 | 2/2008 | Florencio et al. | 7,447,360 | B2 | 11/2008 | Li et al. |
| 7,345,670 | B2 | 3/2008 | Armstrong | 7,447,624 | B2 | 11/2008 | Fuhrmann et al. |
| 7,345,671 | B2 | 3/2008 | Robbin et al. | 7,447,635 | B1 | 11/2008 | Konopka et al. |
| 7,349,953 | B2 | 3/2008 | Lisitsa et al. | 7,447,637 | B1 | 11/2008 | Grant et al. |
| 7,353,139 | B1 | 4/2008 | Burrell et al. | 7,451,081 | B1 | 11/2008 | Gajic et al. |
| 7,356,748 | B2 | 4/2008 | Taleb | 7,454,351 | B2 | 11/2008 | Jeschke et al. |
| 7,359,493 | B1 | 4/2008 | Wang et al. | 7,460,652 | B2 | 12/2008 | Chang |
| 7,359,671 | B2 | 4/2008 | Richenstein et al. | 7,461,043 | B2 | 12/2008 | Hess |
| 7,359,851 | B2 | 4/2008 | Tong et al. | 7,467,087 | B1 | 12/2008 | Gillick et al. |
| 7,360,158 | B1 | 4/2008 | Beeman | 7,467,164 | B2 | 12/2008 | Marsh |
| 7,362,738 | B2 | 4/2008 | Taube et al. | 7,472,061 | B1 | 12/2008 | Alewine et al. |
| 7,363,227 | B2 | 4/2008 | Mapes-Riordan et al. | 7,472,065 | B2 | 12/2008 | Aaron et al. |
| 7,363,586 | B1 | 4/2008 | Briggs et al. | 7,475,010 | B2 | 1/2009 | Chao |
| 7,365,260 | B2 | 4/2008 | Kawashima | 7,475,015 | B2 | 1/2009 | Epstein et al. |
| 7,366,461 | B1 | 4/2008 | Brown | 7,475,063 | B2 | 1/2009 | Datta et al. |
| 7,369,984 | B2 | 5/2008 | Fairweather | 7,477,238 | B2 | 1/2009 | Fux et al. |
| 7,373,291 | B2 | 5/2008 | Garst | 7,477,240 | B2 | 1/2009 | Yanagisawa |
| 7,373,612 | B2 | 5/2008 | Risch et al. | 7,478,037 | B2 | 1/2009 | Strong |
| 7,376,556 | B2 | 5/2008 | Bennett | 7,478,091 | B2 | 1/2009 | Mojsilovic et al. |
| 7,376,632 | B1 | 5/2008 | Sadek et al. | 7,478,129 | B1 | 1/2009 | Chemtob |
| 7,376,645 | B2 | 5/2008 | Bernard | 7,479,948 | B2 | 1/2009 | Kim et al. |
| 7,378,963 | B1 | 5/2008 | Begault et al. | 7,479,949 | B2 | 1/2009 | Jobs et al. |
| 7,379,874 | B2 | 5/2008 | Schmid et al. | 7,483,832 | B2 | 1/2009 | Tischer |
| 7,380,203 | B2 | 5/2008 | Keely et al. | 7,483,894 | B2 | 1/2009 | Cao |
| 7,383,170 | B2 | 6/2008 | Mills et al. | 7,487,089 | B2 | 2/2009 | Mozer |
| 7,386,110 | B2 | 6/2008 | Petrunka et al. | 7,487,093 | B2 | 2/2009 | Mutsuno et al. |
| 7,386,438 | B1 | 6/2008 | Franz et al. | 7,490,034 | B2 | 2/2009 | Finnigan et al. |
| 7,386,449 | B2 | 6/2008 | Sun et al. | 7,490,039 | B1 | 2/2009 | Shaffer et al. |
| 7,386,799 | B1 | 6/2008 | Clanton et al. | 7,493,251 | B2 | 2/2009 | Gao et al. |
| 7,389,224 | B1 | 6/2008 | Elworthy | 7,493,560 | B1 | 2/2009 | Kipnes et al. |
| 7,389,225 | B1 | 6/2008 | Jensen et al. | 7,496,498 | B2 | 2/2009 | Chu et al. |
| 7,392,185 | B2 | 6/2008 | Bennett | 7,496,512 | B2 | 2/2009 | Zhao et al. |
| 7,394,947 | B2 | 7/2008 | Li et al. | 7,499,923 | B2 | 3/2009 | Kawatani |
| 7,398,209 | B2 | 7/2008 | Kennewick et al. | 7,502,738 | B2 | 3/2009 | Kennewick et al. |
| 7,401,300 | B2 | 7/2008 | Nurmi | 7,505,795 | B1 | 3/2009 | Lim et al. |
| 7,403,938 | B2 | 7/2008 | Harrison et al. | 7,508,324 | B2 | 3/2009 | Suraqui |
| 7,403,941 | B2 | 7/2008 | Bedworth et al. | 7,508,373 | B2 | 3/2009 | Lin et al. |
| 7,404,143 | B2 | 7/2008 | Freelander et al. | 7,516,123 | B2 | 4/2009 | Betz et al. |
| 7,409,337 | B1 | 8/2008 | Potter et al. | 7,519,327 | B2 | 4/2009 | White |
| 7,409,347 | B1 | 8/2008 | Bellegarda | 7,519,398 | B2 | 4/2009 | Hirose |
| 7,412,389 | B2 | 8/2008 | Yang | 7,522,927 | B2 | 4/2009 | Fitch et al. |
| 7,412,470 | B2 | 8/2008 | Masuno et al. | 7,523,036 | B2 | 4/2009 | Akabane et al. |
| 7,415,100 | B2 | 8/2008 | Cooper et al. | 7,523,108 | B2 | 4/2009 | Cao |
| 7,415,469 | B2 | 8/2008 | Singh et al. | 7,526,466 | B2 | 4/2009 | Au |
| 7,418,382 | B1 | 8/2008 | Maes | 7,526,738 | B2 | 4/2009 | Ording et al. |
| 7,418,389 | B2 | 8/2008 | Chu et al. | 7,528,713 | B2 | 5/2009 | Singh et al. |
| 7,418,392 | B1 | 8/2008 | Mozer et al. | 7,529,671 | B2 | 5/2009 | Rockenbeck et al. |
| 7,426,467 | B2 | 9/2008 | Nashida et al. | 7,529,676 | B2 | 5/2009 | Koyama |
| 7,426,468 | B2 | 9/2008 | Coifman et al. | 7,535,997 | B1 | 5/2009 | McQuaide, Jr. et al. |
| | | | | 7,536,029 | B2 | 5/2009 | Choi et al. |
| | | | | 7,536,565 | B2 | 5/2009 | Girish et al. |
| | | | | 7,538,685 | B1 | 5/2009 | Cooper et al. |
| | | | | 7,539,619 | B1 | 5/2009 | Seligman et al. |
| | | | | 7,539,656 | B2 | 5/2009 | Fratkina et al. |
| | | | | 7,541,940 | B2 | 6/2009 | Upton |
| | | | | 7,542,967 | B2 | 6/2009 | Hurst-Hiller et al. |
| | | | | 7,542,971 | B2 | 6/2009 | Thione et al. |
| | | | | 7,543,232 | B2 | 6/2009 | Easton, Jr. et al. |
| | | | | 7,546,382 | B2 | 6/2009 | Healey et al. |
| | | | | 7,546,529 | B2 | 6/2009 | Reynar et al. |
| | | | | 7,548,895 | B2 | 6/2009 | Pulsipher |
| | | | | 7,552,045 | B2 | 6/2009 | Barliga et al. |
| | | | | 7,552,055 | B2 | 6/2009 | Lecoeuche |
| | | | | 7,555,431 | B2 | 6/2009 | Bennett |
| | | | | 7,555,496 | B1 | 6/2009 | Lantrip et al. |
| | | | | 7,558,381 | B1 | 7/2009 | Ali et al. |
| | | | | 7,558,730 | B2 | 7/2009 | Davis et al. |
| | | | | 7,559,026 | B2 | 7/2009 | Girish et al. |
| | | | | 7,561,069 | B2 | 7/2009 | Horstemeyer |
| | | | | 7,562,007 | B2 | 7/2009 | Hwang |

(56)

References Cited

U.S. PATENT DOCUMENTS

7,562,032 B2	7/2009	Abbosh et al.	7,689,245 B2	3/2010	Cox et al.
7,565,104 B1	7/2009	Brown et al.	7,689,408 B2	3/2010	Chen et al.
7,565,380 B1	7/2009	Venkatachary	7,689,409 B2	3/2010	Heinecke
7,568,151 B2	7/2009	Bargerion et al.	7,689,412 B2	3/2010	Wu et al.
7,571,092 B1	8/2009	Nieh	7,689,421 B2	3/2010	Li et al.
7,571,106 B2	8/2009	Cao et al.	7,693,715 B2	4/2010	Hwang et al.
7,577,522 B2	8/2009	Rosenberg	7,693,717 B2	4/2010	Kahn et al.
7,580,551 B1	8/2009	Srihari et al.	7,693,719 B2	4/2010	Chu et al.
7,580,576 B2	8/2009	Wang et al.	7,693,720 B2	4/2010	Kennewick et al.
7,580,839 B2	8/2009	Tamura et al.	7,698,131 B2	4/2010	Bennett
7,584,093 B2	9/2009	Potter et al.	7,702,500 B2	4/2010	Blaedow
7,584,278 B2	9/2009	Rajarajan et al.	7,702,508 B2	4/2010	Bennett
7,584,429 B2	9/2009	Fabritius	7,703,091 B1	4/2010	Martin et al.
7,593,868 B2	9/2009	Margiloff et al.	7,706,510 B2	4/2010	Ng
7,596,269 B2	9/2009	King et al.	7,707,026 B2	4/2010	Liu
7,596,499 B2	9/2009	Anguera et al.	7,707,027 B2	4/2010	Balchandran et al.
7,596,606 B2	9/2009	Codignotto	7,707,032 B2	4/2010	Wang et al.
7,596,765 B2	9/2009	Almas	7,707,221 B1	4/2010	Dunning et al.
7,599,918 B2	10/2009	Shen et al.	7,707,226 B1	4/2010	Tonse
7,603,349 B1	10/2009	Kraft et al.	7,707,267 B2	4/2010	Lisitsa et al.
7,603,381 B2	10/2009	Burke et al.	7,710,262 B2	5/2010	Ruha
7,606,444 B1	10/2009	Erol et al.	7,711,129 B2	5/2010	Lindahl et al.
7,609,179 B2	10/2009	Diaz-Gutierrez et al.	7,711,550 B1	5/2010	Feinberg et al.
7,610,258 B2	10/2009	Yuknewicz et al.	7,711,565 B1	5/2010	Gazdzinski
7,613,264 B2	11/2009	Wells et al.	7,711,672 B2	5/2010	Au
7,614,008 B2	11/2009	Ording	7,712,053 B2	5/2010	Bradford et al.
7,617,094 B2	11/2009	Aoki et al.	7,716,056 B2	5/2010	Weng et al.
7,620,407 B1	11/2009	Donald et al.	7,716,216 B1	5/2010	Harik et al.
7,620,549 B2	11/2009	Di Cristo et al.	7,720,674 B2	5/2010	Kaiser et al.
7,620,894 B1	11/2009	Kahn	7,720,683 B1	5/2010	Vermeulen et al.
7,623,119 B2	11/2009	Autio et al.	7,721,226 B2	5/2010	Barabe et al.
7,624,007 B2	11/2009	Bennett	7,721,301 B2	5/2010	Wong et al.
7,627,481 B1	12/2009	Kuo et al.	7,724,242 B2	5/2010	Hillis et al.
7,630,900 B1	12/2009	Strom	7,724,696 B1	5/2010	Parekh
7,630,901 B2	12/2009	Omi	7,725,307 B2	5/2010	Bennett
7,633,076 B2	12/2009	Huppi et al.	7,725,318 B2	5/2010	Gavalda et al.
7,634,409 B2	12/2009	Kennewick et al.	7,725,320 B2	5/2010	Bennett
7,634,413 B1	12/2009	Kuo et al.	7,725,321 B2	5/2010	Bennett
7,634,718 B2	12/2009	Nakajima	7,725,838 B2	5/2010	Williams
7,634,732 B1	12/2009	Blagsvedt et al.	7,729,904 B2	6/2010	Bennett
7,636,657 B2	12/2009	Ju et al.	7,729,916 B2	6/2010	Coffman et al.
7,640,158 B2	12/2009	Detlef et al.	7,734,461 B2	6/2010	Kwak et al.
7,640,160 B2	12/2009	Di Cristo et al.	7,735,012 B2	6/2010	Naik
7,643,990 B1	1/2010	Bellegarda	7,739,588 B2	6/2010	Reynar et al.
7,647,225 B2	1/2010	Bennett et al.	7,742,953 B2	6/2010	King et al.
7,649,454 B2	1/2010	Singh et al.	7,743,188 B2	6/2010	Haitani et al.
7,649,877 B2	1/2010	Vieri et al.	7,747,616 B2	6/2010	Yamada et al.
7,653,883 B2	1/2010	Hotelling et al.	7,752,152 B2	7/2010	Paek et al.
7,656,393 B2	2/2010	King et al.	7,756,708 B2	7/2010	Cohen et al.
7,657,424 B2	2/2010	Bennett	7,756,868 B2	7/2010	Lee
7,657,828 B2	2/2010	Lucas et al.	7,756,871 B2	7/2010	Yacoub et al.
7,657,844 B2	2/2010	Gibson et al.	7,757,173 B2	7/2010	Beaman
7,657,849 B2	2/2010	Chaudhri et al.	7,757,182 B2	7/2010	Elliott et al.
7,660,715 B1	2/2010	Thambiratnam	7,761,296 B1	7/2010	Bakis et al.
7,663,607 B2	2/2010	Hotelling et al.	7,763,842 B2	7/2010	Hsu et al.
7,664,558 B2	2/2010	Lindahl et al.	7,774,202 B2	8/2010	Spengler et al.
7,664,638 B2	2/2010	Cooper et al.	7,774,204 B2	8/2010	Mozer et al.
7,668,710 B2	2/2010	Doyle	7,774,388 B1	8/2010	Runchey
7,669,134 B1	2/2010	Christie et al.	7,777,717 B2	8/2010	Fux et al.
7,672,841 B2	3/2010	Bennett	7,778,432 B2	8/2010	Larsen
7,672,952 B2	3/2010	Isaacson et al.	7,778,595 B2	8/2010	White et al.
7,673,238 B2	3/2010	Girish et al.	7,778,632 B2	8/2010	Kurlander et al.
7,673,251 B1	3/2010	Wibisono	7,778,830 B2	8/2010	Davis et al.
7,673,340 B1	3/2010	Cohen et al.	7,779,353 B2	8/2010	Grigoriu et al.
7,676,026 B1	3/2010	Baxter, Jr.	7,779,356 B2	8/2010	Griesmer
7,676,365 B2	3/2010	Hwang et al.	7,779,357 B2	8/2010	Naik
7,676,463 B2	3/2010	Thompson et al.	7,783,283 B2	8/2010	Kuusinen et al.
7,679,534 B2	3/2010	Kay et al.	7,783,486 B2	8/2010	Rosser et al.
7,680,649 B2	3/2010	Park	7,788,590 B2	8/2010	Taboada et al.
7,681,126 B2	3/2010	Roose	7,788,663 B2	8/2010	Illowsky et al.
7,683,886 B2	3/2010	Willey	7,796,980 B1	9/2010	McKinney et al.
7,683,893 B2	3/2010	Kim	7,797,265 B2	9/2010	Brinker et al.
7,684,985 B2	3/2010	Dominach et al.	7,797,269 B2	9/2010	Rieman et al.
7,684,990 B2	3/2010	Caskey et al.	7,797,331 B2	9/2010	Theimer et al.
7,684,991 B2	3/2010	Stohr et al.	7,797,629 B2	9/2010	Fux et al.
			7,801,721 B2	9/2010	Rosart et al.
			7,801,728 B2	9/2010	Ben-David et al.
			7,801,729 B2	9/2010	Mozer
			7,805,299 B2	9/2010	Coifman

(56)

References Cited

U.S. PATENT DOCUMENTS

7,809,550	B1	10/2010	Barrows	7,925,610	B2	4/2011	Elbaz et al.
7,809,565	B2	10/2010	Coifman	7,929,805	B2	4/2011	Wang et al.
7,809,569	B2	10/2010	Attwater et al.	7,930,168	B2	4/2011	Weng et al.
7,809,570	B2	10/2010	Kennewick et al.	7,930,183	B2	4/2011	Odell et al.
7,809,610	B2	10/2010	Cao	7,930,197	B2	4/2011	Ozzie et al.
7,809,744	B2	10/2010	Nevidomski et al.	7,936,339	B2	5/2011	Marggraff et al.
7,818,165	B2	10/2010	Carlgren et al.	7,936,861	B2	5/2011	Martin et al.
7,818,176	B2	10/2010	Freeman et al.	7,936,863	B2	5/2011	John et al.
7,818,215	B2	10/2010	King et al.	7,937,075	B2	5/2011	Zellner
7,818,291	B2	10/2010	Ferguson et al.	7,941,009	B2	5/2011	Li et al.
7,818,672	B2	10/2010	McCormack et al.	7,945,294	B2	5/2011	Zhang et al.
7,822,608	B2	10/2010	Cross, Jr. et al.	7,945,470	B1	5/2011	Cohen et al.
7,823,123	B2	10/2010	Sabbouh	7,949,529	B2	5/2011	Weider et al.
7,826,945	B2	11/2010	Zhang et al.	7,949,534	B2	5/2011	Davis et al.
7,827,047	B2	11/2010	Anderson et al.	7,949,752	B2	5/2011	Lange et al.
7,831,423	B2	11/2010	Schubert	7,953,679	B2	5/2011	Chidlovskii et al.
7,831,426	B2	11/2010	Bennett	7,957,975	B2	6/2011	Burns et al.
7,831,432	B2	11/2010	Bodin et al.	7,958,136	B1	6/2011	Curtis et al.
7,835,504	B1	11/2010	Donald et al.	7,962,179	B2	6/2011	Huang
7,836,437	B2	11/2010	Kacmarcik et al.	7,974,835	B2	7/2011	Balchandran et al.
7,840,348	B2	11/2010	Kim et al.	7,974,844	B2	7/2011	Sumita
7,840,400	B2	11/2010	Lavi et al.	7,974,972	B2	7/2011	Cao
7,840,447	B2	11/2010	Kleinrock et al.	7,975,216	B2	7/2011	Woolf et al.
7,840,581	B2	11/2010	Ross et al.	7,983,478	B2	7/2011	Liu et al.
7,840,912	B2	11/2010	Elias et al.	7,983,915	B2	7/2011	Knight et al.
7,844,394	B2	11/2010	Kim	7,983,917	B2	7/2011	Kennewick et al.
7,848,924	B2	12/2010	Nurminen et al.	7,983,919	B2	7/2011	Conkie
7,848,926	B2	12/2010	Goto et al.	7,983,997	B2	7/2011	Allen et al.
7,853,444	B2	12/2010	Wang et al.	7,984,062	B2	7/2011	Dunning et al.
7,853,445	B2	12/2010	Bachenko et al.	7,986,431	B2	7/2011	Emori et al.
7,853,574	B2	12/2010	Kraenzel et al.	7,987,151	B2	7/2011	Schott et al.
7,853,577	B2	12/2010	Sundaresan et al.	7,987,244	B1	7/2011	Lewis et al.
7,853,664	B1	12/2010	Wang et al.	7,991,614	B2	8/2011	Washio et al.
7,853,900	B2	12/2010	Nguyen et al.	7,992,085	B2	8/2011	Wang-Aryattanwanich et al.
7,865,817	B2	1/2011	Ryan et al.	7,996,228	B2	8/2011	Miller et al.
7,869,998	B1	1/2011	Di Fabrizio et al.	7,996,589	B2	8/2011	Schultz et al.
7,869,999	B2	1/2011	Amato et al.	7,996,769	B2	8/2011	Fux et al.
7,870,118	B2	1/2011	Jiang et al.	7,996,792	B2	8/2011	Anzures et al.
7,870,133	B2	1/2011	Krishnamoorthy et al.	7,999,669	B2	8/2011	Singh et al.
7,873,149	B2	1/2011	Schultz et al.	8,000,453	B2	8/2011	Cooper et al.
7,873,519	B2	1/2011	Bennett	8,005,664	B2	8/2011	Hanumanthappa
7,873,523	B2*	1/2011	Potter G10L 15/01 704/275	8,005,679	B2	8/2011	Jordan et al.
7,873,654	B2	1/2011	Bernard	8,006,180	B2	8/2011	Tunning et al.
7,877,705	B2	1/2011	Chambers et al.	8,014,308	B2	9/2011	Gates et al.
7,880,730	B2	2/2011	Robinson et al.	8,015,006	B2	9/2011	Kennewick et al.
7,881,283	B2	2/2011	Cormier et al.	8,015,011	B2	9/2011	Nagano et al.
7,881,936	B2	2/2011	Longe et al.	8,015,144	B2	9/2011	Zheng et al.
7,885,390	B2	2/2011	Chaudhuri et al.	8,018,431	B1	9/2011	Zehr et al.
7,885,844	B1	2/2011	Cohen et al.	8,019,271	B1	9/2011	Izdepski
7,886,233	B2	2/2011	Rainisto et al.	8,020,104	B2	9/2011	Robarts et al.
7,889,101	B2	2/2011	Yokota	8,024,195	B2	9/2011	Mozer et al.
7,889,184	B2	2/2011	Blumenberg et al.	8,024,415	B2	9/2011	Horvitz et al.
7,889,185	B2	2/2011	Blumenberg et al.	8,027,836	B2	9/2011	Baker et al.
7,890,329	B2*	2/2011	Wu 704/231	8,031,943	B2	10/2011	Chen et al.
7,890,330	B2	2/2011	Ozkaragoz et al.	8,032,383	B1	10/2011	Bhardwaj et al.
7,890,652	B2	2/2011	Bull et al.	8,036,901	B2	10/2011	Mozer
7,895,039	B2	2/2011	Braho et al.	8,037,034	B2	10/2011	Plachta et al.
7,895,531	B2	2/2011	Radtke et al.	8,041,557	B2	10/2011	Liu
7,899,666	B2	3/2011	Varone	8,041,570	B2	10/2011	Mirkovic et al.
7,904,297	B2	3/2011	Mirkovic et al.	8,041,611	B2	10/2011	Kleinrock et al.
7,908,287	B1	3/2011	Katragadda	8,042,053	B2	10/2011	Darwish et al.
7,912,289	B2	3/2011	Kansal et al.	8,046,363	B2	10/2011	Cha et al.
7,912,699	B1	3/2011	Saraclar et al.	8,046,374	B1	10/2011	Bromwich et al.
7,912,702	B2	3/2011	Bennett	8,050,500	B1	11/2011	Batty et al.
7,912,720	B1	3/2011	Hakkani-Tur et al.	8,054,180	B1	11/2011	Scofield et al.
7,912,828	B2	3/2011	Bonnet et al.	8,055,502	B2	11/2011	Clark et al.
7,913,185	B1	3/2011	Benson et al.	8,055,708	B2	11/2011	Chitsaz et al.
7,916,979	B2	3/2011	Simmons	8,056,070	B2	11/2011	Goller et al.
7,917,367	B2	3/2011	Di Cristo et al.	8,060,824	B2	11/2011	Brownrigg, Jr. et al.
7,917,497	B2	3/2011	Harrison et al.	8,064,753	B2	11/2011	Freeman
7,920,678	B2	4/2011	Cooper et al.	8,065,143	B2	11/2011	Yanagihara
7,920,682	B2	4/2011	Byrne et al.	8,065,155	B1	11/2011	Gazdzinski
7,920,857	B2	4/2011	Lau et al.	8,065,156	B2	11/2011	Gazdzinski
7,925,525	B2	4/2011	Chin	8,068,604	B2	11/2011	Leeds et al.
				8,069,046	B2	11/2011	Kennewick et al.
				8,069,422	B2	11/2011	Sheshagiri et al.
				8,073,681	B2	12/2011	Baldwin et al.
				8,073,695	B1	12/2011	Hendricks et al.
				8,077,153	B2	12/2011	Benko et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,078,473	B1	12/2011	Gazdzinski	8,290,778	B2	10/2012	Gazdzinski
8,082,153	B2	12/2011	Coffman et al.	8,290,781	B2	10/2012	Gazdzinski
8,082,498	B2	12/2011	Salamon et al.	8,296,124	B1	10/2012	Holsztynska et al.
8,090,571	B2	1/2012	Elshishiny et al.	8,296,145	B2	10/2012	Clark et al.
8,095,364	B2	1/2012	Longe et al.	8,296,146	B2	10/2012	Gazdzinski
8,099,289	B2	1/2012	Mozer et al.	8,296,153	B2	10/2012	Gazdzinski
8,099,395	B2	1/2012	Pabla et al.	8,296,380	B1	10/2012	Kelly et al.
8,099,418	B2	1/2012	Inoue et al.	8,296,383	B2	10/2012	Lindahl
8,103,510	B2	1/2012	Sato	8,300,801	B2	10/2012	Sweeney et al.
8,107,401	B2	1/2012	John et al.	8,301,456	B2	10/2012	Gazdzinski
8,112,275	B2	2/2012	Kennewick et al.	8,311,189	B2	11/2012	Champlin et al.
8,112,280	B2	2/2012	Lu	8,311,834	B1	11/2012	Gazdzinski
8,117,037	B2	2/2012	Gazdzinski	8,311,835	B2	11/2012	Lecoeuche
8,117,542	B2	2/2012	Radtke et al.	8,311,838	B2	11/2012	Lindahl et al.
8,121,413	B2	2/2012	Hwang et al.	8,312,017	B2	11/2012	Martin et al.
8,121,837	B2	2/2012	Agapi et al.	8,321,786	B2	11/2012	Lunati et al.
8,122,094	B1	2/2012	Kotab	8,326,627	B2	12/2012	Kennewick et al.
8,122,353	B2	2/2012	Bouta	8,332,205	B2	12/2012	Krishnan et al.
8,130,929	B2	3/2012	Wilkes et al.	8,332,218	B2	12/2012	Cross et al.
8,131,557	B2	3/2012	Davis et al.	8,332,224	B2	12/2012	Di Cristo et al.
8,135,115	B1	3/2012	Hogg, Jr. et al.	8,332,748	B1	12/2012	Karam
8,138,912	B2	3/2012	Singh et al.	8,340,975	B1	12/2012	Rosenberger
8,140,335	B2	3/2012	Kennewick et al.	8,345,665	B2	1/2013	Vieri et al.
8,140,567	B2	3/2012	Padovitz et al.	8,346,563	B1	1/2013	Hjelm et al.
8,145,489	B2	3/2012	Freeman et al.	8,352,183	B2	1/2013	Thota et al.
8,150,694	B2	4/2012	Kennewick et al.	8,352,268	B2	1/2013	Naik et al.
8,150,700	B2	4/2012	Shin et al.	8,352,272	B2	1/2013	Rogers et al.
8,155,956	B2	4/2012	Cho et al.	8,355,919	B2	1/2013	Silverman et al.
8,156,005	B2	4/2012	Vieri	8,359,234	B2	1/2013	Vieri
8,160,877	B1	4/2012	Nucci et al.	8,370,145	B2	2/2013	Endo et al.
8,160,883	B2	4/2012	Lecoeuche	8,370,158	B2	2/2013	Gazdzinski
8,165,321	B2	4/2012	Paquier et al.	8,371,503	B2	2/2013	Gazdzinski
8,165,886	B1	4/2012	Gagnon et al.	8,374,871	B2	2/2013	Ehsani et al.
8,166,019	B1	4/2012	Lee et al.	8,375,320	B2	2/2013	Kotler et al.
8,166,032	B2	4/2012	Sommer et al.	8,380,504	B1	2/2013	Peden et al.
8,170,790	B2	5/2012	Lee et al.	8,380,507	B2	2/2013	Herman et al.
8,175,872	B2	5/2012	Kristjansson et al.	8,381,107	B2	2/2013	Rottler et al.
8,179,370	B1	5/2012	Yamasani et al.	8,381,135	B2	2/2013	Hotelling et al.
8,188,856	B2	5/2012	Singh et al.	8,386,485	B2	2/2013	Kerschberg et al.
8,190,359	B2	5/2012	Bourne	8,386,926	B1	2/2013	Matsuoka
8,190,596	B2	5/2012	Nambiar et al.	8,391,844	B2	3/2013	Lamiroux et al.
8,195,467	B2	6/2012	Mozer et al.	8,396,714	B2	3/2013	Rogers et al.
8,195,468	B2	6/2012	Kennewick et al.	8,396,715	B2 *	3/2013	Odell G10L 15/08 704/231
8,200,495	B2	6/2012	Braho et al.	8,401,163	B1	3/2013	Kirchhoff et al.
8,201,109	B2	6/2012	Van Os et al.	8,406,745	B1	3/2013	Upadhyay et al.
8,204,238	B2	6/2012	Mozer	8,423,288	B2	4/2013	Stahl et al.
8,205,788	B1	6/2012	Gazdzinski et al.	8,428,758	B2	4/2013	Naik et al.
8,209,183	B1	6/2012	Patel et al.	8,433,778	B1	4/2013	Shreesha et al.
8,213,911	B2	7/2012	Williams et al.	8,442,821	B1	5/2013	Vanhoucke
8,219,115	B1	7/2012	Nelissen	8,447,612	B2	5/2013	Gazdzinski
8,219,406	B2	7/2012	Yu et al.	8,452,597	B2	5/2013	Bringert et al.
8,219,407	B1	7/2012	Roy et al.	8,457,959	B2	6/2013	Kaiser
8,219,608	B2	7/2012	alSafadi et al.	8,458,115	B2	6/2013	Cai et al.
8,224,649	B2	7/2012	Chaudhari et al.	8,458,278	B2	6/2013	Christie et al.
8,228,299	B1	7/2012	Maloney et al.	8,464,150	B2	6/2013	Davidson et al.
8,233,919	B2	7/2012	Haag et al.	8,473,289	B2	6/2013	Jitkoff et al.
8,234,111	B2	7/2012	Lloyd et al.	8,479,122	B2	7/2013	Hotelling et al.
8,239,206	B1	8/2012	LeBeau et al.	8,484,027	B1	7/2013	Murphy
8,239,207	B2	8/2012	Seligman et al.	8,489,599	B2	7/2013	Bellotti
8,244,712	B2	8/2012	Serlet et al.	8,498,857	B2	7/2013	Kopparapu et al.
8,250,071	B1	8/2012	Killalea et al.	8,514,197	B2	8/2013	Shaharary et al.
8,254,829	B1	8/2012	Kindred et al.	8,515,736	B1	8/2013	Duta
8,255,216	B2	8/2012	White	8,515,750	B1	8/2013	Lei et al.
8,255,217	B2	8/2012	Stent et al.	8,521,513	B2	8/2013	Millett et al.
8,260,247	B2	9/2012	Lazaridis et al.	8,521,531	B1	8/2013	Kim
8,260,617	B2	9/2012	Dhanakshirur et al.	8,527,276	B1	9/2013	Senior et al.
8,270,933	B2	9/2012	Riemer et al.	8,543,398	B1	9/2013	Strope et al.
8,271,287	B1	9/2012	Kermani	8,560,229	B1	10/2013	Park et al.
8,275,621	B2	9/2012	Alewine et al.	8,571,851	B1	10/2013	Tickner et al.
8,279,171	B2	10/2012	Hirai et al.	8,583,416	B2	11/2013	Huang et al.
8,280,438	B2	10/2012	Barbera	8,583,511	B2	11/2013	Hendrickson
8,285,546	B2	10/2012	Reich	8,589,869	B2	11/2013	Wolfram
8,285,551	B2	10/2012	Gazdzinski	8,589,911	B1	11/2013	Sharkey et al.
8,285,553	B2	10/2012	Gazdzinski	8,595,004	B2	11/2013	Koshinaka
8,290,777	B1	10/2012	Nguyen et al.	8,600,743	B2	12/2013	Lindahl et al.
				8,600,930	B2	12/2013	Sata et al.
				8,606,568	B1	12/2013	Tickner et al.
				8,620,659	B2	12/2013	Di Cristo et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,620,662	B2	12/2013	Bellegarda	8,983,383	B1	3/2015	Haskin
8,626,681	B1	1/2014	Jurca et al.	8,989,713	B2	3/2015	Doulton
8,639,516	B2	1/2014	Lindahl et al.	8,990,235	B2	3/2015	King et al.
8,645,137	B2	2/2014	Bellegarda et al.	8,994,660	B2	3/2015	Neels et al.
8,645,138	B1	2/2014	Weinstein et al.	8,996,350	B1	3/2015	Dub et al.
8,654,936	B1	2/2014	Tofighbakhsh et al.	8,996,376	B2	3/2015	Fleizach et al.
8,655,646	B2	2/2014	Lee et al.	8,996,381	B2	3/2015	Mozer et al.
8,655,901	B1	2/2014	Li et al.	8,996,639	B1	3/2015	Faaborg et al.
8,660,843	B2	2/2014	Falcon et al.	9,009,046	B1	4/2015	Stewart
8,660,849	B2	2/2014	Gruber et al.	9,020,804	B2	4/2015	Barbaiani et al.
8,660,970	B1	2/2014	Fiedorowicz	9,026,425	B2	5/2015	Nikoulina et al.
8,661,112	B2	2/2014	Creamer et al.	9,031,834	B2	5/2015	Coorman et al.
8,661,340	B2	2/2014	Goldsmith et al.	9,037,967	B1	5/2015	Al-Jefri et al.
8,670,979	B2	3/2014	Gruber et al.	9,043,208	B2	5/2015	Koch et al.
8,675,084	B2	3/2014	Bolton et al.	9,049,255	B2	6/2015	MacFarlane et al.
8,676,904	B2	3/2014	Lindahl et al.	9,049,295	B1	6/2015	Cooper et al.
8,677,377	B2	3/2014	Cheyser et al.	9,053,706	B2	6/2015	Jitkoff et al.
8,681,950	B2	3/2014	Vlack et al.	9,058,811	B2	6/2015	Wang et al.
8,682,667	B2	3/2014	Haughay et al.	9,063,979	B2	6/2015	Chiu et al.
8,687,777	B1	4/2014	Lavian et al.	9,070,366	B1	6/2015	Mathias et al.
8,688,446	B2	4/2014	Yanagihara et al.	9,071,701	B2	6/2015	Donaldson et al.
8,688,453	B1	4/2014	Joshi et al.	9,076,448	B2	7/2015	Bennett et al.
8,695,074	B2	4/2014	Saraf et al.	9,076,450	B1	7/2015	Sadek et al.
8,696,364	B2	4/2014	Cohen	9,081,411	B2	7/2015	Kalns et al.
8,706,472	B2	4/2014	Ramerth et al.	9,081,482	B1	7/2015	Zhai et al.
8,706,474	B2	4/2014	Blume et al.	9,082,402	B2	7/2015	Yadgar et al.
8,706,503	B2	4/2014	Cheyser et al.	9,098,467	B1	8/2015	Blanksteen et al.
8,713,119	B2	4/2014	Lindahl et al.	9,101,279	B2	8/2015	Ritchey et al.
8,713,418	B2	4/2014	King et al.	9,112,984	B2	8/2015	Sejnoha et al.
8,719,006	B2	5/2014	Bellegarda et al.	9,117,447	B2	8/2015	Gruber et al.
8,719,014	B2	5/2014	Wagner et al.	9,123,338	B1	9/2015	Sanders et al.
8,731,610	B2	5/2014	Appaji	9,171,541	B2	10/2015	Kennewick et al.
8,731,912	B1	5/2014	Tickner et al.	9,171,546	B1	10/2015	Pike
8,731,942	B2	5/2014	Cheyser et al.	9,190,062	B2	11/2015	Haughay
8,739,208	B2	5/2014	Rodriguez et al.	9,208,153	B1	12/2015	Zaveri et al.
8,744,852	B1	6/2014	Seymour et al.	9,218,809	B2	12/2015	Bellegarda
8,760,537	B2	6/2014	Johnson et al.	9,218,819	B1	12/2015	Stekkelpak et al.
8,762,145	B2	6/2014	Ouchi et al.	9,223,537	B2	12/2015	Brown et al.
8,762,156	B2	6/2014	Chen et al.	9,255,812	B2	2/2016	Maeoka et al.
8,762,469	B2	6/2014	Lindahl et al.	9,258,604	B1	2/2016	Bilobrov et al.
8,768,693	B2	7/2014	Lempel et al.	9,262,612	B2	2/2016	Cheyser
8,768,702	B2	7/2014	Boettcher et al.	9,286,910	B1	3/2016	Li et al.
8,775,154	B2	7/2014	Clinchant et al.	9,292,487	B1	3/2016	Weber
8,775,931	B2	7/2014	Fux et al.	9,292,489	B1	3/2016	Sak et al.
8,781,456	B2	7/2014	Prociw	9,299,344	B2	3/2016	Braho et al.
8,781,841	B1	7/2014	Wang	9,305,543	B2	4/2016	Fleizach et al.
8,798,255	B2	8/2014	Lubowich et al.	9,305,548	B2	4/2016	Kennewick et al.
8,798,995	B1	8/2014	Edara et al.	9,311,912	B1	4/2016	Swietlinski et al.
8,799,000	B2	8/2014	Guzzoni et al.	9,313,317	B1	4/2016	LeBeau et al.
8,805,690	B1	8/2014	LeBeau et al.	9,318,108	B2	4/2016	Gruber et al.
8,812,302	B2	8/2014	Xiao et al.	9,325,809	B1	4/2016	Barros et al.
8,838,457	B2	9/2014	Cerra et al.	9,330,659	B2	5/2016	Ju et al.
8,855,915	B2	10/2014	Furuhata et al.	9,330,720	B2	5/2016	Lee
8,861,925	B1	10/2014	Ohme	9,338,493	B2	5/2016	Van Os et al.
8,862,252	B2	10/2014	Rottler et al.	9,349,368	B1	5/2016	LeBeau et al.
8,868,409	B1	10/2014	Mengibar et al.	9,361,084	B1	6/2016	Costa
8,880,405	B2	11/2014	Cerra et al.	9,367,541	B1	6/2016	Servan et al.
8,886,534	B2	11/2014	Nakano et al.	9,377,871	B2	6/2016	Waddell et al.
8,886,540	B2	11/2014	Cerra et al.	9,378,740	B1	6/2016	Rosen et al.
8,886,541	B2	11/2014	Friedlander	9,380,155	B1	6/2016	Reding et al.
8,892,446	B2	11/2014	Cheyser et al.	9,390,726	B1	7/2016	Smus et al.
8,893,023	B2	11/2014	Perry et al.	9,401,147	B2	7/2016	Jitkoff et al.
8,898,568	B2	11/2014	Bull et al.	9,412,392	B2	8/2016	Lindahl
8,903,716	B2	12/2014	Chen et al.	9,423,266	B2	8/2016	Clark et al.
8,909,693	B2	12/2014	Frissora et al.	9,436,918	B2	9/2016	Pantel et al.
8,918,321	B2*	12/2014	Czahor G10L 15/22 704/231	9,437,186	B1	9/2016	Liu et al.
8,930,176	B2	1/2015	Li et al.	9,437,189	B2	9/2016	Epstein et al.
8,930,191	B2	1/2015	Gruber et al.	9,454,957	B1	9/2016	Mathias et al.
8,938,394	B1	1/2015	Faaborg et al.	9,484,021	B1	11/2016	Mairesse et al.
8,942,986	B2	1/2015	Cheyser et al.	9,495,129	B2	11/2016	Fleizach et al.
8,943,423	B2	1/2015	Merrill et al.	9,501,741	B2	11/2016	Cheyser et al.
8,972,240	B2	3/2015	Brockett et al.	9,502,025	B2	11/2016	Kennewick et al.
8,972,432	B2	3/2015	Shaw et al.	9,510,044	B1	11/2016	Pereira et al.
8,972,878	B2	3/2015	Mohler et al.	9,535,906	B2	1/2017	Lee et al.
				9,536,527	B1	1/2017	Carlson
				9,547,647	B2	1/2017	Badaskar
				9,548,050	B2	1/2017	Gruber et al.
				9,575,964	B2	2/2017	Yadgar et al.
				9,578,173	B2	2/2017	Sanghavi et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,607,612	B2	3/2017	Deleeuw	2008/0082332	A1	4/2008	Mallett et al.
9,620,113	B2	4/2017	Kennewick et al.	2008/0082338	A1	4/2008	O'Neil et al.
9,620,126	B2	4/2017	Chiba	2008/0082390	A1	4/2008	Hawkins et al.
9,626,955	B2	4/2017	Fleizach et al.	2008/0082576	A1	4/2008	Bodin et al.
9,633,004	B2	4/2017	Giuli et al.	2008/0082651	A1	4/2008	Singh et al.
9,633,660	B2	4/2017	Haughay	2008/0084974	A1	4/2008	Dhanakshirur
9,652,453	B2	5/2017	Mathur et al.	2008/0085689	A1	4/2008	Zellner
9,658,746	B2	5/2017	Cohn et al.	2008/0091406	A1	4/2008	Baldwin et al.
9,668,121	B2	5/2017	Naik et al.	2008/0091426	A1	4/2008	Rempel et al.
9,672,725	B2	6/2017	Dotan-Cohen et al.	2008/0091428	A1	4/2008	Bellegarda
9,697,827	B1	7/2017	Lilly et al.	2008/0091443	A1	4/2008	Strope et al.
9,720,907	B2	8/2017	Bangalore et al.	2008/0096531	A1	4/2008	McQuaide et al.
9,734,839	B1	8/2017	Adams	2008/0096533	A1	4/2008	Manfredi et al.
10,469,665	B1 *	11/2019	Bell H04L 67/306	2008/0096726	A1	4/2008	Riley et al.
2008/0001785	A1	1/2008	Elizarov et al.	2008/0097937	A1	4/2008	Hadjarian
2008/0010050	A1	1/2008	Fux et al.	2008/0098302	A1	4/2008	Roose
2008/0010355	A1	1/2008	Vieri et al.	2008/0098480	A1	4/2008	Henry et al.
2008/0010605	A1	1/2008	Frank et al.	2008/0100579	A1	5/2008	Robinson et al.
2008/0012950	A1	1/2008	Lee et al.	2008/0101584	A1	5/2008	Gray et al.
2008/0013751	A1	1/2008	Hiselius	2008/0103774	A1	5/2008	White
2008/0015863	A1	1/2008	Agapi et al.	2008/0109222	A1	5/2008	Liu
2008/0015864	A1	1/2008	Ross et al.	2008/0109402	A1	5/2008	Wang et al.
2008/0016575	A1	1/2008	Vincent et al.	2008/0114480	A1	5/2008	Harb
2008/0021708	A1	1/2008	Bennett et al.	2008/0114598	A1	5/2008	Prieto et al.
2008/0021886	A1	1/2008	Wang-Aryattanwanich et al.	2008/0114604	A1	5/2008	Wei et al.
2008/0022208	A1	1/2008	Morse	2008/0114841	A1	5/2008	Lambert
2008/0027711	A1	1/2008	Rajendran et al.	2008/0115084	A1	5/2008	Scott et al.
2008/0027726	A1	1/2008	Hansen et al.	2008/0118143	A1	5/2008	Gordon et al.
2008/0031475	A1	2/2008	Goldstein	2008/0119953	A1	5/2008	Reed
2008/0033719	A1	2/2008	Hall et al.	2008/0120102	A1	5/2008	Rao
2008/0033723	A1	2/2008	Jang et al.	2008/0120112	A1	5/2008	Jordan et al.
2008/0034032	A1	2/2008	Healey et al.	2008/0120196	A1	5/2008	Reed et al.
2008/0034044	A1	2/2008	Bhakta et al.	2008/0120311	A1	5/2008	Reed
2008/0036743	A1	2/2008	Westerman et al.	2008/0120312	A1	5/2008	Reed
2008/0040339	A1	2/2008	Zhou et al.	2008/0120330	A1	5/2008	Reed
2008/0042970	A1	2/2008	Liang et al.	2008/0120342	A1	5/2008	Reed et al.
2008/0043936	A1	2/2008	Liebermann	2008/0122796	A1	5/2008	Jobs et al.
2008/0043943	A1	2/2008	Sipher et al.	2008/0124695	A1	5/2008	Myers et al.
2008/0046239	A1	2/2008	Boo	2008/0126075	A1	5/2008	Thorn et al.
2008/0046250	A1	2/2008	Agapi et al.	2008/0126077	A1	5/2008	Thorn
2008/0046422	A1	2/2008	Lee et al.	2008/0126091	A1	5/2008	Clark et al.
2008/0046820	A1	2/2008	Lee et al.	2008/0126093	A1	5/2008	Sivadas
2008/0046948	A1	2/2008	Verosub	2008/0126100	A1	5/2008	Grost et al.
2008/0048908	A1	2/2008	Sato	2008/0126491	A1	5/2008	Portele et al.
2008/0050027	A1	2/2008	Bashyam et al.	2008/0129520	A1	6/2008	Lee
2008/0052063	A1	2/2008	Bennett et al.	2008/0130867	A1	6/2008	Bowen
2008/0052073	A1	2/2008	Goto et al.	2008/0131006	A1	6/2008	Oliver
2008/0052077	A1	2/2008	Bennett et al.	2008/0132221	A1	6/2008	Willey et al.
2008/0052080	A1	2/2008	Narayanan et al.	2008/0132295	A1	6/2008	Horowitz
2008/0052262	A1	2/2008	Kosinov et al.	2008/0133215	A1	6/2008	Sarukkai
2008/0055194	A1	3/2008	Baudino et al.	2008/0133228	A1	6/2008	Rao
2008/0056459	A1	3/2008	Vallier et al.	2008/0133230	A1	6/2008	Herforth et al.
2008/0056579	A1	3/2008	Guha	2008/0133241	A1	6/2008	Baker et al.
2008/0057922	A1	3/2008	Kokes et al.	2008/0133479	A1	6/2008	Zelevinsky et al.
2008/0059190	A1	3/2008	Chu et al.	2008/0133956	A1	6/2008	Fadell
2008/0059200	A1	3/2008	Puli	2008/0140413	A1	6/2008	Millman et al.
2008/0059876	A1	3/2008	Hantler et al.	2008/0140415	A1	6/2008	Shostak
2008/0062141	A1	3/2008	Chaudhri	2008/0140416	A1	6/2008	Shostak
2008/0065382	A1	3/2008	Gerl et al.	2008/0140652	A1	6/2008	Millman et al.
2008/0065387	A1	3/2008	Cross et al.	2008/0140657	A1	6/2008	Azvine et al.
2008/0071529	A1	3/2008	Silverman et al.	2008/0140702	A1	6/2008	Reed et al.
2008/0071544	A1	3/2008	Beaufays et al.	2008/0141125	A1	6/2008	Ghassabian et al.
2008/0071742	A1	3/2008	Yang et al.	2008/0141180	A1	6/2008	Reed et al.
2008/0072143	A1	3/2008	Assadollahi	2008/0141182	A1	6/2008	Barsness et al.
2008/0075296	A1	3/2008	Lindahl et al.	2008/0146245	A1	6/2008	Appaji
2008/0076972	A1	3/2008	Dorogusker et al.	2008/0146290	A1	6/2008	Sreeram et al.
2008/0077310	A1	3/2008	Murlidar et al.	2008/0147408	A1	6/2008	Da Palma et al.
2008/0077384	A1	3/2008	Agapi et al.	2008/0147411	A1	6/2008	Dames et al.
2008/0077386	A1	3/2008	Gao et al.	2008/0147874	A1	6/2008	Yoneda et al.
2008/0077391	A1	3/2008	Chino et al.	2008/0150900	A1	6/2008	Han
2008/0077393	A1	3/2008	Gao et al.	2008/0154577	A1	6/2008	Kim et al.
2008/0077406	A1	3/2008	Ganong, III	2008/0154599	A1	6/2008	Muschett et al.
2008/0077859	A1	3/2008	Schabes et al.	2008/0154600	A1	6/2008	Tian et al.
2008/0079566	A1	4/2008	Singh et al.	2008/0154603	A1	6/2008	Oddo
2008/0080411	A1	4/2008	Cole	2008/0154612	A1	6/2008	Evermann et al.
				2008/0154828	A1	6/2008	Antebi et al.
				2008/0157867	A1	7/2008	Krah
				2008/0161113	A1	7/2008	Hansen et al.
				2008/0162120	A1	7/2008	Mactavish et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0162137	A1	7/2008	Saitoh et al.	2008/0255842	A1	10/2008	Simhi et al.
2008/0162471	A1	7/2008	Bernard	2008/0255845	A1	10/2008	Bennett
2008/0163119	A1	7/2008	Kim et al.	2008/0256613	A1	10/2008	Grover
2008/0163131	A1	7/2008	Hirai et al.	2008/0259022	A1	10/2008	Mansfield et al.
2008/0165144	A1	7/2008	Forstall et al.	2008/0261572	A1	10/2008	Tsui et al.
2008/0165980	A1	7/2008	Pavlovic et al.	2008/0262828	A1	10/2008	Och et al.
2008/0165994	A1	7/2008	Caren et al.	2008/0262838	A1	10/2008	Nurminen et al.
2008/0167013	A1	7/2008	Novick et al.	2008/0262846	A1	10/2008	Burns et al.
2008/0167858	A1	7/2008	Christie et al.	2008/0263139	A1	10/2008	Martin
2008/0167876	A1	7/2008	Bakis et al.	2008/0267416	A1	10/2008	Goldstein et al.
2008/0168052	A1	7/2008	Ott et al.	2008/0270118	A1	10/2008	Kuo et al.
2008/0168144	A1	7/2008	Lee	2008/0270138	A1	10/2008	Knight et al.
2008/0168366	A1	7/2008	Kocienda et al.	2008/0270139	A1	10/2008	Shi et al.
2008/0172698	A1	7/2008	Berger et al.	2008/0270140	A1	10/2008	Hertz et al.
2008/0183473	A1	7/2008	Nagano et al.	2008/0270151	A1	10/2008	Mahoney et al.
2008/0186960	A1	8/2008	Kocheisen et al.	2008/0270344	A1	10/2008	Yurick et al.
2008/0189099	A1	8/2008	Friedman et al.	2008/0273672	A1	11/2008	Didcock et al.
2008/0189106	A1	8/2008	Low et al.	2008/0277473	A1	11/2008	Kotlarsky et al.
2008/0189110	A1	8/2008	Freeman et al.	2008/0281510	A1	11/2008	Shahine
2008/0189114	A1	8/2008	Fail et al.	2008/0281582	A1	11/2008	Hsu et al.
2008/0189606	A1	8/2008	Rybak	2008/0288259	A1	11/2008	Chambers et al.
2008/0195312	A1	8/2008	Aaron et al.	2008/0288460	A1	11/2008	Poniatowski et al.
2008/0195388	A1	8/2008	Bower et al.	2008/0292112	A1	11/2008	Valenzuela et al.
2008/0195391	A1	8/2008	Marple et al.	2008/0294418	A1	11/2008	Cleary et al.
2008/0195601	A1	8/2008	Ntoulas et al.	2008/0294517	A1	11/2008	Hill
2008/0195630	A1	8/2008	Exartier et al.	2008/0294651	A1	11/2008	Masuyanna et al.
2008/0195940	A1	8/2008	Gail et al.	2008/0294981	A1	11/2008	Balzano et al.
2008/0200142	A1	8/2008	Abdel-Kader et al.	2008/0298563	A1	12/2008	Rondeau et al.
2008/0201000	A1	8/2008	Heikkila et al.	2008/0298766	A1	12/2008	Wen et al.
2008/0201306	A1	8/2008	Cooper et al.	2008/0299523	A1	12/2008	Chai et al.
2008/0201375	A1	8/2008	Khedouri et al.	2008/0300871	A1	12/2008	Gilbert
2008/0201434	A1	8/2008	Holmes et al.	2008/0300877	A1	12/2008	Gilbert et al.
2008/0204379	A1	8/2008	Perez-Noguera	2008/0300878	A1	12/2008	Bennett
2008/0207176	A1	8/2008	Brackbill et al.	2008/0301567	A1	12/2008	Martin et al.
2008/0208585	A1	8/2008	Ativanichayaphong et al.	2008/0303645	A1	12/2008	Seymour et al.
2008/0208587	A1	8/2008	Ben-David et al.	2008/0306727	A1	12/2008	Thurmair et al.
2008/0208864	A1	8/2008	Cucerzan et al.	2008/0312909	A1	12/2008	Hermansen et al.
2008/0212796	A1	9/2008	Denda	2008/0312928	A1	12/2008	Goebel et al.
2008/0219641	A1	9/2008	Sandrew et al.	2008/0313335	A1	12/2008	Jung et al.
2008/0221866	A1	9/2008	Katragadda et al.	2008/0316183	A1	12/2008	Westerman et al.
2008/0221879	A1	9/2008	Cerra et al.	2008/0319735	A1	12/2008	Kambhatla et al.
2008/0221880	A1	9/2008	Cerra et al.	2008/0319738	A1	12/2008	Liu et al.
2008/0221887	A1	9/2008	Rose et al.	2008/0319753	A1	12/2008	Hancock
2008/0221889	A1	9/2008	Cerra et al.	2008/0319763	A1	12/2008	Di Fabbizio et al.
2008/0221903	A1	9/2008	Kanevsky et al.	2008/0319783	A1	12/2008	Yao et al.
2008/0222118	A1	9/2008	Scian et al.	2009/0003115	A1	1/2009	Lindahl et al.
2008/0226130	A1	9/2008	Kansal et al.	2009/0005012	A1	1/2009	Van Heugten
2008/0228463	A1	9/2008	Mori et al.	2009/0005891	A1	1/2009	Batson et al.
2008/0228485	A1	9/2008	Owen	2009/0006096	A1	1/2009	Li et al.
2008/0228490	A1	9/2008	Fischer et al.	2009/0006097	A1	1/2009	Etezadi et al.
2008/0228495	A1	9/2008	Cross et al.	2009/0006099	A1	1/2009	Sharpe et al.
2008/0228496	A1	9/2008	Yu et al.	2009/0006100	A1	1/2009	Badger et al.
2008/0228928	A1	9/2008	Donelli et al.	2009/0006343	A1	1/2009	Platt et al.
2008/0229185	A1	9/2008	Lynch	2009/0006345	A1	1/2009	Platt et al.
2008/0229218	A1	9/2008	Maeng	2009/0006488	A1	1/2009	Lindahl et al.
2008/0235017	A1	9/2008	Satomura et al.	2009/0006671	A1	1/2009	Batson et al.
2008/0235023	A1	9/2008	Kennewick et al.	2009/0007001	A1	1/2009	Morin et al.
2008/0235024	A1	9/2008	Goldberg et al.	2009/0011709	A1	1/2009	Akasaka et al.
2008/0235027	A1	9/2008	Cross	2009/0012748	A1	1/2009	Beish et al.
2008/0240569	A1	10/2008	Tonouchi	2009/0012775	A1	1/2009	El Hady et al.
2008/0242280	A1	10/2008	Shapiro et al.	2009/0018828	A1	1/2009	Nakadai et al.
2008/0242322	A1	10/2008	Scott et al.	2009/0018829	A1	1/2009	Kuperstein
2008/0242363	A1	10/2008	Onda et al.	2009/0018834	A1	1/2009	Cooper et al.
2008/0243501	A1	10/2008	Hafsteinsson et al.	2009/0018835	A1	1/2009	Cooper et al.
2008/0243834	A1	10/2008	Rieman et al.	2009/0018839	A1	1/2009	Cooper et al.
2008/0244390	A1	10/2008	Fux et al.	2009/0018840	A1	1/2009	Lutz et al.
2008/0244446	A1	10/2008	Lefevre et al.	2009/0022329	A1	1/2009	Mahowald
2008/0247519	A1	10/2008	Abella et al.	2009/0024595	A1	1/2009	Chen
2008/0247529	A1	10/2008	Barton et al.	2009/0028435	A1	1/2009	Wu et al.
2008/0248797	A1	10/2008	Freeman et al.	2009/0030800	A1	1/2009	Grois
2008/0249770	A1	10/2008	Kim et al.	2009/0030978	A1	1/2009	Johnson et al.
2008/0249778	A1	10/2008	Barton et al.	2009/0043580	A1	2/2009	Mozer et al.
2008/0253577	A1	10/2008	Eppolito	2009/0043583	A1	2/2009	Agapi et al.
2008/0254425	A1	10/2008	Cohen et al.	2009/0043763	A1	2/2009	Peng
2008/0255837	A1	10/2008	Kahn et al.	2009/0044094	A1	2/2009	Rapp et al.
				2009/0048821	A1	2/2009	Yam et al.
				2009/0048841	A1	2/2009	Pollet et al.
				2009/0048845	A1	2/2009	Burckart et al.
				2009/0049067	A1	2/2009	Murray

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0055168	A1	2/2009	Wu et al.	2009/0154669	A1	6/2009	Wood et al.
2009/0055175	A1	2/2009	Terrell et al.	2009/0157382	A1	6/2009	Bar
2009/0055179	A1	2/2009	Cho et al.	2009/0157384	A1	6/2009	Toutanova et al.
2009/0055186	A1	2/2009	Lance et al.	2009/0157401	A1	6/2009	Bennett
2009/0055380	A1	2/2009	Peng et al.	2009/0158200	A1	6/2009	Palahnuik et al.
2009/0055381	A1	2/2009	Wu et al.	2009/0158323	A1	6/2009	Bober et al.
2009/0055648	A1	2/2009	Kim et al.	2009/0158423	A1	6/2009	Orlassino et al.
2009/0058823	A1	3/2009	Kocienda	2009/0160803	A1	6/2009	Hashimoto
2009/0058860	A1	3/2009	Fong et al.	2009/0163243	A1	6/2009	Barbera
2009/0060351	A1	3/2009	Li et al.	2009/0164301	A1	6/2009	O'Sullivan et al.
2009/0060472	A1	3/2009	Bull et al.	2009/0164441	A1	6/2009	Cheyser
2009/0063974	A1	3/2009	Bull et al.	2009/0164655	A1	6/2009	Pettersson et al.
2009/0064031	A1	3/2009	Bull et al.	2009/0164937	A1	6/2009	Alviar et al.
2009/0070097	A1	3/2009	Wu et al.	2009/0167508	A1	7/2009	Fadell et al.
2009/0070102	A1	3/2009	Maegawa	2009/0167509	A1	7/2009	Fadell et al.
2009/0070109	A1	3/2009	Didcock et al.	2009/0171578	A1	7/2009	Kim et al.
2009/0070114	A1	3/2009	Staszak	2009/0171662	A1	7/2009	Huang et al.
2009/0074214	A1	3/2009	Bradford et al.	2009/0171664	A1	7/2009	Kennewick et al.
2009/0076792	A1	3/2009	Lawson-Tancred	2009/0172108	A1	7/2009	Singh
2009/0076796	A1	3/2009	Daraselia	2009/0172542	A1	7/2009	Girish et al.
2009/0076798	A1	3/2009	Oh et al.	2009/0174667	A1	7/2009	Kocienda et al.
2009/0076819	A1	3/2009	Wouters et al.	2009/0174677	A1	7/2009	Gehani et al.
2009/0076821	A1	3/2009	Brenner et al.	2009/0177300	A1	7/2009	Lee
2009/0076825	A1	3/2009	Bradford et al.	2009/0177461	A1	7/2009	Ehsani et al.
2009/0077165	A1	3/2009	Rhodes et al.	2009/0177966	A1	7/2009	Chaudhri
2009/0079622	A1	3/2009	Seshadri et al.	2009/0182445	A1	7/2009	Girish et al.
2009/0083034	A1	3/2009	Hernandez et al.	2009/0182549	A1	7/2009	Anisimovich et al.
2009/0083035	A1	3/2009	Huang et al.	2009/0182702	A1	7/2009	Miller
2009/0083036	A1	3/2009	Zhao et al.	2009/0183070	A1	7/2009	Robbins
2009/0083037	A1	3/2009	Gleason et al.	2009/0187402	A1	7/2009	Scholl
2009/0083047	A1	3/2009	Lindahl et al.	2009/0187577	A1	7/2009	Reznik et al.
2009/0089058	A1	4/2009	Bellegarda	2009/0187950	A1	7/2009	Nicas et al.
2009/0091537	A1	4/2009	Huang et al.	2009/0190774	A1	7/2009	Wang et al.
2009/0092239	A1	4/2009	Macwan et al.	2009/0191895	A1	7/2009	Singh et al.
2009/0092260	A1	4/2009	Powers	2009/0192782	A1	7/2009	Drewes
2009/0092261	A1	4/2009	Bard	2009/0192787	A1	7/2009	Roon
2009/0092262	A1	4/2009	Costa et al.	2009/0192798	A1	7/2009	Basson et al.
2009/0094029	A1	4/2009	Koch et al.	2009/0198497	A1	8/2009	Kwon
2009/0094033	A1	4/2009	Mozer et al.	2009/0204402	A1	8/2009	Marhawa et al.
2009/0097634	A1	4/2009	Nambiar et al.	2009/0204409	A1	8/2009	Mozer et al.
2009/0097637	A1	4/2009	Boscher et al.	2009/0204478	A1	8/2009	Kaib et al.
2009/0098903	A1	4/2009	Donaldson et al.	2009/0204596	A1	8/2009	Brun et al.
2009/0100049	A1	4/2009	Cao	2009/0204601	A1	8/2009	Grasset
2009/0100454	A1	4/2009	Weber	2009/0204620	A1	8/2009	Thione et al.
2009/0104898	A1	4/2009	Harris	2009/0210230	A1	8/2009	Schwarz et al.
2009/0106026	A1	4/2009	Ferrieux	2009/0210232	A1	8/2009	Sanchez et al.
2009/0106376	A1	4/2009	Tom et al.	2009/0213134	A1	8/2009	Stephanick et al.
2009/0106397	A1	4/2009	O'Keefe	2009/0215466	A1	8/2009	Ahl et al.
2009/0112572	A1	4/2009	Thorn	2009/0215503	A1	8/2009	Zhang et al.
2009/0112576	A1	4/2009	Jackson et al.	2009/0216396	A1	8/2009	Yamagata
2009/0112592	A1	4/2009	Candelore et al.	2009/0216528	A1	8/2009	Gemello et al.
2009/0112677	A1	4/2009	Rhett	2009/0216540	A1	8/2009	Tessel et al.
2009/0112892	A1	4/2009	Cardie et al.	2009/0216704	A1	8/2009	Zheng et al.
2009/0119587	A1	5/2009	Allen et al.	2009/0219166	A1	9/2009	MacFarlane et al.
2009/0123021	A1	5/2009	Jung et al.	2009/0221274	A1	9/2009	Venkatakrishnan et al.
2009/0123071	A1	5/2009	Iwasaki	2009/0222257	A1	9/2009	Sumita et al.
2009/0125477	A1	5/2009	Lu et al.	2009/0222270	A2	9/2009	Likens et al.
2009/0125602	A1	5/2009	Bhatia et al.	2009/0222488	A1	9/2009	Boerries et al.
2009/0125947	A1	5/2009	Ibaraki	2009/0228126	A1	9/2009	Spielberg et al.
2009/0128505	A1	5/2009	Partridge et al.	2009/0228273	A1	9/2009	Wang et al.
2009/0132253	A1	5/2009	Bellegarda	2009/0228277	A1	9/2009	Bonforte et al.
2009/0132255	A1	5/2009	Lu	2009/0228281	A1	9/2009	Singleton et al.
2009/0137286	A1	5/2009	Luke et al.	2009/0228439	A1	9/2009	Manolescu et al.
2009/0138263	A1	5/2009	Shozakai et al.	2009/0228792	A1	9/2009	Van Os et al.
2009/0138736	A1	5/2009	Chin	2009/0228842	A1	9/2009	Westerman et al.
2009/0138828	A1	5/2009	Schultz et al.	2009/0233264	A1	9/2009	Rogers et al.
2009/0144036	A1	6/2009	Jorgensen et al.	2009/0234638	A1	9/2009	Ranjan et al.
2009/0144049	A1	6/2009	Haddad et al.	2009/0234651	A1	9/2009	Basir et al.
2009/0144428	A1	6/2009	Bowater et al.	2009/0234655	A1	9/2009	Kwon
2009/0144609	A1	6/2009	Liang et al.	2009/0235280	A1	9/2009	Tannier et al.
2009/0146848	A1	6/2009	Ghassabian	2009/0239202	A1	9/2009	Stone
2009/0150147	A1	6/2009	Jacoby et al.	2009/0239552	A1	9/2009	Churchill et al.
2009/0150156	A1	6/2009	Kennewick et al.	2009/0240485	A1	9/2009	Dalal et al.
2009/0152349	A1	6/2009	Bonev et al.	2009/0241054	A1	9/2009	Hendricks
2009/0153288	A1	6/2009	Hope et al.	2009/0241760	A1	10/2009	Georges
				2009/0247237	A1	10/2009	Mittleman et al.
				2009/0248182	A1	10/2009	Logan et al.
				2009/0248395	A1	10/2009	Alewine et al.
				2009/0248402	A1	10/2009	Ito et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0248420	A1	10/2009	Basir et al.	2010/0013796	A1	1/2010	Abileah et al.
2009/0248422	A1	10/2009	Li et al.	2010/0017212	A1	1/2010	Attwater et al.
2009/0248456	A1	10/2009	Fahmy et al.	2010/0017382	A1	1/2010	Katragadda et al.
2009/0249198	A1	10/2009	Davis et al.	2010/0019834	A1	1/2010	Zerbe et al.
2009/0249247	A1	10/2009	Tseng et al.	2010/0023318	A1	1/2010	Lemoine
2009/0252350	A1	10/2009	Seguin	2010/0023320	A1	1/2010	Di Cristo et al.
2009/0253457	A1	10/2009	Seguin	2010/0023331	A1	1/2010	Duta et al.
2009/0253463	A1	10/2009	Shin et al.	2010/0026526	A1	2/2010	Yokota
2009/0254339	A1	10/2009	Seguin	2010/0030549	A1	2/2010	Lee et al.
2009/0254345	A1	10/2009	Fleizach et al.	2010/0030928	A1	2/2010	Conroy et al.
2009/0254819	A1	10/2009	Song et al.	2010/0031143	A1	2/2010	Rao et al.
2009/0254823	A1	10/2009	Barrett	2010/0036653	A1	2/2010	Kim et al.
2009/0259475	A1	10/2009	Yamagami et al.	2010/0036655	A1	2/2010	Cecil et al.
2009/0259969	A1	10/2009	Pallakoff	2010/0036660	A1	2/2010	Bennett
2009/0265171	A1	10/2009	Davis	2010/0036928	A1	2/2010	Granito et al.
2009/0265368	A1	10/2009	Crider et al.	2010/0037183	A1	2/2010	Miyashita et al.
2009/0271109	A1	10/2009	Lee et al.	2010/0042400	A1	2/2010	Block et al.
2009/0271175	A1	10/2009	Bodin et al.	2010/0042576	A1	2/2010	Roettger et al.
2009/0271176	A1	10/2009	Bodin et al.	2010/0046842	A1	2/2010	Conwell et al.
2009/0271178	A1	10/2009	Bodin et al.	2010/0049498	A1	2/2010	Cao et al.
2009/0271188	A1	10/2009	Agapi et al.	2010/0049514	A1	2/2010	Kennewick et al.
2009/0271189	A1	10/2009	Agapi et al.	2010/0050064	A1	2/2010	Liu et al.
2009/0274315	A1	11/2009	Carnes et al.	2010/0054512	A1	3/2010	Solum
2009/0278804	A1	11/2009	Rubanovich et al.	2010/0057435	A1	3/2010	Kent et al.
2009/0281789	A1	11/2009	Waibel et al.	2010/0057443	A1	3/2010	Di Cristo et al.
2009/0284482	A1	11/2009	Chin	2010/0057457	A1	3/2010	Ogata et al.
2009/0286514	A1	11/2009	Lichorowic et al.	2010/0057461	A1	3/2010	Neubacher et al.
2009/0287583	A1	11/2009	Holmes	2010/0057643	A1	3/2010	Yang
2009/0290718	A1	11/2009	Kahn et al.	2010/0058200	A1	3/2010	Jablokov et al.
2009/0292987	A1	11/2009	Sorenson	2010/0060646	A1	3/2010	Unsal et al.
2009/0296552	A1	12/2009	Hicks et al.	2010/0063804	A1	3/2010	Sato et al.
2009/0298474	A1	12/2009	George	2010/0063825	A1	3/2010	Williams et al.
2009/0298529	A1	12/2009	Mahajan	2010/0063961	A1	3/2010	Guiheneuf et al.
2009/0299745	A1	12/2009	Kennewick et al.	2010/0064113	A1	3/2010	Lindahl et al.
2009/0299849	A1	12/2009	Cao et al.	2010/0064218	A1	3/2010	Bull et al.
2009/0300391	A1	12/2009	Jessup et al.	2010/0064226	A1	3/2010	Stefaniak et al.
2009/0300488	A1	12/2009	Salamon et al.	2010/0066684	A1	3/2010	Shahraray et al.
2009/0304198	A1	12/2009	Herre et al.	2010/0067723	A1	3/2010	Bergmann et al.
2009/0305203	A1	12/2009	Okumura et al.	2010/0067867	A1	3/2010	Lin et al.
2009/0306967	A1	12/2009	Nicolov et al.	2010/0070281	A1	3/2010	Conkie et al.
2009/0306969	A1	12/2009	Goud et al.	2010/0070521	A1	3/2010	Clinchant et al.
2009/0306979	A1	12/2009	Jaiswal et al.	2010/0070899	A1	3/2010	Hunt et al.
2009/0306980	A1	12/2009	Shin	2010/0071003	A1	3/2010	Bychkov et al.
2009/0306981	A1	12/2009	Cromack et al.	2010/0076760	A1	3/2010	Kraenzel et al.
2009/0306985	A1	12/2009	Roberts et al.	2010/0076993	A1	3/2010	Klawitter et al.
2009/0306988	A1	12/2009	Chen et al.	2010/0077350	A1	3/2010	Lim et al.
2009/0306989	A1	12/2009	Kaji	2010/0079501	A1	4/2010	Ikeda et al.
2009/0307162	A1	12/2009	Bui et al.	2010/0080398	A1	4/2010	Waldmann
2009/0307201	A1	12/2009	Dunning et al.	2010/0080470	A1	4/2010	Deluca et al.
2009/0307584	A1	12/2009	Davidson et al.	2010/0081456	A1	4/2010	Singh et al.
2009/0307594	A1	12/2009	Kosonen et al.	2010/0081487	A1	4/2010	Chen et al.
2009/0309352	A1	12/2009	Walker et al.	2010/0082286	A1	4/2010	Leung
2009/0313014	A1	12/2009	Shin et al.	2010/0082327	A1	4/2010	Rogers et al.
2009/0313020	A1	12/2009	Koivunen	2010/0082328	A1	4/2010	Rogers et al.
2009/0313023	A1	12/2009	Jones	2010/0082329	A1	4/2010	Silverman et al.
2009/0313026	A1	12/2009	Coffman et al.	2010/0082333	A1	4/2010	Al-Shammari
2009/0313544	A1	12/2009	Wood et al.	2010/0082346	A1	4/2010	Rogers et al.
2009/0313564	A1	12/2009	Rottler et al.	2010/0082347	A1	4/2010	Rogers et al.
2009/0316943	A1	12/2009	Frigola Munoz et al.	2010/0082348	A1	4/2010	Silverman et al.
2009/0318119	A1	12/2009	Basir et al.	2010/0082349	A1	4/2010	Bellegarda et al.
2009/0318198	A1	12/2009	Carroll	2010/0082567	A1	4/2010	Rosenblatt et al.
2009/0319257	A1	12/2009	Blume et al.	2010/0082970	A1	4/2010	Lindahl et al.
2009/0319266	A1	12/2009	Brown et al.	2010/0086152	A1	4/2010	Rank et al.
2009/0319342	A1	12/2009	Shilman et al.	2010/0086153	A1	4/2010	Hagen et al.
2009/0326923	A1	12/2009	Yan et al.	2010/0086156	A1	4/2010	Rank et al.
2009/0326936	A1	12/2009	Nagashima	2010/0088020	A1	4/2010	Sano et al.
2009/0326938	A1	12/2009	Marila et al.	2010/0088093	A1	4/2010	Lee et al.
2009/0326949	A1	12/2009	Douthitt et al.	2010/0088100	A1	4/2010	Lindahl
2009/0327977	A1	12/2009	Bachfischer et al.	2010/0094632	A1	4/2010	Davis et al.
2010/0004918	A1	1/2010	Lee et al.	2010/0098231	A1	4/2010	Wohlert et al.
2010/0004931	A1	1/2010	Ma et al.	2010/0100212	A1	4/2010	Lindahl et al.
2010/0005081	A1	1/2010	Bennett	2010/0100384	A1	4/2010	Ju et al.
2010/0010803	A1	1/2010	Ishikawa et al.	2010/0100385	A1	4/2010	Davis et al.
2010/0010814	A1	1/2010	Patel	2010/0100816	A1	4/2010	McCloskey et al.
2010/0013760	A1	1/2010	Hirai et al.	2010/0103776	A1	4/2010	Chan
				2010/0106486	A1	4/2010	Hua et al.
				2010/0106498	A1	4/2010	Morrison et al.
				2010/0106500	A1	4/2010	McKee et al.
				2010/0106503	A1	4/2010	Farrell et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0114856	A1	5/2010	Kuboyama	2010/0250599	A1	9/2010	Schmidt et al.
2010/0114887	A1	5/2010	Conway et al.	2010/0255858	A1	10/2010	Juhasz
2010/0121637	A1	5/2010	Roy et al.	2010/0257160	A1	10/2010	Cao
2010/0125456	A1	5/2010	Weng et al.	2010/0257478	A1	10/2010	Longe et al.
2010/0125458	A1	5/2010	Franco et al.	2010/0262599	A1	10/2010	Nitz
2010/0125460	A1	5/2010	Mellott et al.	2010/0268537	A1	10/2010	Al-Telmissani
2010/0125811	A1	5/2010	Moore et al.	2010/0268539	A1	10/2010	Xu et al.
2010/0131269	A1	5/2010	Park et al.	2010/0269040	A1	10/2010	Lee
2010/0131273	A1	5/2010	Aley-Raz et al.	2010/0274753	A1	10/2010	Liberty et al.
2010/0131498	A1	5/2010	Linthicum et al.	2010/0277579	A1	11/2010	Cho et al.
2010/0131899	A1	5/2010	Hubert	2010/0278320	A1	11/2010	Arsenault et al.
2010/0138215	A1	6/2010	Williams	2010/0278453	A1	11/2010	King
2010/0138224	A1	6/2010	Bedingfield, Sr.	2010/0280983	A1	11/2010	Cho et al.
2010/0138416	A1	6/2010	Bellotti	2010/0281034	A1	11/2010	Petrou et al.
2010/0138680	A1	6/2010	Brisebois et al.	2010/0286984	A1	11/2010	Wandinger et al.
2010/0138759	A1	6/2010	Roy	2010/0286985	A1	11/2010	Kennewick et al.
2010/0138798	A1	6/2010	Wilson et al.	2010/0287514	A1	11/2010	Cragun et al.
2010/0142740	A1	6/2010	Roerup	2010/0290632	A1	11/2010	Lin
2010/0145694	A1	6/2010	Ju et al.	2010/0293460	A1	11/2010	Budelli
2010/0145700	A1	6/2010	Kennewick et al.	2010/0295645	A1	11/2010	Falldin et al.
2010/0145707	A1	6/2010	Ljolje et al.	2010/0299133	A1	11/2010	Kopparapu et al.
2010/0146442	A1	6/2010	Nagasaka et al.	2010/0299138	A1	11/2010	Kim
2010/0150321	A1	6/2010	Harris et al.	2010/0299142	A1	11/2010	Freeman et al.
2010/0153114	A1	6/2010	Shih et al.	2010/0302056	A1	12/2010	Dutton et al.
2010/0153115	A1	6/2010	Klee et al.	2010/0304342	A1	12/2010	Zilber
2010/0153448	A1	6/2010	Harpur et al.	2010/0304705	A1	12/2010	Hursey et al.
2010/0161311	A1	6/2010	Massuh	2010/0305807	A1	12/2010	Basir et al.
2010/0161313	A1	6/2010	Karttunen	2010/0305947	A1	12/2010	Schwarz et al.
2010/0161337	A1	6/2010	Pulz et al.	2010/0312547	A1	12/2010	Van Os et al.
2010/0161554	A1	6/2010	Datuashvili et al.	2010/0312566	A1	12/2010	Odinak et al.
2010/0164897	A1	7/2010	Morin et al.	2010/0318366	A1	12/2010	Sullivan et al.
2010/0169075	A1	7/2010	Raffa et al.	2010/0318576	A1	12/2010	Kim
2010/0169093	A1	7/2010	Washio	2010/0322438	A1	12/2010	Siotis
2010/0169097	A1	7/2010	Nachman et al.	2010/0324709	A1	12/2010	Starmen
2010/0169098	A1	7/2010	Patch	2010/0324895	A1	12/2010	Kurzweil et al.
2010/0171713	A1	7/2010	Kwok et al.	2010/0324896	A1	12/2010	Attwater et al.
2010/0174544	A1	7/2010	Heifets	2010/0324905	A1	12/2010	Kurzweil et al.
2010/0175066	A1	7/2010	Paik	2010/0325131	A1	12/2010	Dumais et al.
2010/0179932	A1	7/2010	Yoon et al.	2010/0325158	A1	12/2010	Oral et al.
2010/0179991	A1	7/2010	Lorch et al.	2010/0325573	A1	12/2010	Estrada et al.
2010/0180218	A1	7/2010	Boston et al.	2010/0325588	A1	12/2010	Reddy et al.
2010/0185448	A1	7/2010	Meisel	2010/0330908	A1	12/2010	Maddern et al.
2010/0185949	A1	7/2010	Jaeger	2010/0332220	A1	12/2010	Hursey et al.
2010/0191520	A1	7/2010	Gruhn et al.	2010/0332224	A1	12/2010	Mäkelä et al.
2010/0197359	A1	8/2010	Harris	2010/0332235	A1	12/2010	David
2010/0199180	A1	8/2010	Brichter et al.	2010/0332236	A1	12/2010	Tan
2010/0199215	A1	8/2010	Seymour et al.	2010/0332280	A1	12/2010	Bradley et al.
2010/0204986	A1	8/2010	Kennewick et al.	2010/0332348	A1	12/2010	Cao
2010/0211199	A1	8/2010	Naik et al.	2010/0332428	A1	12/2010	McHenry et al.
2010/0211379	A1	8/2010	Gorman et al.	2010/0332976	A1	12/2010	Fux et al.
2010/0211644	A1	8/2010	Lavoie et al.	2010/0333030	A1	12/2010	Johns
2010/0216509	A1	8/2010	Riemer et al.	2010/0333163	A1	12/2010	Daly
2010/0217604	A1	8/2010	Baldwin et al.	2011/0002487	A1	1/2011	Panther et al.
2010/0222033	A1	9/2010	Scott et al.	2011/0004475	A1	1/2011	Bellegarda
2010/0222098	A1	9/2010	Garg	2011/0009107	A1	1/2011	Guba et al.
2010/0223055	A1	9/2010	McLean	2011/0010178	A1	1/2011	Lee et al.
2010/0223056	A1	9/2010	Kadirkamanathan et al.	2011/0010644	A1	1/2011	Merrill et al.
2010/0223131	A1	9/2010	Scott et al.	2011/0015928	A1	1/2011	Odell et al.
2010/0225599	A1	9/2010	Danielsson et al.	2011/0016150	A1	1/2011	Engstrom et al.
2010/0225809	A1	9/2010	Connors et al.	2011/0018695	A1	1/2011	Bells et al.
2010/0227642	A1	9/2010	Kim et al.	2011/0021213	A1	1/2011	Carr
2010/0228540	A1	9/2010	Bennett	2011/0022292	A1	1/2011	Shen et al.
2010/0228549	A1	9/2010	Herman et al.	2011/0022388	A1	1/2011	Wu et al.
2010/0228691	A1	9/2010	Yang et al.	2011/0022393	A1	1/2011	Waller et al.
2010/0229082	A1	9/2010	Karmarkar et al.	2011/0022394	A1	1/2011	Wide et al.
2010/0229100	A1	9/2010	Miller et al.	2011/0022472	A1	1/2011	Zon et al.
2010/0231474	A1	9/2010	Yamagajo et al.	2011/0022952	A1	1/2011	Wu et al.
2010/0235167	A1	9/2010	Bourdon	2011/0029616	A1	2/2011	Wang et al.
2010/0235341	A1	9/2010	Bennett	2011/0030067	A1	2/2011	Wilson
2010/0235729	A1	9/2010	Kocienda et al.	2011/0033064	A1	2/2011	Johnson et al.
2010/0235732	A1	9/2010	Bergman	2011/0034183	A1	2/2011	Haag et al.
2010/0235770	A1	9/2010	Ording et al.	2011/0035144	A1	2/2011	Okamoto et al.
2010/0235780	A1	9/2010	Westerman et al.	2011/0035434	A1	2/2011	Lockwood
2010/0241418	A1	9/2010	Maeda et al.	2011/0038489	A1	2/2011	Visser et al.
2010/0250542	A1	9/2010	Fujimaki	2011/0040707	A1	2/2011	Theisen et al.
				2011/0045841	A1	2/2011	Kuhlke et al.
				2011/0047072	A1	2/2011	Ciurea
				2011/0047149	A1	2/2011	Vaananen
				2011/0047161	A1	2/2011	Myaeng et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0047266	A1	2/2011	Yu et al.	2011/0161852	A1	6/2011	Vainio et al.
2011/0047605	A1	2/2011	Sontag et al.	2011/0166851	A1	7/2011	LeBeau et al.
2011/0050591	A1	3/2011	Kim et al.	2011/0167350	A1	7/2011	Hoellwarth
2011/0050592	A1	3/2011	Kim et al.	2011/0175810	A1	7/2011	Markovic et al.
2011/0054647	A1	3/2011	Chipchase	2011/0179002	A1	7/2011	Dumitru et al.
2011/0054894	A1	3/2011	Phillips et al.	2011/0179372	A1	7/2011	Moore et al.
2011/0054901	A1	3/2011	Qin et al.	2011/0183650	A1	7/2011	Mckee et al.
2011/0055256	A1	3/2011	Phillips et al.	2011/0184721	A1	7/2011	Subramanian et al.
2011/0060584	A1	3/2011	Ferrucci et al.	2011/0184730	A1	7/2011	LeBeau et al.
2011/0060587	A1	3/2011	Phillips et al.	2011/0184736	A1	7/2011	Slotznick
2011/0060589	A1	3/2011	Weinberg et al.	2011/0184737	A1	7/2011	Nakano et al.
2011/0060807	A1	3/2011	Martin et al.	2011/0184768	A1	7/2011	Norton et al.
2011/0064387	A1	3/2011	Mendeloff et al.	2011/0185288	A1	7/2011	Gupta et al.
2011/0065456	A1	3/2011	Brennan et al.	2011/0191108	A1	8/2011	Friedlander
2011/0066366	A1	3/2011	Ellanti et al.	2011/0191271	A1	8/2011	Baker et al.
2011/0066468	A1	3/2011	Huang et al.	2011/0191344	A1	8/2011	Jin et al.
2011/0066634	A1	3/2011	Phillips et al.	2011/0195758	A1	8/2011	Damale et al.
2011/0072492	A1	3/2011	Mohler et al.	2011/0196670	A1	8/2011	Dang et al.
2011/0076994	A1	3/2011	Kim et al.	2011/0197128	A1	8/2011	Assadollahi et al.
2011/0077943	A1	3/2011	Miki et al.	2011/0199312	A1	8/2011	Okuta
2011/0080260	A1	4/2011	Wang et al.	2011/0201385	A1	8/2011	Higginbotham et al.
2011/0081889	A1	4/2011	Gao et al.	2011/0201387	A1	8/2011	Paek et al.
2011/0082688	A1	4/2011	Kim et al.	2011/0202526	A1	8/2011	Lee et al.
2011/0083079	A1	4/2011	Farrell et al.	2011/0205149	A1	8/2011	Tom et al.
2011/0087491	A1	4/2011	Wittenstein et al.	2011/0208511	A1	8/2011	Sikstrom et al.
2011/0090078	A1	4/2011	Kim et al.	2011/0208524	A1	8/2011	Haughay
2011/0093261	A1	4/2011	Angott	2011/0209088	A1	8/2011	Hinckley et al.
2011/0093265	A1	4/2011	Stent et al.	2011/0212717	A1	9/2011	Rhoads et al.
2011/0093271	A1	4/2011	Bernard et al.	2011/0218806	A1	9/2011	Alewine et al.
2011/0099000	A1	4/2011	Rai et al.	2011/0218855	A1	9/2011	Cao et al.
2011/0103682	A1	5/2011	Chidlovskii et al.	2011/0219018	A1	9/2011	Bailey et al.
2011/0105097	A1	5/2011	Tadayon et al.	2011/0223893	A1	9/2011	Lau et al.
2011/0106736	A1	5/2011	Aharonson et al.	2011/0224972	A1	9/2011	Millett et al.
2011/0106892	A1	5/2011	Nelson et al.	2011/0228913	A1	9/2011	Cochinwala et al.
2011/0110502	A1	5/2011	Daye et al.	2011/0231182	A1	9/2011	Weider et al.
2011/0111724	A1	5/2011	Baptiste	2011/0231184	A1	9/2011	Kerr
2011/0112827	A1	5/2011	Kennewick et al.	2011/0231188	A1	9/2011	Kennewick et al.
2011/0112837	A1	5/2011	Kurki-Suonio et al.	2011/0231432	A1	9/2011	Sata et al.
2011/0112838	A1	5/2011	Adibi	2011/0231474	A1	9/2011	Locker et al.
2011/0112921	A1	5/2011	Kennewick et al.	2011/0238191	A1	9/2011	Kristjansson et al.
2011/0116610	A1	5/2011	Shaw et al.	2011/0238407	A1	9/2011	Kent
2011/0119049	A1	5/2011	Ylonen	2011/0238408	A1	9/2011	Larcheveque et al.
2011/0119051	A1	5/2011	Li et al.	2011/0238676	A1	9/2011	Liu et al.
2011/0119623	A1	5/2011	Kim	2011/0239111	A1	9/2011	Grover
2011/0119715	A1	5/2011	Chang et al.	2011/0242007	A1	10/2011	Gray et al.
2011/0123004	A1	5/2011	Chang et al.	2011/0244888	A1	10/2011	Ohki
2011/0125498	A1	5/2011	Pickering et al.	2011/0246471	A1	10/2011	Rakib et al.
2011/0125540	A1	5/2011	Jang et al.	2011/0249144	A1	10/2011	Chang
2011/0125701	A1	5/2011	Nair et al.	2011/0250570	A1	10/2011	Mack et al.
2011/0130958	A1	6/2011	Stahl et al.	2011/0257966	A1	10/2011	Rychlik
2011/0131036	A1	6/2011	DiCristo et al.	2011/0258188	A1	10/2011	Abdalmageed et al.
2011/0131038	A1	6/2011	Oyaizu et al.	2011/0260829	A1	10/2011	Lee
2011/0131045	A1	6/2011	Cristo et al.	2011/0260861	A1	10/2011	Singh et al.
2011/0137636	A1	6/2011	Srihari et al.	2011/0264643	A1	10/2011	Cao
2011/0141141	A1	6/2011	Kankainen	2011/0264999	A1	10/2011	Bells et al.
2011/0143726	A1	6/2011	de Silva	2011/0274303	A1	11/2011	Filson et al.
2011/0143811	A1	6/2011	Rodriguez	2011/0276595	A1	11/2011	Kirkland et al.
2011/0144857	A1	6/2011	Wingrove et al.	2011/0276598	A1	11/2011	Kozempel
2011/0144901	A1	6/2011	Wang	2011/0276944	A1	11/2011	Bergman et al.
2011/0144973	A1	6/2011	Bocchieri et al.	2011/0279368	A1	11/2011	Klein et al.
2011/0144999	A1	6/2011	Jang et al.	2011/0282663	A1	11/2011	Talwar et al.
2011/0145718	A1	6/2011	Ketola et al.	2011/0282888	A1	11/2011	Koperski et al.
2011/0151830	A1	6/2011	Blanda et al.	2011/0282906	A1	11/2011	Wong
2011/0153209	A1	6/2011	Geelen	2011/0283189	A1	11/2011	McCarty
2011/0153322	A1	6/2011	Kwak et al.	2011/0283190	A1	11/2011	Poltorak
2011/0153324	A1	6/2011	Ballinger et al.	2011/0288852	A1	11/2011	Dymetman et al.
2011/0153329	A1	6/2011	Moorer	2011/0288855	A1	11/2011	Roy
2011/0153330	A1	6/2011	Yazdani et al.	2011/0288861	A1	11/2011	Kurzweil et al.
2011/0153373	A1	6/2011	Dantzig et al.	2011/0288863	A1	11/2011	Rasmussen
2011/0154193	A1	6/2011	Creutz et al.	2011/0288866	A1	11/2011	Rasmussen
2011/0157029	A1	6/2011	Tseng	2011/0298585	A1	12/2011	Barry
2011/0161072	A1	6/2011	Terao et al.	2011/0301943	A1	12/2011	Patch
2011/0161076	A1	6/2011	Davis et al.	2011/0302162	A1	12/2011	Xiao et al.
2011/0161079	A1	6/2011	Gruhn et al.	2011/0306426	A1	12/2011	Novak et al.
2011/0161309	A1	6/2011	Lung et al.	2011/0307241	A1	12/2011	Waibel et al.
				2011/0307491	A1	12/2011	Fisk et al.
				2011/0307810	A1	12/2011	Hilerio et al.
				2011/0313775	A1	12/2011	Laligand et al.
				2011/0314003	A1	12/2011	Ju et al.

(56)	References Cited					
	U.S. PATENT DOCUMENTS					
	2011/0314032	A1	12/2011	Bennett et al.	2012/0150544	A1 6/2012 McLoughlin et al.
	2011/0314404	A1	12/2011	Kotler et al.	2012/0150580	A1 6/2012 Norton
	2011/0320187	A1	12/2011	Motik et al.	2012/0158293	A1 6/2012 Burnham
	2012/0002820	A1	1/2012	Leichter	2012/0158399	A1 6/2012 Tremblay et al.
	2012/0005602	A1	1/2012	Anttila et al.	2012/0158422	A1 6/2012 Burnham et al.
	2012/0008754	A1	1/2012	Mukherjee et al.	2012/0159380	A1 6/2012 Kocienda et al.
	2012/0010886	A1	1/2012	Razavilar	2012/0163710	A1 6/2012 Skaff et al.
	2012/0011138	A1	1/2012	Dunning et al.	2012/0166196	A1 6/2012 Ju et al.
	2012/0013609	A1	1/2012	Reponen et al.	2012/0173222	A1 7/2012 Wang et al.
	2012/0015629	A1	1/2012	Olsen et al.	2012/0173244	A1 7/2012 Kwak et al.
	2012/0016658	A1	1/2012	Wu et al.	2012/0173464	A1 7/2012 Tur et al.
	2012/0016678	A1	1/2012	Gruber et al.	2012/0174121	A1 7/2012 Treat et al.
	2012/0019400	A1	1/2012	Patel et al.	2012/0179457	A1 7/2012 Newman et al.
	2012/0020490	A1	1/2012	Leichter	2012/0179467	A1 7/2012 Williams
	2012/0022787	A1	1/2012	LeBeau et al.	2012/0185237	A1 7/2012 Gajic et al.
	2012/0022857	A1	1/2012	Baldwin et al.	2012/0185480	A1 7/2012 Ni et al.
	2012/0022860	A1	1/2012	Lloyd et al.	2012/0185781	A1 7/2012 Guzman et al.
	2012/0022868	A1	1/2012	LeBeau et al.	2012/0191461	A1 7/2012 Lin et al.
	2012/0022869	A1	1/2012	Lloyd et al.	2012/0192096	A1 7/2012 Bowman et al.
	2012/0022870	A1	1/2012	Kristjansson et al.	2012/0197743	A1 8/2012 Grigg et al.
	2012/0022872	A1	1/2012	Gruber et al.	2012/0197995	A1 8/2012 Caruso
	2012/0022874	A1	1/2012	Lloyd et al.	2012/0197998	A1 8/2012 Kessel et al.
	2012/0022876	A1	1/2012	LeBeau et al.	2012/0201362	A1 8/2012 Crossan et al.
	2012/0022967	A1	1/2012	Bachman et al.	2012/0209853	A1 8/2012 Desai et al.
	2012/0023088	A1	1/2012	Cheng et al.	2012/0209874	A1 8/2012 Wong et al.
	2012/0023095	A1	1/2012	Wadycki et al.	2012/0214141	A1 8/2012 Raya et al.
	2012/0023462	A1	1/2012	Rosing et al.	2012/0214517	A1 8/2012 Singh et al.
	2012/0029661	A1	2/2012	Jones et al.	2012/0215762	A1 8/2012 Hall et al.
	2012/0029910	A1	2/2012	Medlock et al.	2012/0221339	A1 8/2012 Wang et al.
	2012/0034904	A1	2/2012	LeBeau et al.	2012/0221552	A1 8/2012 Reponen et al.
	2012/0035907	A1	2/2012	Lebeau et al.	2012/0223889	A1 9/2012 Medlock et al.
	2012/0035908	A1	2/2012	Lebeau et al.	2012/0223936	A1 9/2012 Aughey et al.
	2012/0035924	A1	2/2012	Jitkoff et al.	2012/0232885	A1 9/2012 Barbosa et al.
	2012/0035925	A1	2/2012	Friend et al.	2012/0232886	A1 9/2012 Capuozzo et al.
	2012/0035926	A1	2/2012	Ambler	2012/0232906	A1 9/2012 Lindahl et al.
	2012/0035931	A1	2/2012	LeBeau et al.	2012/0239661	A1 9/2012 Giblin
	2012/0035932	A1	2/2012	Jitkoff et al.	2012/0239761	A1 9/2012 Linner et al.
	2012/0036556	A1	2/2012	LeBeau et al.	2012/0242482	A1 9/2012 Elumalai et al.
	2012/0039539	A1	2/2012	Boiman et al.	2012/0245719	A1 9/2012 Story, Jr. et al.
	2012/0041752	A1	2/2012	Wang et al.	2012/0245941	A1 9/2012 Cheyer
	2012/0042014	A1	2/2012	Desai et al.	2012/0245944	A1 9/2012 Gruber et al.
	2012/0042343	A1	2/2012	Laligand et al.	2012/0246064	A1 9/2012 Balkow
	2012/0053815	A1	3/2012	Montanari et al.	2012/0250858	A1 10/2012 Iqbal et al.
	2012/0053829	A1	3/2012	Agarwal et al.	2012/0252367	A1 10/2012 Gaglio et al.
	2012/0053945	A1	3/2012	Gupta et al.	2012/0252540	A1 10/2012 Kirigaya
	2012/0056815	A1	3/2012	Mehra	2012/0253785	A1 10/2012 Hamid et al.
	2012/0059655	A1	3/2012	Cartales	2012/0254143	A1 10/2012 Varma et al.
	2012/0059813	A1	3/2012	Sejnoha et al.	2012/0254152	A1 10/2012 Park et al.
	2012/0062473	A1	3/2012	Xiao et al.	2012/0254290	A1 10/2012 Naaman
	2012/0066212	A1	3/2012	Jennings	2012/0259615	A1 10/2012 Morin et al.
	2012/0066581	A1	3/2012	Spalink	2012/0265528	A1 10/2012 Gruber et al.
	2012/0075054	A1	3/2012	Ge et al.	2012/0265535	A1 10/2012 Bryant-Rich et al.
	2012/0078611	A1	3/2012	Soltani et al.	2012/0265806	A1 10/2012 Blanchflower et al.
	2012/0078624	A1	3/2012	Yook et al.	2012/0271625	A1 10/2012 Bernard
	2012/0078627	A1	3/2012	Wagner	2012/0271634	A1 10/2012 Lenke
	2012/0078635	A1	3/2012	Rothkopf et al.	2012/0271635	A1 10/2012 Ljolje
	2012/0082317	A1	4/2012	Pance et al.	2012/0271640	A1 10/2012 Basir
	2012/0083286	A1	4/2012	Kim et al.	2012/0271676	A1 10/2012 Aravamudan et al.
	2012/0084086	A1	4/2012	Gilbert et al.	2012/0275377	A1 11/2012 Lehane et al.
	2012/0084634	A1	4/2012	Wong et al.	2012/0284015	A1 11/2012 Drewes
	2012/0088219	A1	4/2012	Briscoe et al.	2012/0284027	A1 11/2012 Mallett et al.
	2012/0089331	A1	4/2012	Schmidt et al.	2012/0290291	A1 11/2012 Shelley et al.
	2012/0108166	A1	5/2012	Hymel	2012/0290300	A1 11/2012 Lee et al.
	2012/0108221	A1	5/2012	Thomas et al.	2012/0295708	A1 11/2012 Hernandez-Abrego et al.
	2012/0116770	A1	5/2012	Chen et al.	2012/0296649	A1 11/2012 Bansal et al.
	2012/0117499	A1	5/2012	Mori et al.	2012/0296654	A1 11/2012 Hendrickson et al.
	2012/0124126	A1	5/2012	Alcazar et al.	2012/0296891	A1 11/2012 Rangan
	2012/0128322	A1	5/2012	Shaffer et al.	2012/0297348	A1 11/2012 Santoro
	2012/0130709	A1	5/2012	Bocchieri et al.	2012/0303369	A1 11/2012 Brush et al.
	2012/0136572	A1	5/2012	Norton	2012/0303371	A1 11/2012 Labsky et al.
	2012/0136855	A1	5/2012	Ni et al.	2012/0304124	A1 11/2012 Chen et al.
	2012/0136985	A1	5/2012	Popescu et al.	2012/0309363	A1 12/2012 Gruber et al.
	2012/0137367	A1	5/2012	Dupont et al.	2012/0310642	A1 12/2012 Cao et al.
	2012/0149342	A1	6/2012	Cohen et al.	2012/0310649	A1 12/2012 Cannistraro et al.
	2012/0149394	A1	6/2012	Singh et al.	2012/0310652	A1 12/2012 O'Sullivan
					2012/0310922	A1 12/2012 Johnson et al.
					2012/0311478	A1 12/2012 Van Os et al.
					2012/0311583	A1 12/2012 Gruber et al.
					2012/0311584	A1 12/2012 Gruber et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0311585	A1	12/2012	Gruber et al.	2013/0110518	A1	5/2013	Gruber et al.
2012/0316862	A1	12/2012	Sultan et al.	2013/0110519	A1	5/2013	Cheyser et al.
2012/0316875	A1	12/2012	Nyquist et al.	2013/0110520	A1	5/2013	Cheyser et al.
2012/0316878	A1	12/2012	Singleton et al.	2013/0110943	A1	5/2013	Menon et al.
2012/0317194	A1	12/2012	Tian	2013/0111330	A1	5/2013	Staikos et al.
2012/0317498	A1	12/2012	Logan et al.	2013/0111348	A1	5/2013	Gruber et al.
2012/0321112	A1	12/2012	Schubert et al.	2013/0111487	A1	5/2013	Cheyser et al.
2012/0324391	A1	12/2012	Tocci et al.	2013/0111581	A1	5/2013	Griffin et al.
2012/0327009	A1	12/2012	Fleizach	2013/0115927	A1	5/2013	Gruber et al.
2012/0329529	A1	12/2012	van der Raadt	2013/0117022	A1	5/2013	Chen et al.
2012/0330660	A1	12/2012	Jaiswal	2013/0124189	A1	5/2013	Baldwin et al.
2012/0330661	A1	12/2012	Lindahl	2013/0132084	A1	5/2013	Stonehocker et al.
2012/0330990	A1	12/2012	Chen et al.	2013/0132089	A1	5/2013	Fanty et al.
2013/0002716	A1	1/2013	Walker et al.	2013/0132871	A1	5/2013	Zeng et al.
2013/0005405	A1	1/2013	Prociw	2013/0141551	A1	6/2013	Kim
2013/0006633	A1	1/2013	Grokop et al.	2013/0142317	A1	6/2013	Reynolds
2013/0006637	A1	1/2013	Kanevsky et al.	2013/0142345	A1	6/2013	Waldmann
2013/0006638	A1	1/2013	Lindahl	2013/0144594	A1	6/2013	Bangalore et al.
2013/0007648	A1	1/2013	Gannon et al.	2013/0144616	A1	6/2013	Bangalore et al.
2013/0010575	A1	1/2013	He et al.	2013/0151339	A1	6/2013	Kim et al.
2013/0013313	A1	1/2013	Shechtman et al.	2013/0152092	A1	6/2013	Yadgar et al.
2013/0013319	A1	1/2013	Grant et al.	2013/0154811	A1	6/2013	Ferren et al.
2013/0018659	A1	1/2013	Chi	2013/0157629	A1	6/2013	Lee et al.
2013/0024576	A1	1/2013	Dishneau et al.	2013/0158977	A1	6/2013	Senior
2013/0027875	A1	1/2013	Zhu et al.	2013/0165232	A1	6/2013	Nelson et al.
2013/0030787	A1	1/2013	Cancedda et al.	2013/0166303	A1	6/2013	Chang et al.
2013/0030789	A1	1/2013	Dalce	2013/0166442	A1	6/2013	Nakajima et al.
2013/0030804	A1	1/2013	Zavaliagko et al.	2013/0170738	A1	7/2013	Capuzzo et al.
2013/0030815	A1	1/2013	Madhvanath et al.	2013/0172022	A1	7/2013	Seymour et al.
2013/0030955	A1	1/2013	David	2013/0176244	A1	7/2013	Yamamoto et al.
2013/0031162	A1	1/2013	Willis et al.	2013/0176592	A1	7/2013	Sasaki
2013/0031476	A1	1/2013	Coin et al.	2013/0179440	A1	7/2013	Gordon
2013/0033643	A1	2/2013	Kim et al.	2013/0183944	A1	7/2013	Mozer et al.
2013/0035086	A1	2/2013	Chardon et al.	2013/0185059	A1	7/2013	Riccardi et al.
2013/0035942	A1	2/2013	Kim et al.	2013/0185074	A1	7/2013	Gruber et al.
2013/0035961	A1	2/2013	Yegnanarayanan	2013/0185081	A1	7/2013	Cheyser et al.
2013/0041647	A1	2/2013	Ramerth et al.	2013/0185336	A1	7/2013	Singh et al.
2013/0041654	A1	2/2013	Walker et al.	2013/0187850	A1	7/2013	Schulz et al.
2013/0041661	A1	2/2013	Lee et al.	2013/0191117	A1	7/2013	Atti et al.
2013/0041665	A1	2/2013	Jang et al.	2013/0197911	A1	8/2013	Wei et al.
2013/0041968	A1	2/2013	Cohen et al.	2013/0204813	A1	8/2013	Master et al.
2013/0046544	A1	2/2013	Kay et al.	2013/0204897	A1	8/2013	McDougall
2013/0050089	A1	2/2013	Neels et al.	2013/0207898	A1	8/2013	Sullivan et al.
2013/0054550	A1	2/2013	Bolohan	2013/0218553	A1	8/2013	Fujii et al.
2013/0054609	A1	2/2013	Rajput et al.	2013/0218560	A1	8/2013	Hsiao et al.
2013/0054613	A1	2/2013	Bishop	2013/0222249	A1	8/2013	Pasquero et al.
2013/0054675	A1	2/2013	Jenkins et al.	2013/0225128	A1	8/2013	Gomar
2013/0054706	A1	2/2013	Graham et al.	2013/0231917	A1	9/2013	Naik
2013/0055099	A1	2/2013	Yao et al.	2013/0234947	A1	9/2013	Kristensson et al.
2013/0055147	A1	2/2013	Vasudev et al.	2013/0235987	A1	9/2013	Arroniz-Escobar et al.
2013/0063611	A1	3/2013	Papakipos et al.	2013/0238647	A1	9/2013	Thompson
2013/0066832	A1	3/2013	Sheehan et al.	2013/0244615	A1	9/2013	Miller et al.
2013/0067307	A1	3/2013	Tian et al.	2013/0246048	A1	9/2013	Nagase et al.
2013/0073286	A1	3/2013	Bastea-Forte et al.	2013/0246050	A1	9/2013	Yu et al.
2013/0073346	A1	3/2013	Chun et al.	2013/0246329	A1	9/2013	Pasquero et al.
2013/0080152	A1	3/2013	Brun et al.	2013/0253911	A1	9/2013	Petri et al.
2013/0080162	A1	3/2013	Chang et al.	2013/0253912	A1	9/2013	Medlock et al.
2013/0080167	A1	3/2013	Mozer	2013/0275117	A1	10/2013	Winer
2013/0080177	A1	3/2013	Chen	2013/0275138	A1	10/2013	Gruber et al.
2013/0080251	A1	3/2013	Dempski	2013/0275164	A1	10/2013	Gruber et al.
2013/0085755	A1	4/2013	Bringert et al.	2013/0275199	A1	10/2013	Proctor, Jr. et al.
2013/0085761	A1	4/2013	Bringert et al.	2013/0275625	A1	10/2013	Taivalsaari et al.
2013/0090921	A1	4/2013	Liu et al.	2013/0275875	A1	10/2013	Gruber et al.
2013/0091090	A1	4/2013	Spivack et al.	2013/0275899	A1	10/2013	Schubert et al.
2013/0095805	A1	4/2013	Lebeau et al.	2013/0283168	A1	10/2013	Brown et al.
2013/0096909	A1	4/2013	Brun et al.	2013/0289991	A1	10/2013	Eshwar et al.
2013/0096917	A1	4/2013	Edgar et al.	2013/0289993	A1	10/2013	Rao et al.
2013/0097566	A1	4/2013	Berglund	2013/0289994	A1	10/2013	Newman et al.
2013/0097682	A1	4/2013	Zeljko et al.	2013/0291015	A1	10/2013	Pan
2013/0100268	A1	4/2013	Mihailidis et al.	2013/0297317	A1	11/2013	Lee et al.
2013/0103391	A1	4/2013	Millmore et al.	2013/0297319	A1	11/2013	Kim
2013/0103405	A1	4/2013	Namba et al.	2013/0297348	A1	11/2013	Cardoza et al.
2013/0106742	A1	5/2013	Lee et al.	2013/0300645	A1	11/2013	Fedorov
2013/0110505	A1	5/2013	Gruber et al.	2013/0303106	A1	11/2013	Martin
2013/0110515	A1	5/2013	Guzzoni et al.	2013/0304479	A1	11/2013	Teller et al.
				2013/0304758	A1	11/2013	Gruber et al.
				2013/0304815	A1	11/2013	Puente et al.
				2013/0305119	A1	11/2013	Kern et al.
				2013/0307855	A1	11/2013	Lamb et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0307997	A1	11/2013	O'Keefe et al.	2014/0134983	A1	5/2014	Jung et al.
2013/0308922	A1	11/2013	Sano et al.	2014/0135036	A1	5/2014	Bonanni et al.
2013/0311997	A1	11/2013	Gruber et al.	2014/0136187	A1	5/2014	Wolverton et al.
2013/0316746	A1	11/2013	Miller et al.	2014/0136195	A1	5/2014	Abdossalami et al.
2013/0322634	A1	12/2013	Bennett et al.	2014/0136212	A1	5/2014	Kwon et al.
2013/0325436	A1	12/2013	Wang et al.	2014/0136946	A1	5/2014	Matas
2013/0325443	A1	12/2013	Begeja et al.	2014/0142923	A1	5/2014	Jones et al.
2013/0325447	A1	12/2013	Levien et al.	2014/0142935	A1	5/2014	Lindahl et al.
2013/0325448	A1	12/2013	Levien et al.	2014/0143550	A1	5/2014	Ganong, III et al.
2013/0325481	A1	12/2013	Van Os et al.	2014/0143721	A1	5/2014	Suzuki et al.
2013/0325484	A1	12/2013	Chakladar et al.	2014/0146200	A1	5/2014	Scott et al.
2013/0325967	A1	12/2013	Parks et al.	2014/0152577	A1	6/2014	Yuen et al.
2013/0325979	A1	12/2013	Mansfield et al.	2014/0155031	A1	6/2014	Lee et al.
2013/0329023	A1	12/2013	Suplee, III et al.	2014/0157422	A1	6/2014	Livshits et al.
2013/0331127	A1	12/2013	Sabatelli et al.	2014/0163951	A1	6/2014	Nikoulina et al.
2013/0332159	A1	12/2013	Federighi et al.	2014/0163953	A1	6/2014	Parikh
2013/0332162	A1	12/2013	Keen	2014/0163954	A1	6/2014	Joshi et al.
2013/0332164	A1	12/2013	Nalk	2014/0163981	A1	6/2014	Cook et al.
2013/0332168	A1	12/2013	Kim et al.	2014/0164476	A1	6/2014	Thomson
2013/0332400	A1	12/2013	González	2014/0164532	A1	6/2014	Lynch et al.
2013/0339256	A1	12/2013	Shroff	2014/0164533	A1	6/2014	Lynch et al.
2013/0346068	A1	12/2013	Solem et al.	2014/0169795	A1	6/2014	Clough
2013/0346347	A1	12/2013	Patterson et al.	2014/0173460	A1	6/2014	Kim
2014/0006012	A1	1/2014	Zhou et al.	2014/0180499	A1	6/2014	Cooper et al.
2014/0006025	A1	1/2014	Krishnan et al.	2014/0180689	A1	6/2014	Kim et al.
2014/0006027	A1	1/2014	Kim et al.	2014/0180697	A1	6/2014	Torok et al.
2014/0006153	A1	1/2014	Thangam et al.	2014/0188477	A1	7/2014	Zhang
2014/0012580	A1	1/2014	Ganong et al.	2014/0195230	A1	7/2014	Han et al.
2014/0012586	A1	1/2014	Rubin et al.	2014/0195233	A1	7/2014	Bapat
2014/0019116	A1	1/2014	Lundberg et al.	2014/0195244	A1	7/2014	Cha et al.
2014/0019133	A1	1/2014	Bao et al.	2014/0195251	A1	7/2014	Zeinstra et al.
2014/0028735	A1	1/2014	Williams et al.	2014/0195252	A1	7/2014	Gruber et al.
2014/0032453	A1	1/2014	Eustice et al.	2014/0198048	A1	7/2014	Unruh et al.
2014/0033071	A1	1/2014	Gruber et al.	2014/0203939	A1	7/2014	Harrington et al.
2014/0035823	A1	2/2014	Khoe et al.	2014/0207439	A1	7/2014	Venkatapathy et al.
2014/0039894	A1	2/2014	Shostak	2014/0207446	A1	7/2014	Klein et al.
2014/0040274	A1	2/2014	Aravamudan et al.	2014/0207468	A1	7/2014	Bartnik
2014/0040748	A1	2/2014	Lemay et al.	2014/0207582	A1	7/2014	Flinn et al.
2014/0040801	A1	2/2014	Patel et al.	2014/0214429	A1	7/2014	Pantel
2014/0040918	A1	2/2014	Li et al.	2014/0214537	A1	7/2014	Yoo et al.
2014/0046934	A1	2/2014	Zhou et al.	2014/0218372	A1	8/2014	Missig et al.
2014/0047001	A1	2/2014	Phillips et al.	2014/0222436	A1	8/2014	Binder et al.
2014/0052680	A1	2/2014	Nitz et al.	2014/0222678	A1	8/2014	Sheets et al.
2014/0052791	A1	2/2014	Chakra et al.	2014/0223377	A1	8/2014	Shaw et al.
2014/0053082	A1	2/2014	Park et al.	2014/0223481	A1	8/2014	Fundament
2014/0053210	A1	2/2014	Cheong et al.	2014/0230055	A1	8/2014	Boehl
2014/0057610	A1	2/2014	Olincy et al.	2014/0232656	A1	8/2014	Pasquero et al.
2014/0059030	A1	2/2014	Hakkani-Tur et al.	2014/0236595	A1	8/2014	Gray
2014/0067361	A1	3/2014	Nikoulina et al.	2014/0236986	A1	8/2014	Guzman
2014/0067371	A1	3/2014	Liensberger	2014/0237042	A1	8/2014	Ahmed et al.
2014/0067402	A1	3/2014	Kim	2014/0244248	A1	8/2014	Arisoy et al.
2014/0068751	A1	3/2014	Last et al.	2014/0244254	A1	8/2014	Ju et al.
2014/0074466	A1	3/2014	Sharifi et al.	2014/0244257	A1	8/2014	Colibro et al.
2014/0074470	A1	3/2014	Jansche et al.	2014/0244258	A1	8/2014	Song et al.
2014/0074472	A1	3/2014	Lin et al.	2014/0244263	A1	8/2014	Pontual et al.
2014/0074815	A1	3/2014	Plimton	2014/0244268	A1	8/2014	Abdelsamie et al.
2014/0078065	A1	3/2014	Akkok et al.	2014/0244271	A1	8/2014	Lindahl
2014/0080428	A1	3/2014	Rhoads et al.	2014/0244712	A1	8/2014	Walters et al.
2014/0081633	A1	3/2014	Badaskar et al.	2014/0245140	A1	8/2014	Brown et al.
2014/0082501	A1	3/2014	Bae et al.	2014/0247383	A1	9/2014	Dave et al.
2014/0086458	A1	3/2014	Rogers et al.	2014/0247926	A1	9/2014	Gainsboro et al.
2014/0087711	A1	3/2014	Geyer et al.	2014/0249817	A1	9/2014	Hart et al.
2014/0088961	A1	3/2014	Woodward et al.	2014/0249821	A1	9/2014	Kennewick et al.
2014/0095171	A1	4/2014	Lynch et al.	2014/0250046	A1	9/2014	Winn et al.
2014/0095172	A1	4/2014	Cabaco et al.	2014/0257815	A1	9/2014	Zhao et al.
2014/0095173	A1	4/2014	Lynch et al.	2014/0258857	A1	9/2014	Dykstra-Erickson et al.
2014/0096209	A1	4/2014	Saraf et al.	2014/0267022	A1	9/2014	Kim
2014/0098247	A1	4/2014	Rao et al.	2014/0267599	A1	9/2014	Drouin et al.
2014/0108017	A1	4/2014	Mason et al.	2014/0272821	A1	9/2014	Pitschel et al.
2014/0114554	A1	4/2014	Lagassey	2014/0274203	A1	9/2014	Ganong et al.
2014/0118155	A1	5/2014	Bowers et al.	2014/0274211	A1	9/2014	Sejnoha et al.
2014/0122059	A1	5/2014	Patel et al.	2014/0278343	A1	9/2014	Tran
2014/0122086	A1	5/2014	Kapur et al.	2014/0278349	A1	9/2014	Grieves et al.
2014/0122136	A1	5/2014	Jayanthi	2014/0278379	A1	9/2014	Coccaro et al.
2014/0122153	A1	5/2014	Truitt	2014/0278390	A1	9/2014	Kingsbury et al.
				2014/0278391	A1	9/2014	Braho et al.
				2014/0278406	A1	9/2014	Tsumura et al.
				2014/0278413	A1	9/2014	Pitschel et al.
				2014/0278429	A1	9/2014	Ganong, III

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0278435	A1	9/2014	Ganong et al.	2015/0058785	A1	2/2015	Ookawara
2014/0278443	A1	9/2014	Gunn et al.	2015/0065200	A1	3/2015	Namgung et al.
2014/0278513	A1	9/2014	Prakash et al.	2015/0066494	A1	3/2015	Salvador et al.
2014/0280138	A1	9/2014	Li et al.	2015/0066496	A1	3/2015	Deoras et al.
2014/0280292	A1	9/2014	Skinder	2015/0066506	A1	3/2015	Romano et al.
2014/0280353	A1	9/2014	Delaney et al.	2015/0066516	A1	3/2015	Nishikawa et al.
2014/0280450	A1	9/2014	Luna	2015/0067485	A1	3/2015	Kim et al.
2014/0281983	A1	9/2014	Xian et al.	2015/0067822	A1	3/2015	Randall
2014/0282003	A1	9/2014	Gruber et al.	2015/0073788	A1	3/2015	Allauzen et al.
2014/0282007	A1	9/2014	Fleizach	2015/0073804	A1	3/2015	Senior et al.
2014/0282045	A1	9/2014	Ayanam et al.	2015/0074524	A1	3/2015	Nicholson et al.
2014/0282201	A1	9/2014	Pasquero et al.	2015/0082229	A1	3/2015	Ouyang et al.
2014/0282586	A1	9/2014	Shear et al.	2015/0088511	A1	3/2015	Bharadwaj et al.
2014/0282743	A1	9/2014	Howard et al.	2015/0088514	A1	3/2015	Typrin
2014/0288990	A1	9/2014	Moore et al.	2015/0088522	A1	3/2015	Hendrickson et al.
2014/0297267	A1	10/2014	Spencer et al.	2015/0088523	A1	3/2015	Schuster
2014/0297281	A1	10/2014	Togawa et al.	2015/0095031	A1	4/2015	Conkie et al.
2014/0297284	A1	10/2014	Gruber et al.	2015/0095278	A1	4/2015	Flinn et al.
2014/0297288	A1	10/2014	Yu et al.	2015/0100316	A1	4/2015	Williams et al.
2014/0304605	A1	10/2014	Ohmura et al.	2015/0100537	A1	4/2015	Grieves et al.
2014/0310001	A1	10/2014	Kalns et al.	2015/0100983	A1	4/2015	Pan
2014/0310002	A1	10/2014	Nitz et al.	2015/0106093	A1	4/2015	Weeks et al.
2014/0316585	A1	10/2014	Boesveld et al.	2015/0113407	A1	4/2015	Hoffert et al.
2014/0317502	A1	10/2014	Brown et al.	2015/0120723	A1	4/2015	Deshmukh et al.
2014/0324884	A1	10/2014	Lindahl et al.	2015/0121216	A1	4/2015	Brown et al.
2014/0337048	A1	11/2014	Brown et al.	2015/0127350	A1	5/2015	Agiomyrgiannakis
2014/0337266	A1	11/2014	Wolverton et al.	2015/0133109	A1	5/2015	Freeman et al.
2014/0337371	A1	11/2014	Li	2015/0134334	A1	5/2015	Sachidanandam et al.
2014/0337438	A1	11/2014	Govande et al.	2015/0135085	A1	5/2015	Shoham et al.
2014/0337751	A1	11/2014	Linn et al.	2015/0135123	A1	5/2015	Carr et al.
2014/0337814	A1	11/2014	Kalns et al.	2015/0142420	A1	5/2015	Sarikaya et al.
2014/0342762	A1	11/2014	Hajdu et al.	2015/0142438	A1	5/2015	Dai et al.
2014/0344627	A1	11/2014	Schaub et al.	2015/0142447	A1	5/2015	Kennewick et al.
2014/0344687	A1	11/2014	Durham et al.	2015/0142851	A1	5/2015	Gupta et al.
2014/0350924	A1	11/2014	Zurek et al.	2015/0148013	A1	5/2015	Baldwin et al.
2014/0350933	A1	11/2014	Bak et al.	2015/0149177	A1	5/2015	Kalns et al.
2014/0351741	A1	11/2014	Medlock et al.	2015/0149182	A1	5/2015	Kalns et al.
2014/0351760	A1	11/2014	Skory et al.	2015/0149354	A1	5/2015	Mccoy
2014/0358519	A1	12/2014	Mirkin et al.	2015/0149469	A1	5/2015	Xu et al.
2014/0358523	A1	12/2014	Sheth et al.	2015/0154185	A1	6/2015	Waibel
2014/0365209	A1	12/2014	Evermann	2015/0161370	A1	6/2015	North et al.
2014/0365214	A1	12/2014	Bayley	2015/0161989	A1	6/2015	Hsu et al.
2014/0365216	A1	12/2014	Gruber et al.	2015/0169336	A1	6/2015	Harper et al.
2014/0365226	A1	12/2014	Sinha	2015/0170664	A1	6/2015	Doherty et al.
2014/0365227	A1	12/2014	Cash et al.	2015/0172463	A1	6/2015	Quast et al.
2014/0365407	A1	12/2014	Brown et al.	2015/0178388	A1	6/2015	Winnemoeller et al.
2014/0365880	A1	12/2014	Bellegarda	2015/0179176	A1	6/2015	Ryu et al.
2014/0365885	A1	12/2014	Carson et al.	2015/0185964	A1	7/2015	Stout
2014/0365895	A1	12/2014	Paulson et al.	2015/0186012	A1	7/2015	Coleman et al.
2014/0370817	A1	12/2014	Luna	2015/0186110	A1	7/2015	Kannan
2014/0370841	A1	12/2014	Roberts et al.	2015/0186155	A1	7/2015	Brown et al.
2014/0372112	A1	12/2014	Xue et al.	2015/0186156	A1	7/2015	Brown et al.
2014/0372356	A1	12/2014	Bilal et al.	2015/0186351	A1	7/2015	Hicks et al.
2014/0372931	A1	12/2014	Zhai et al.	2015/0187355	A1	7/2015	Parkinson et al.
2014/0379334	A1	12/2014	Fry	2015/0187369	A1	7/2015	Dadu et al.
2015/0003797	A1	1/2015	Schmidt	2015/0189362	A1	7/2015	Lee et al.
2015/0006148	A1	1/2015	Goldszmit et al.	2015/0193379	A1	7/2015	Mehta
2015/0006157	A1	1/2015	Andrade Silva et al.	2015/0193391	A1	7/2015	Khvostichenko et al.
2015/0006178	A1	1/2015	Peng et al.	2015/0193392	A1	7/2015	Greenblatt et al.
2015/0006199	A1	1/2015	Snider et al.	2015/0194152	A1	7/2015	Katuri et al.
2015/0012271	A1	1/2015	Peng et al.	2015/0195379	A1	7/2015	Zhang et al.
2015/0019219	A1	1/2015	Tzirkel-hancock et al.	2015/0195606	A1	7/2015	McDevitt
2015/0019221	A1	1/2015	Lee et al.	2015/0199077	A1	7/2015	Zuger et al.
2015/0031416	A1	1/2015	Wells et al.	2015/0199960	A1	7/2015	Huo et al.
2015/0033219	A1	1/2015	Breiner et al.	2015/0199965	A1	7/2015	Leak et al.
2015/0039292	A1	2/2015	Suleman et al.	2015/0199967	A1	7/2015	Reddy et al.
2015/0039299	A1	2/2015	Weinstein et al.	2015/0201064	A1	7/2015	Bells et al.
2015/0039305	A1	2/2015	Huang	2015/0205858	A1	7/2015	Xie et al.
2015/0040012	A1	2/2015	Faaborg et al.	2015/0208226	A1	7/2015	Kuusilinnä et al.
2015/0045003	A1	2/2015	Vora et al.	2015/0212791	A1	7/2015	Kumar et al.
2015/0045068	A1	2/2015	Soffer et al.	2015/0213796	A1	7/2015	Waltermann et al.
2015/0046537	A1	2/2015	Rakib	2015/0220507	A1	8/2015	Mohajer et al.
2015/0050633	A1	2/2015	Christmas et al.	2015/0221304	A1	8/2015	Stewart
2015/0058013	A1	2/2015	Pakhomov et al.	2015/0221307	A1	8/2015	Shah et al.
2015/0058018	A1	2/2015	Georges et al.	2015/0227633	A1	8/2015	Shapira
				2015/0228281	A1	8/2015	Raniere
				2015/0234636	A1	8/2015	Barnes, Jr.
				2015/0234800	A1	8/2015	Patrick et al.
				2015/0242091	A1	8/2015	Lu et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0243278	A1	8/2015	Kibre et al.	2016/0055422	A1	2/2016	Li
2015/0243283	A1	8/2015	Halash et al.	2016/0062605	A1	3/2016	Agarwal et al.
2015/0245154	A1	8/2015	Dadu et al.	2016/0063998	A1	3/2016	Krishnamoorthy et al.
2015/0248651	A1	9/2015	Akutagawa et al.	2016/0070581	A1	3/2016	Soon-Shiong
2015/0248886	A1	9/2015	Sarikaya et al.	2016/0071516	A1	3/2016	Lee et al.
2015/0254057	A1	9/2015	Klein et al.	2016/0071521	A1	3/2016	Haughay
2015/0254058	A1	9/2015	Klein et al.	2016/0077794	A1	3/2016	Kim et al.
2015/0254333	A1	9/2015	Fife et al.	2016/0078860	A1	3/2016	Paulik et al.
2015/0255071	A1	9/2015	Chiba	2016/0080165	A1	3/2016	Ehsani et al.
2015/0256873	A1	9/2015	Klein et al.	2016/0086116	A1	3/2016	Rao et al.
2015/0261496	A1	9/2015	Faaborg et al.	2016/0091967	A1	3/2016	Prokofieva et al.
2015/0269139	A1	9/2015	McAteer et al.	2016/0092447	A1	3/2016	Venkataraman et al.
2015/0277574	A1	10/2015	Jain et al.	2016/0093291	A1	3/2016	Kim
2015/0278370	A1	10/2015	Stratvert et al.	2016/0093298	A1	3/2016	Naik et al.
2015/0279358	A1	10/2015	Kingsbury et al.	2016/0093301	A1	3/2016	Bellegarda et al.
2015/0279360	A1	10/2015	Mengibar et al.	2016/0093304	A1	3/2016	Kim et al.
2015/0281380	A1	10/2015	Wang et al.	2016/0094979	A1	3/2016	Naik et al.
2015/0286627	A1	10/2015	Chang et al.	2016/0117386	A1	4/2016	Ajmera et al.
2015/0287401	A1	10/2015	Lee et al.	2016/0119338	A1	4/2016	Cheyre
2015/0287409	A1	10/2015	Jang	2016/0125048	A1	5/2016	Hamada
2015/0288629	A1	10/2015	Choi et al.	2016/0125071	A1	5/2016	Gabbai
2015/0294086	A1	10/2015	Kare et al.	2016/0132484	A1	5/2016	Nauze et al.
2015/0294516	A1	10/2015	Chiang	2016/0139662	A1	5/2016	Dabhade
2015/0302855	A1	10/2015	Kim et al.	2016/0147725	A1	5/2016	Patten et al.
2015/0302856	A1	10/2015	Kim et al.	2016/0148610	A1	5/2016	Kennewick, Jr. et al.
2015/0302857	A1	10/2015	Yamada	2016/0155442	A1	6/2016	Kannan et al.
2015/0309997	A1	10/2015	Lee et al.	2016/0155443	A1	6/2016	Khan et al.
2015/0310858	A1	10/2015	Li et al.	2016/0162456	A1	6/2016	Munro et al.
2015/0310862	A1	10/2015	Dauphin et al.	2016/0163312	A1	6/2016	Naik et al.
2015/0310879	A1	10/2015	Buchanan et al.	2016/0170966	A1	6/2016	Kolo
2015/0312182	A1	10/2015	Langholz	2016/0173960	A1	6/2016	Snibbe et al.
2015/0317069	A1	11/2015	Clements et al.	2016/0179462	A1	6/2016	Bjorkengren
2015/0317310	A1	11/2015	Eiche et al.	2016/0180844	A1	6/2016	Vanblon et al.
2015/0324041	A1	11/2015	Varley et al.	2016/0182410	A1	6/2016	Janakiraman et al.
2015/0324334	A1	11/2015	Lee et al.	2016/0188181	A1	6/2016	Smith
2015/0331664	A1	11/2015	Osawa et al.	2016/0188738	A1	6/2016	Gruber et al.
2015/0331711	A1	11/2015	Huang et al.	2016/0189717	A1	6/2016	Kannan et al.
2015/0332667	A1	11/2015	Mason	2016/0210981	A1	7/2016	Lee
2015/0339049	A1	11/2015	Kasemset et al.	2016/0212488	A1	7/2016	Os et al.
2015/0339391	A1	11/2015	Kang et al.	2016/0217784	A1	7/2016	Gelfenbeyn et al.
2015/0340040	A1	11/2015	Mun et al.	2016/0224540	A1	8/2016	Stewart et al.
2015/0340042	A1	11/2015	Sejnoha et al.	2016/0225372	A1	8/2016	Cheung et al.
2015/0341717	A1	11/2015	Song et al.	2016/0240187	A1	8/2016	Fleizach et al.
2015/0347086	A1	12/2015	Liedholm et al.	2016/0247061	A1	8/2016	Trask et al.
2015/0347381	A1	12/2015	Bellegarda	2016/0253312	A1	9/2016	Rhodes
2015/0347382	A1	12/2015	Dolfing et al.	2016/0259656	A1	9/2016	Sumner et al.
2015/0347385	A1	12/2015	Flor et al.	2016/0260431	A1	9/2016	Newendorp et al.
2015/0347393	A1	12/2015	Futrell et al.	2016/0260433	A1	9/2016	Sumner et al.
2015/0347733	A1	12/2015	Tsou et al.	2016/0260436	A1	9/2016	Lemay et al.
2015/0347985	A1	12/2015	Gross et al.	2016/0266871	A1	9/2016	Schmid et al.
2015/0348547	A1	12/2015	Paulik et al.	2016/0267904	A1	9/2016	Biadysy et al.
2015/0348548	A1	12/2015	Piernot et al.	2016/0275941	A1	9/2016	Bellegarda et al.
2015/0348549	A1	12/2015	Giuli et al.	2016/0275947	A1	9/2016	Li et al.
2015/0348551	A1	12/2015	Gruber et al.	2016/0282956	A1	9/2016	Ouyang et al.
2015/0348554	A1	12/2015	Orr et al.	2016/0284199	A1	9/2016	Dotan-Cohen et al.
2015/0350031	A1	12/2015	Burks et al.	2016/0286045	A1	9/2016	Shaltiel et al.
2015/0355879	A1	12/2015	Beckhardt et al.	2016/0299685	A1	10/2016	Zhai et al.
2015/0370531	A1	12/2015	Faaborg	2016/0299882	A1	10/2016	Hegerty et al.
2015/0370780	A1	12/2015	Wang et al.	2016/0299883	A1	10/2016	Zhu et al.
2015/0371639	A1	12/2015	Foerster et al.	2016/0307566	A1	10/2016	Bellegarda
2015/0371665	A1	12/2015	Naik et al.	2016/0314788	A1	10/2016	Jitkoff et al.
2015/0373183	A1	12/2015	Woolsey et al.	2016/0314792	A1	10/2016	Alvarez et al.
2015/0382047	A1	12/2015	Napolitano et al.	2016/0321261	A1	11/2016	Spasojevic et al.
2015/0382079	A1	12/2015	Lister et al.	2016/0322045	A1	11/2016	Hatfield et al.
2016/0004690	A1	1/2016	Bangalore et al.	2016/0322050	A1	11/2016	Wang et al.
2016/0014476	A1	1/2016	Caliendo, Jr. et al.	2016/0328893	A1	11/2016	Cordova et al.
2016/0019886	A1	1/2016	Hong	2016/0336007	A1	11/2016	Hanazawa
2016/0026258	A1	1/2016	Ou et al.	2016/0336010	A1	11/2016	Lindahl
2016/0027431	A1	1/2016	Kurzweil et al.	2016/0337299	A1	11/2016	Lane et al.
2016/0028666	A1	1/2016	Li	2016/0337301	A1	11/2016	Rollins et al.
2016/0029316	A1	1/2016	Mohan et al.	2016/0342685	A1	11/2016	Basu et al.
2016/0034811	A1	2/2016	Paulik et al.	2016/0351190	A1	12/2016	Binder et al.
2016/0042735	A1	2/2016	Vibbert et al.	2016/0357304	A1	12/2016	Hatori et al.
2016/0042748	A1	2/2016	Jain et al.	2016/0357728	A1	12/2016	Bellegarda et al.
2016/0048666	A1	2/2016	Dey et al.	2016/0357861	A1	12/2016	Carlhian et al.
				2016/0357870	A1	12/2016	Hentschel et al.
				2016/0358598	A1	12/2016	Williams et al.
				2016/0358600	A1	12/2016	Nallasamy et al.
				2016/0358619	A1	12/2016	Ramprashad et al.

(56)	References Cited			CN	101499156	A	8/2009
	U.S. PATENT DOCUMENTS			CN	101500041	A	8/2009
				CN	101535983	A	9/2009
				CN	101547396	A	9/2009
2016/0359771	A1	12/2016	Sridhar	CN	101557432	A	10/2009
2016/0360039	A1	12/2016	Sanghavi et al.	CN	101604521	A	12/2009
2016/0364378	A1	12/2016	Futrell et al.	CN	101632316	A	1/2010
2016/0371250	A1	12/2016	Rhodes	CN	101636736	A	1/2010
2016/0378747	A1	12/2016	Orr et al.	CN	101673544	A	3/2010
2016/0379641	A1	12/2016	Liu et al.	CN	101751387	A	6/2010
2017/0004824	A1	1/2017	Yoo et al.	CN	101847405	A	9/2010
2017/0013124	A1	1/2017	Havelka et al.	CN	101894547	A	11/2010
2017/0019987	A1	1/2017	Dragone et al.	CN	101939740	A	1/2011
2017/0031576	A1	2/2017	Saoji et al.	CN	101951553	A	1/2011
2017/0040002	A1	2/2017	Basson et al.	CN	102137193	A	7/2011
2017/0055895	A1	3/2017	Des Jardins et al.	CN	102160043	A	8/2011
2017/0060853	A1	3/2017	Lee et al.	CN	102246136	A	11/2011
2017/0068423	A1	3/2017	Napolitano et al.	CN	202035047	U	11/2011
2017/0068513	A1	3/2017	Stasior et al.	CN	202092650	U	12/2011
2017/0068670	A1	3/2017	Orr et al.	CN	102368256	A	3/2012
2017/0083179	A1	3/2017	Gruber et al.	CN	102498457	A	6/2012
2017/0091168	A1	3/2017	Bellegarda et al.	CN	102682771	A	9/2012
2017/0092270	A1	3/2017	Newendorp et al.	CN	102685295	A	9/2012
2017/0092278	A1	3/2017	Evermann et al.	CN	102693725	A	9/2012
2017/0105190	A1	4/2017	Logan et al.	CN	102792320	A	11/2012
2017/0116989	A1	4/2017	Yadgar et al.	CN	102917004	A	2/2013
2017/0132199	A1	5/2017	Vescovi et al.	CN	103035240	A	4/2013
2017/0140644	A1	5/2017	Hwang et al.	CN	104423625	A	3/2015
2017/0161018	A1	6/2017	Lemay et al.	DE	102008024258	A1	11/2009
2017/0169819	A1	6/2017	Mese et al.	EP	1892700	A1	2/2008
2017/0178619	A1	6/2017	Naik et al.	EP	1912205	A2	4/2008
2017/0178626	A1	6/2017	Gruber et al.	EP	1939860	A1	7/2008
2017/0180499	A1	6/2017	Gelfenbeyn et al.	EP	1944997	A2	7/2008
2017/0186429	A1	6/2017	Giuli et al.	EP	651543	B1	9/2008
2017/0193083	A1	7/2017	Bhatt et al.	EP	1909263	B1	1/2009
2017/0199874	A1	7/2017	Patel et al.	EP	1335620	B1	3/2009
2017/0227935	A1	8/2017	Su et al.	EP	2069895	A1	6/2009
2017/0230709	A1	8/2017	Van Os et al.	EP	2094032	A1	8/2009
2017/0242653	A1	8/2017	Lang et al.	EP	2096840	A1	9/2009
2017/0243468	A1	8/2017	Dotan-Cohen et al.	EP	2107553	A1	10/2009
2017/0256256	A1	9/2017	Wang et al.	EP	2109295	A1	10/2009
2017/0263248	A1	9/2017	Gruber et al.	EP	1720375	B1	7/2010
2017/0285915	A1	10/2017	Napolitano et al.	EP	2205010	A1	7/2010
2017/0316775	A1	11/2017	Le et al.	EP	2309491	A1	4/2011
2017/0316782	A1	11/2017	Haughay et al.	EP	2329348	AO	6/2011
2017/0323637	A1	11/2017	Naik	EP	2400373	A1	12/2011
2017/0345411	A1	11/2017	Raitio et al.	EP	2431842	A2	3/2012
2017/0352346	A1	12/2017	Paulik et al.	EP	2551784	A1	1/2013
2017/0357632	A1	12/2017	Pagallo et al.	EP	2555536	A1	2/2013
2017/0357633	A1	12/2017	Wang et al.	EP	2575128	A2	4/2013
2017/0357716	A1	12/2017	Bellegarda et al.	EP	2733598	A2	5/2014
2017/0358301	A1	12/2017	Raitio et al.	EP	2801890	A1	11/2014
2017/0358304	A1	12/2017	Castillo et al.	EP	2801972	A1	11/2014
2017/0358305	A1	12/2017	Kudurshian et al.	EP	2930715	A1	10/2015
2018/0007538	A1	1/2018	Naik et al.	EP	2938022	A1	10/2015
2018/0012596	A1	1/2018	Piernot et al.	EP	2940556	A1	11/2015
2018/0033431	A1	2/2018	Newendorp et al.	FR	2911201	A1	7/2008
2018/0090143	A1	3/2018	Saddler et al.	GB	2445436	A	7/2008
2018/0108346	A1	4/2018	Paulik et al.	GB	2445667	A	7/2008
				JP	2008-009120	A	1/2008
				JP	2008-21002	A	1/2008
				JP	2008-26381	A	2/2008
				JP	2008-39928	A	2/2008
CA	2666438	C	6/2013	JP	2008-58813	A	3/2008
CN	101162153	A	4/2008	JP	2008-064687	A	3/2008
CN	101174366	A	5/2008	JP	2008-90545	A	4/2008
CN	101179754	A	5/2008	JP	2008-97003	A	4/2008
CN	101183525	A	5/2008	JP	2008-134949	A	6/2008
CN	101188644	A	5/2008	JP	2008-526101	A	7/2008
CN	101228503	A	7/2008	JP	2008-185693	A	8/2008
CN	101233741	A	7/2008	JP	2008-198022	A	8/2008
CN	101246020	A	8/2008	JP	2008-217468	A	9/2008
CN	101271689	A	9/2008	JP	2008-228129	A	9/2008
CN	101277501	A	10/2008	JP	2008-233678	A	10/2008
CN	101297541	A	10/2008	JP	2008-236448	A	10/2008
CN	101325756	A	12/2008	JP	2008-252161	A	10/2008
CN	101416471	A	4/2009	JP	2008-268684	A	11/2008
CN	101427244	A	5/2009	JP	2008-269480	A	11/2008
CN	101448340	A	6/2009	JP	2008-271481	A	11/2008
CN	101453498	A	6/2009	JP			

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2008-275731	A	11/2008	KR	10-2009-0127961	A	12/2009
JP	2008-299221	A	12/2008	KR	10-2009-0129192	A	12/2009
JP	2009-503623	A	1/2009	KR	10-2010-0015958	A	2/2010
JP	2009-36999	A	2/2009	KR	10-2010-0048571	A	5/2010
JP	2009-505142	A	2/2009	KR	10-2010-0053149	A	5/2010
JP	2009-47920	A	3/2009	KR	10-2010-0119519	A	11/2010
JP	2009-069062	A	4/2009	KR	10-2011-0043644	A	4/2011
JP	2009-98490	A	5/2009	KR	10-1032792	B1	5/2011
JP	2009-110300	A	5/2009	KR	10-2011-0068490	A	6/2011
JP	2009-140444	A	6/2009	KR	10-2011-0072847	A	6/2011
JP	2009-186989	A	8/2009	KR	10-2011-0086492	A	7/2011
JP	2009-193448	A	8/2009	KR	10-2011-0100620	A	9/2011
JP	2009-193457	A	8/2009	KR	10-2011-0113414	A	10/2011
JP	2009-193532	A	8/2009	KR	10-2011-0115134	A	10/2011
JP	2009-205367	A	9/2009	KR	10-2012-0020164	A	3/2012
JP	2009-223840	A	10/2009	KR	10-2012-0031722	A	4/2012
JP	2009-294913	A	12/2009	KR	10-1178310	B1	8/2012
JP	2009-294946	A	12/2009	KR	10-2012-0120316	A	11/2012
JP	2010-66519	A	3/2010	KR	10-2012-0137435	A	12/2012
JP	2010-78979	A	4/2010	KR	10-2012-0137440	A	12/2012
JP	2010-108378	A	5/2010	KR	10-2012-0138826	A	12/2012
JP	2010-518526	A	5/2010	KR	10-2012-0139827	A	12/2012
JP	2010-157207	A	7/2010	KR	10-1193668	B1	12/2012
JP	2010-224236	A	10/2010	KR	10-2013-0035983	A	4/2013
JP	4563106	B2	10/2010	KR	10-1334342	B1	11/2013
JP	2010-535377	A	11/2010	KR	10-2013-0131252	A	12/2013
JP	2010-287063	A	12/2010	KR	10-2015-0043512	A	4/2015
JP	2011-33874	A	2/2011	KR	10-2016-0010523	A	1/2016
JP	2011-41026	A	2/2011	RU	2349970	C2	3/2009
JP	2011-45005	A	3/2011	RU	2353068	C2	4/2009
JP	2011-59659	A	3/2011	RU	2364917	C2	8/2009
JP	2011-81541	A	4/2011	TW	200801988	A	1/2008
JP	2011-525045	A	9/2011	TW	I301373	B	9/2008
JP	2011-238022	A	11/2011	TW	M348993	U	1/2009
JP	2011-250027	A	12/2011	TW	200943903	A	10/2009
JP	2012-014394	A	1/2012	TW	201018258	A	5/2010
JP	2012-089020	A	5/2012	TW	201027515	A1	7/2010
JP	2012-116442	A	6/2012	TW	201028996	A1	8/2010
JP	2012-147063	A	8/2012	TW	201110108	A1	3/2011
JP	2012-518847	A	8/2012	TW	2011-42823	A1	12/2011
JP	2013-37688	A	2/2013	TW	201227715	A1	7/2012
JP	2013-511214	A	3/2013	TW	201245989	A1	11/2012
JP	2013-73240	A	4/2013	TW	201312548	A1	3/2013
JP	2013-513315	A	4/2013	WO	2008/030970	A2	3/2008
JP	2013-080476	A	5/2013	WO	2008/071231	A1	6/2008
JP	2013-517566	A	5/2013	WO	2008/085742	A2	7/2008
JP	2013-134430	A	7/2013	WO	2008/098900	A2	8/2008
JP	2013-527947	A	7/2013	WO	2008/109835	A2	8/2008
JP	2013-156349	A	8/2013	WO	2008/120036	A1	10/2008
JP	2013-200423	A	10/2013	WO	2008/130095	A1	10/2008
JP	2013-205999	A	10/2013	WO	2008/140236	A1	11/2008
JP	2013-238936	A	11/2013	WO	2008/142472	A1	11/2008
JP	2014-10688	A	1/2014	WO	2008/153639	A1	12/2008
JP	2014-026629	A	2/2014	WO	2009/009240	A2	1/2009
JP	2014-72586	A	4/2014	WO	2009/016631	A2	2/2009
JP	2014-077969	A	5/2014	WO	2009/017280	A1	2/2009
JP	2014-124332	A	7/2014	WO	2009/075912	A1	6/2009
JP	2014-145842	A	8/2014	WO	2009/104126	A1	8/2009
JP	2014-150323	A	8/2014	WO	2009/156438	A1	12/2009
JP	2014-222514	A	11/2014	WO	2009/156978	A1	12/2009
JP	2015-41845	A	3/2015	WO	2010/054373	A2	5/2010
JP	2016-119615	A	6/2016	WO	2010/075623	A1	7/2010
KR	10-0801227	B1	2/2008	WO	2010/100937	A1	9/2010
KR	10-0810500	B1	3/2008	WO	2010/141802	A1	12/2010
KR	10-2008-0033070	A	4/2008	WO	2011/057346	A1	5/2011
KR	10-0819928	B1	4/2008	WO	2011/060106	A1	5/2011
KR	10-2008-0049647	A	6/2008	WO	2011/088053	A2	7/2011
KR	10-2008-0059332	A	6/2008	WO	2011/093025	A1	8/2011
KR	10-2008-0109322	A	12/2008	WO	2011/116309	A1	9/2011
KR	10-2009-0001716	A	1/2009	WO	2011/133543	A1	10/2011
KR	10-2009-0028464	A	3/2009	WO	2011/150730	A1	12/2011
KR	10-2009-0030117	A	3/2009	WO	2011/163350	A1	12/2011
KR	10-2009-0086805	A	8/2009	WO	2011/088053	A3	1/2012
KR	10-0920267	B1	10/2009	WO	2012/019637	A1	2/2012
KR	10-2009-0122944	A	12/2009	WO	2012/129231	A1	9/2012
				WO	2012/135157	A2	10/2012
				WO	2012/154317	A1	11/2012
				WO	2012/155079	A2	11/2012
				WO	2012/167168	A2	12/2012

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	2013/009578	A2	1/2013
WO	2013/022135	A1	2/2013
WO	2013/022223	A2	2/2013
WO	2013/048880	A1	4/2013
WO	2013/049358	A1	4/2013
WO	2013/169842	A2	11/2013
WO	2013/173504	A1	11/2013
WO	2013/173511	A2	11/2013
WO	2013/184953	A1	12/2013
WO	2013/184990	A1	12/2013
WO	2014/003138	A1	1/2014
WO	2014/022148	A1	2/2014
WO	2014/028797	A1	2/2014
WO	2014/031505	A1	2/2014
WO	2014/066352	A1	5/2014
WO	2014/078965	A1	5/2014
WO	2014/096506	A1	6/2014
WO	2014/138604	A1	9/2014
WO	2014/143959	A2	9/2014
WO	2014/144579	A1	9/2014
WO	2014/159581	A1	10/2014
WO	2014/197336	A1	12/2014
WO	2014/200728	A1	12/2014
WO	2014/204659	A2	12/2014
WO	2015/030796	A1	3/2015
WO	2015/041892	A1	3/2015
WO	2015/084659	A1	6/2015
WO	2015/094169	A1	6/2015
WO	2015/094369	A1	6/2015
WO	2015/099939	A1	7/2015
WO	2015/116151	A1	8/2015
WO	2015/151133	A1	10/2015
WO	2015/157013	A1	10/2015
WO	2015/183401	A1	12/2015
WO	2015/200207	A1	12/2015
WO	2016/028946	A1	2/2016
WO	2016/033257	A1	3/2016
WO	2016/057268	A1	4/2016
WO	2016/075081	A1	5/2016
WO	2016/144982	A1	9/2016
WO	2016/209444	A1	12/2016
WO	2017/044629	A1	3/2017
WO	2017/053311	A1	3/2017

OTHER PUBLICATIONS

"Alexa, Turn Up the Heat!", Smartthings Samsung [online], Available online at <https://web.archive.org/web/20160329142041/https://blog.smartthings.com/news/smartthingsupdates/alexa-turn-up-the-heat/>, Mar. 3, 2016, 3 pages.

Alfred App, "Alfred", available at <http://www.alfredapp.com/>, retrieved on Feb. 8, 2012, 5 pages.

Anania, Peter, "Amazon Echo with Horne Automation (Smartthings)", Available online at <https://www.youtube.com/watch?v=LMW6aXmsWNE>, Dec. 20, 2015, 1 page.

api.ai, "Android App Review—Speaktoit Assistant", Available at <https://www.youtube.com/watch?v=myE498nyfGw>, Mar. 30, 2011, 3 pages.

Apple Computer, "Knowledge Navigator", published by Apple Computer no later than 2008, as depicted in Exemplary Screenshots from video entitled 'Knowledge Navigator', 2008, 7 pages.

Apple, "VoiceOver", available at <http://www.apple.com/accessibility/voiceover/>, May 19, 2014, 3 pages.

Asakura et al., "What LG thinks; How the TV should be in the Living Room", HiVi, vol. 31, No. 7 (Jul. 2013), Stereo Sound Publishing, Inc., Jun. 17, 2013, pp. 68-71 (Official Copy Only). (See Communication under 37 CFR § 1.98(a) (3)).

"Ask Alexa—Things That Are Smart Wiki", Available online at http://thingsataresmart.wiki/index.php?title=Ask_Alexa&oldid=4283, [retrieved from internet on Aug. 2, 2017], Jun. 8, 2016, pp. 1-31.

Berry et al., "PTIME: Personalized Assistance for Calendaring",

ACM Transactions on Intelligent Systems and Technology, vol. 2, No. 4, Article 40, Jul. 2011, pp. 1-22.

Bertulucci, Jeff, "Google Adds Voice Search to Chrome Browser", PC World, Jun. 14, 2011, 5 pages.

Bocchieri et al., "Use of Geographical Meta-Data in ASR Language and Acoustic Models", IEEE International Conference on Acoustics Speech and Signal Processing, 2010, pp. 5118-5121.

Butcher, Mike, "EVI Arrives in Town to go Toe-to-Toe with Siri", TechCrunch, Jan. 23, 2012, 2 pages.

Caraballo et al., "Language Identification Based on a Discriminative Text Categorization Technique", Iberspeech 2012—VII Jornadas en Tecnologia del Habla and III Iberians! Tech Workshop, Nov. 21, 2012, pp. 1-10.

Castleos, "Whole House Voice Control Demonstration", available online at https://www.youtube.com/watch?v=9SRCoxrZ_W4, Jun. 2, 2012, 26 pages.

Chamberlain, Kim, "Quick Start Guide Natural Reader", available online at http://atrc.colostate.edu/files/quickstarts/Natural_Reader_Quick_Start_Guide., Apr. 2008, 5 pages.

Chen, Yi, "Multimedia Siri Finds and Plays Whatever You Ask For", PSFK Report, Feb. 9, 2012, 9 pages.

Cheyre, Adam, "About Adam Cheyre", available at <http://www.adam.cheyre.com/about.html>, retrieved on Sep. 17, 2012, 2 pages.

Choi et al., "Acoustic and Visual Signal based Context Awareness System for Mobile Application", IEEE Transactions on Consumer Electronics, vol. 57, No. 2, May 2011, pp. 738-746.

Colt, Sam, "Here's One Way Apple's Smartwatch Could Be Better Than Anything Else", Business Insider, Aug. 21, 2014, pp. 1-4.

Deedeuvu, "Amazon Echo Alarm Feature", Available online at <https://www.youtube.com/watch?v=fdjU8eRlk7c>, Feb. 16, 2015, 1 page.

"DIRECTV™ Voice", Now Part of the DIRECTV Mobile App for Phones, Sep. 18, 2013, 5 pages.

Elliott et al., "Annotation Suggestion and Search for Personal Multimedia Objects on the Web", CIVR, Jul. 7-9, 2008, pp. 75-84.

Erol et al., "Multimedia Clip Generation From Documents for Browsing on Mobile Devices", IEEE Transactions on Multimedia, vol. 10, No. 5, Aug. 2008, 13 pages.

Evi, "Meet Evi: The One Mobile Application that Provides Solutions for your Everyday Problems", Feb. 2012, 3 pages.

Exhibit 1, "Natural Language Interface Using Constrained Intermediate Dictionary of Results", List of Publications Manually Reviewed for the Search of U.S. Pat. No. 7,177,798, Mar. 22, 2013, 1 page.

Filipowicz, Luke, "How to use the Quick Type Keyboard in iOS 8", available online at <https://www.imore.com/comment/568232>, Oct. 11, 2014, pp. 1-17.

Findlater et al., "Beyond QWERTY: Augmenting Touch-Screen Keyboards with Multi-Touch Gestures for Non-Alphanumeric Input", CHI '12, Austin, Texas, USA, May 5-10, 2012, 4 pages.

Finkel et al., "Joint Parsing and Named Entity Recognition", Human Language Technologies: The 2009 Annual Conference of the North American Chapter of the ACL, Jun. 2009, pp. 326-334.

Gannes, Liz, "Alfred App Gives Personalized Restaurant Recommendations", AllThingsD, Jul. 18, 2011, pp. 1-3.

Gomez et al., "Mouth Gesture and Voice Command Based Robot Command Interface", IEEE International Conference on Robotics and Automation, May 12-17, 2009, pp. 333-338.

Gruber, Thomas R., et al., U.S. Appl. No. 61/186,414, filed Jun. 12, 2009 titled "System and Method for Semantic Auto-Completion" 13 pages (Copy Not Attached).

Gruber, Tom, "Big Think Small Screen: How Semantic Computing in the Cloud will Revolutionize the Consumer Experience on the Phone", Keynote Presentation at Web 3.0 Conference, Jan. 2010, 41 pages.

Gruber, Tom, "Despite Our Best Efforts, Ontologies are not the Problem", AAAI Spring Symposium, Available online at <http://tomgruber.org/writing/aaai-ss08.htm>, Mar. 2008, pp. 1-40.

Gruber, Tom, "Intelligence at the Interface: Semantic Technology and the Consumer Internet Experience", Presentation at Semantic Technologies Conference, Available online at <http://tomgruber.org/writing/semtech08.htm>, May 20, 2008, pp. 1-40.

(56)

References Cited**OTHER PUBLICATIONS**

- Gruber, Tom, "Siri, A Virtual Personal Assistant-Bringing Intelligence to the Interface", Semantic Technologies Conference, Jun. 16, 2009, 21 pages.
- Guay, Matthew, "Location-Driven Productivity with Task Ave", available at <<http://iphone.appstorm.net/reviews/productivity/location-driven-productivity-with-task-ave/>>, Feb. 19, 2011, 7 pages.
- Guim, Mark, "How to Set a Person-Based Reminder with Cortana", available at <<http://www.wpcentral.com/how-to-person-based-reminder-cortana>>, Apr. 26, 2014, 15 pages.
- Hardwar, Devindra, "Driving App Waze Builds its own Siri for Hands-Free Voice Control", Available online at <<http://venturebeat.com/2012/02/09/driving-app-waze-builds-its-own-siri-for-hands-free-voice-control/>>, retrieved on Feb. 9, 2012, 4 pages.
- Hashimoto, Yoshiyuki, "Simple Guide for iPhone Siri, Which Can Be Operated with Your Voice", Shuwa System Co., Ltd., vol. 1, Jul. 5, 2012, pp. 8, 130, 131.
- Headset Button Controller v7.3 APK Full APP Download for Android, Blackberry, iPhone, Jan. 27, 2014, 11 pages.
- Hear voice from Google translate, Available on URL:<https://www.youtube.com/watch?v=18AvMhFqD28>, Jan. 28, 2011, 1 page.
- id3.org, "id3v2.4.0-Frames", available at <<http://id3.org/id3v2.4.0-frames?action=print>>, retrieved on Jan. 22, 2015, 41 pages.
- Interactive Voice, available at <<http://www.helloivee.com/company/>>, retrieved on Feb. 10, 2014, 2 pages.
- Iowegian International, "FIR Filter Properties, DSPGuru, Digital Signal Processing Central", available at <<http://www.dspguru.com/dsp/faq/fir/properties>> retrieved on Jul. 28, 2010, 6 pages.
- Jawaid et al., "Machine Translation with Significant Word Reordering and Rich Target-Side Morphology", WDS'11 Proceedings of Contributed Papers, Part I, 2011, pp. 161-166.
- Jiang et al., "A Syllable-based Name Transliteration System", Proc. of the 2009 Named Entities Workshop, Aug. 7 2009, pp. 96-99.
- Jonsson et al., "Proximity-based Reminders Using Bluetooth", 2014 IEEE International Conference on Pervasive Computing and Communications Demonstrations, 2014, pp. 151-153.
- Jouvet et al., "Evaluating Grapheme-to-phoneme Converters in Automatic Speech Recognition Context", IEEE., 2012., pp. 4821-4824.
- Kane et al., "Slide Rule: Making Mobile Touch Screens Accessible to Blind People Using Multi-Touch Interaction Techniques", Assets, Oct. 13-15, 2008, pp. 73-80.
- Kazmucha, Allyson, "How to Send Map Locations Using iMessage", iMore.com, Available at <<http://www.imore.com/how-use-imessage-share-your-location-your-iphone>>, Aug. 2, 2012, 6 pages.
- Kickstarter, "Ivee Sleek: Wi-Fi Voice-Activated Assistant", available at <<https://www.kickstarter.com/projects/ivee/ivee-sleek-wi-fi-voice-activated-assistant>>, retrieved on Feb. 10, 2014, 13 pages.
- Knownav, "Knowledge Navigator", YouTube Video available at <http://www.youtube.com/watch?v=QRH8eimU_20>, Apr. 29, 2008, 1 page.
- Lewis, Cameron, "Task Ave for iPhone Review", Mac Life, Available at <http://www.maclife.com/article/reviews/task_ave_iphone_review>, Mar. 3, 2011, 5 pages.
- Mactech, "KeyStrokes 3.5 for Mac OS X Boosts Word Prediction", available at <<http://www.mactech.com/news/?p=1007129>>, retrieved on Jan. 7, 2008, 3 pages.
- Majerus, Wesley, "Cell Phone Accessibility for your Blind Child", Retrieved from the Internet <URL:https://web.archive.org/web/20100210001100/https://nfb.org/images/nfb/publications/fr/fr28/3/fr280314.htm>, 2010, pp. 1-5.
- Martins et al., "Extracting and Exploring the Geo-Temporal Semantics of Textual Resources", Semantic Computing, IEEE International Conference, 2008, pp. 1-9.
- Meet Ivee, Your Wi-Fi Voice Activated Assistant, available at <<http://www.helloivee.com/>>, retrieved on Feb. 10, 2014, 8 pages.
- Mel Scale, Wikipedia the Free Encyclopedia, Last modified on Oct. 13, 2009 and retrieved on Jul. 28, 2010, available at <http://en.wikipedia.org/wiki/Mel_scale>, 2 pages.
- Mhatre et al., "Donna Interactive Chat-bot acting as a Personal Assistant", International Journal of Computer Applications (0975-8887), vol. 140, No. 10, Apr. 2016, 6 pages.
- Microsoft, "Turn on and Use Magnifier", available at <<http://www.microsoft.com/windowsxp/using/accessibility/magnifierturnon.mspx>>, retrieved on Jun. 6, 2009.
- Miller, Chance, "Google Keyboard Updated with New Personalized Suggestions Feature", available at <<http://9to5google.com/2014/03/19/google-keyboard-updated-with-new-personalized-suggestions-feature/>>, Mar. 19, 2014, 4 pages.
- Minimum Phase, Wikipedia the free Encyclopedia, Last modified on Jan. 12, 2010 and retrieved on Jul. 28, 2010, available at <http://en.wikipedia.org/wiki/Minimum_phase>, 8 pages.
- Mobile Speech Solutions, Mobile Accessibility, SVOX AG Product Information Sheet, available at <<http://www.svox.com/site/bra840604/con782768/mob965831936.aSQ?osLang=1>>, Sep. 27, 2012, 1 page.
- Morrison, Jonathan, "iPhone 5 Siri Demo", Online Available at <https://www.youtube.com/watch?v=_wHWwG5lhWc>, Sep. 21, 2012, 3 pages.
- Morton, Philip, "Checking If an Element is Hidden", StackOverflow, Available at <<http://stackoverflow.com/questions/178325/checking-if-an-element-is-hidden>>, Oct. 7, 2008, 12 pages.
- My Cool Aids, "What's New", available at <<http://www.mycoolaids.com/>>, 2012, 1 page.
- Myers, Brad A., "Shortcutter for Palm", available at <<http://www.cs.cmu.edu/~pebbles/v5/shortcutter/palm/index.html>>, retrieved on Jun. 18, 2014, 10 pages.
- Nakazawa et al., "Detection and Labeling of Significant Scenes from TV program based on Twitter Analysis", Proceedings of the 3rd Forum on Data Engineering and Information Management (deim 2011 proceedings), IEICE Data Engineering Technical Group. Available online at: <http://db-event.jp/deim2011/proceedings/pdf/f5-6.pdf>, Feb. 28, 2011, 10 pages (Official Copy Only). (See Communication under 37 CFR § 1.98(a) (3)).
- Naone, Erica, "TR10: Intelligent Software Assistant", Technology Review, Mar.-Apr. 2009, 2 pages.
- Navigli, Roberto, "Word Sense Disambiguation: A Survey", ACM Computing Surveys, vol. 41, No. 2, Feb. 2009, 69 pages.
- NDTV, "Sony SmartWatch 2 Launched in India for Rs. 14,990", available at <<http://gadgets.ndtv.com/others/news/sony-smartwatch-2-launched-in-india-for-rs-14990-420319>>, Sep. 18, 2013, 4 pages.
- Ng, Simon, "Google's Task List Now Comes to Iphone", SimonBlog, Available at <<http://www.simonblog.com/2009/02/04/googles-task-list-now-comes-to-iphone>>, Feb. 4, 2009, 3 pages.
- Nozawa, Naoki et al., "iPhone 4S Perfect Manual", vol. 1, First Edition, Nov. 11, 2011, 5 pages.
- Oxsdaily, "Get a List of Siri Commands Directly from Siri", Available at <<http://osxdaily.com/2013/02/05/list-siri-commands/>>, Feb. 5, 2013, 15 pages.
- Pan et al., "Natural Language Aided Visual Query Building for Complex Data Access", In proceeding of: Proceedings of the Twenty-Second Conference on Innovative Applications of Artificial Intelligence, XP055114607, Jul. 11, 2010, pp. 1821-1826.
- Pathak et al., "Privacy-preserving Speech Processing: Cryptographic and String-matching Frameworks Show Promise", In: IEEE signal processing magazine, retrieved from <<http://www.merl.com/publications/docs/TR2013-063.pdf>>, Feb. 13, 2013, 16 pages.
- Patra et al., "A Kernel-Based Approach for Biomedical Named Entity Recognition", Scientific World Journal, vol. 2013, 2013, pp. 1-7.
- Phoenix Solutions, Inc., "Declaration of Christopher Schmandt Regarding the MIT Galaxy System", West Interactive Corp., A Delaware Corporation, Document 40, Jul. 2, 2010, 162 pages.
- Powell, Josh, "Now You See Me . . . Show/Hide Performance", available at <http://www.learningjquery.com/2010/05/now-you-see-me-showhide-performance>, May 4, 2010, 3 pages.
- Routines, "SmartThings Support", Available online at <<http://web.archive.org/web/20151207165701/https://support.smartthings.com/hc/en-us/articles/205380034-Routines>>, 2015, 2 pages.
- Sarawagi, Sunita, "CRF Package Page", available at <<http://crf.sourceforge.net/>>, retrieved on Apr. 6, 2011, 2 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Selfridge et al., "Interact: Tightly-coupling Multimodal Dialog with an Interactive Virtual Assistant", International Conference on Multimodal Interaction, ACM, Nov. 9, 2015, pp. 381-382.

Simonite, Tom, "One Easy Way to Make Siri Smarter", Technology Review, Oct. 18, 2011, 2 pages.

"SmartThings +Amazon Echo", Smartthings Samsung [online], Available online at <<https://web.archive.org/web/20160509231428/https://blog.smartthings.com/featured/alexa-turn-on-my-smarththings/>>, Aug. 21, 2015, 3 pages.

Speaker Recognition, Wikipedia, The Free Encyclopedia, Nov. 2, 2010, 4 pages.

Spivack, Nova, "Sneak Preview of Siri—Part Two—Technical Foundations—Interview with Tom Gruber, CTO of Siri", Online Available at <<https://web.archive.org/web/20100114234454/http://www.twine.com/item/12vhy39k4-22m/interview-with-tom-gruber-of-siri>>, Jan. 14, 2010, 5 pages.

SRI, "SRI Speech: Products: Software Development Kits: EduSpeak", available at <<http://web.archive.org/web/20090828084033/http://www.speechsiri.com/products/eduspeak>shhtml>>, retrieved on Jun. 20, 2013, 2 pages.

Stent et al., "Geo-Centric Language Models for Local Business Voice Search", AT&T Labs—Research, 2009, pp. 389-396.

Sullivan, Danny, "How Google Instant's Autocomplete Suggestions Work", available at <<http://searchengineland.com/how-google-instant-autocomplete-suggestions-work-62592>>, Apr. 6, 2011, 12 pages.

Sundaram et al., "Latent Perceptual Mapping with Data-Driven Variable-Length Acoustic Units for Template-Based Speech Recognition", ICASSP 2012, Mar. 2012, pp. 4125-4128.

TextnDrive, "Text'nDrive App Demo-Listen and Reply to your Messages by Voice while Driving!", YouTube Video available at <<http://www.youtube.com/watch?v=WaGfzoHsAMw>>, Apr. 27, 2010, 1 page.

"The world of Virtual Assistants—more SemTech . . .", End of Business as Usual—Glenn's External blog, Online Available at <<https://web.archive.org/web/20091101840940/http://glennas.wordpress.com/2009/10/17/the-world-of-virtual-assistants-more-semtech/>>, Oct. 17, 2009, 5 pages.

Tofel, Kevin C., "SpeakTolt: A Personal Assistant for Older iPhones, iPads", Apple News, Tips and Reviews, Feb. 9, 2012, 7 pages.

Tucker, Joshua, "Too Lazy to Grab Your TV Remote? Use Siri Instead", Engadget, Nov. 30, 2011, 8 pages.

Tur et al., "The CALO Meeting Assistant System", IEEE Transactions on Audio, Speech and Language Processing, vol. 18, No. 6, Aug. 2010, pp. 1601-1611.

Tur et al., "The CALO Meeting Speech Recognition and Understanding System", Proc. IEEE Spoken Language Technology Workshop, 2008, 4 pages.

Vlingo InCar, "Distracted Driving Solution with Vlingo InCar", YouTube Video, Available online at <<http://www.youtube.com/watch?v=Vgs8XfXgZ4>>, Oct. 2010, 2 pages.

Vlingo, "Vlingo Launches Voice Enablement Application on Apple App Store", Press Release, Dec. 3, 2008, 2 pages.

Vodafone Deutschland, "Samsung Galaxy S3 Tastatur Spracheingabe", Available online at—<<https://www.youtube.com/watch?v=6kOd6Gr8uFE>>, Aug. 22, 2012, 1 page.

Voiceassist, "Send Text, Listen to and Send E-Mail by Voice", YouTube Video, Available online at <<http://www.youtube.com/watch?v=0tEU61nHHA4>>, Jul. 30, 2009, 1 page.

VoiceOnTheGo, "Voice on the Go (BlackBerry)", YouTube Video, available online at <<http://www.youtube.com/watch?v=pJqpWgQS98w>>, Jul. 27, 2009, 1 page.

Wikipedia, "Acoustic Model", available at <<http://en.wikipedia.org/wiki/AcousticModel>>, retrieved on Sep. 14, 2011, 2 pages.

Wikipedia, "Language Model", available at <http://en.wikipedia.org/wiki/Language_model>, retrieved on Sep. 14, 2011, 4 pages.

Wikipedia, "Speech Recognition", available at <http://en.wikipedia.org/wiki/Speech_recognition>, retrieved on Sep. 14, 2011, 12 pages.

Wilson, Mark, "New iPod Shuffle Moves Buttons to Headphones, Adds Text to Speech", available at <<http://gizmodo.com/5167946/new-ipod-shuffle-moves-buttons-to-headphones-adds-text-to-speech>>, Mar. 11, 2009, 12 pages.

X.Ai, "How it Works", May 2016, 6 pages.

Xiang et al., "Correcting Phoneme Recognition Errors in Learning Word Pronunciation through Speech Interaction", Speech Communication, vol. 55, No. 1, Jan. 1, 2013, pp. 190-203.

Xu et al., "Speech-Based Interactive Games for Language Learning: Reading, Translation, and Question-Answering", Computational Linguistics and Chinese Language Processing, vol. 14, No. 2, Jun. 2009, pp. 133-160.

Yan et al., "A Scalable Approach to Using DNN-Derived Features in GMM-HMM Based Acoustic Modeling for LVCSR", InInterspeech, 2013, pp. 104-108.

Young et al., "The Hidden Information State model: A practical framework for POMDP-based spoken dialogue management", Computer Speech & Language, vol. 24, Issue 2, 2010, pp. 150-174.

Youtube, "New bar search for Facebook", Available at "https://www.youtube.com/watch?v=vwgN1WbvCas", 1 page.

Zainab, "Google Input Tools Shows Onscreen Keyboard in Multiple Languages [Chrome]", available at <<http://www.addictivetips.com/internet-tips/google-input-tools-shows-multiple-language-onscreen-keyboards-chrome/>>, Jan. 3, 2012, 3 pages.

Zangerle et al., "Recommending #-Tag in Twitter", Proceedings of the Workshop on Semantic Adaptive Socail Web, 2011, pp. 1-12.

Zhang et al., "Research of Text Classification Model Based on Latent Semantic Analysis and Improved HS-SVM", Intelligent Systems and Applications (ISA), 2010 2nd International Workshop, May 22-23, 2010, 5 pages.

Zhong et al., "JustSpeak: Enabling Universal Voice Control on Android", W4A'14, Proceedings of the 11th Web for All Conference, No. 36, Apr. 7-9, 2014, 8 pages.

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2018/066864, dated Mar. 7, 2019, 15 pages.

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5A






FIG. 5B

*FIG. 6A*




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 7C

Process
800 →




FIG. 8

1

MULTI-DIRECTIONAL DIALOG**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims priority to U.S. Provisional Patent Application No. 62/614,907, entitled "MULTI-DIRECTIONAL DIALOG," filed on Jan. 8, 2018, the content of which is hereby incorporated by reference in its entirety.

FIELD

This relates generally to digital assistants and, more specifically, to multi-directional dialog between a user and a digital assistant.

BACKGROUND

Intelligent automated assistants (or digital assistants) can provide a beneficial interface between human users and electronic devices. Such assistants can allow users to interact with devices or systems using natural language in spoken and/or text forms. For example, a user can provide a speech input containing a user request to a digital assistant operating on an electronic device. The digital assistant can interpret the user's intent from the speech input and operationalize the user's intent into tasks. The tasks can then be performed by executing one or more services of the electronic device, and a relevant output responsive to the user request can be returned to the user. In some instances, it is further desirable to allow the user to interact with a digital assistant using natural-language dialog. Contemporary dialog frameworks, however, often lack flexibility, requiring overly linear dialog sequences.

SUMMARY

Example methods are disclosed herein. An example method includes, at an electronic device having one or more processors, receiving a first natural-language input, determining a first intent based on the first natural-language input, identifying a first dialog flow based on the first intent, outputting a natural-language output associated with the first dialog flow, receiving a second natural-language input, determining whether the second natural-language input satisfies dialog criteria associated with the first dialog flow, and in accordance with a determination that the second natural-language input satisfies the dialog criteria, outputting a second natural-language output associated with the first dialog flow.

Example non-transitory computer-readable media are disclosed herein. An example non-transitory computer-readable storage medium stores one or more programs. The one or more programs comprise instructions, which when executed by one or more processors of an electronic device, cause the electronic device to receive a first natural-language input, determine a first intent based on the first natural-language input, identify a first dialog flow based on the first intent, output a natural-language output associated with the first dialog flow, receive a second natural-language input, determine whether the second natural-language input satisfies dialog criteria associated with the first dialog flow, and in accordance with a determination that the second natural-language input satisfies the dialog criteria, output a second natural-language output associated with the first dialog flow.

Example electronic devices are disclosed herein. An example electronic device comprises one or more proces-

2

sors; a memory; and one or more programs, where the one or more programs are stored in the memory and configured to be executed by the one or more processors, the one or more programs including instructions for receiving a first natural-language input; determining a first intent based on the first natural-language input, identifying a first dialog flow based on the first intent, outputting a natural-language output associated with the first dialog flow, receiving a second natural-language input, determining whether the second natural-language input satisfies dialog criteria associated with the first dialog flow, and in accordance with a determination that the second natural-language input satisfies the dialog criteria, outputting a second natural-language output associated with the first dialog flow.

An example electronic device comprises means for receiving a first natural-language input, means for determining a first intent based on the first natural-language input, means for identifying a first dialog flow based on the first intent, means for outputting a natural-language output associated with the first dialog flow, means for receiving a second natural-language input, means for determining whether the second natural-language input satisfies dialog criteria associated with the first dialog flow, and means for, in accordance with a determination that the second natural-language input satisfies the dialog criteria, outputting a second natural-language output associated with the first dialog flow.

Multi-directional dialog, as described herein, provides an intuitive and flexible dialog framework between a user and a digital assistant of an electronic device. By virtue of implementing multi-directional dialog, a user may communicate with a digital assistant without the burdens of traditionally rigid, linear dialog sequences that fail to provide a desirable level of syntactical flexibility.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating a system and environment for implementing a digital assistant, according to various examples.

FIG. 2A is a block diagram illustrating a portable multifunction device implementing the client-side portion of a digital assistant, according to various examples.

FIG. 2B is a block diagram illustrating exemplary components for event handling, according to various examples.

FIG. 3 illustrates a portable multifunction device implementing the client-side portion of a digital assistant, according to various examples.

FIG. 4 is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface, according to various examples.

FIG. 5A illustrates an exemplary user interface for a menu of applications on a portable multifunction device, according to various examples.

FIG. 5B illustrates an exemplary user interface for a multifunction device with a touch-sensitive surface that is separate from the display, according to various examples.

FIG. 6A illustrates a personal electronic device, according to various examples.

FIG. 6B is a block diagram illustrating a personal electronic device, according to various examples.

FIG. 7A is a block diagram illustrating a digital assistant system or a server portion thereof, according to various examples.

FIG. 7B illustrates the functions of the digital assistant shown in FIG. 7A, according to various examples.

FIG. 7C illustrates a portion of an ontology, according to various examples.

FIG. 8 illustrates a process for providing multi-directional dialog, according to various examples.

DETAILED DESCRIPTION

In the following description of examples, reference is made to the accompanying drawings in which are shown by way of illustration specific examples that can be practiced. It is to be understood that other examples can be used and structural changes can be made without departing from the scope of the various examples.

Although the following description uses terms “first,” “second,” etc. to describe various elements, these elements should not be limited by the terms. These terms are only used to distinguish one element from another. For example, a first input could be termed a second input, and, similarly, a second input could be termed a first input, without departing from the scope of the various described examples. The first input and the second input are both inputs and, in some cases, are separate and different inputs.

The terminology used in the description of the various described examples herein is for the purpose of describing particular examples only and is not intended to be limiting. As used in the description of the various described examples and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

The term “if” may be construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” may be construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

1. System and Environment

FIG. 1 illustrates a block diagram of system 100 according to various examples. In some examples, system 100 implements a digital assistant. The terms “digital assistant,” “virtual assistant,” “intelligent automated assistant,” or “automatic digital assistant” refer to any information processing system that interprets natural language input in spoken and/or textual form to infer user intent, and performs actions based on the inferred user intent. For example, to act on an inferred user intent, the system performs one or more of the following: identifying a task flow with steps and parameters designed to accomplish the inferred user intent, inputting specific requirements from the inferred user intent into the task flow; executing the task flow by invoking programs, methods, services, APIs, or the like; and generating output responses to the user in an audible (e.g., speech) and/or visual form.

Specifically, a digital assistant is capable of accepting a user request at least partially in the form of a natural language command, request, statement, narrative, and/or

inquiry. Typically, the user request seeks either an informational answer or performance of a task by the digital assistant. A satisfactory response to the user request includes a provision of the requested informational answer, a performance of the requested task, or a combination of the two. For example, a user asks the digital assistant a question, such as “Where am I right now?” Based on the user’s current location, the digital assistant answers, “You are in Central Park near the west gate.” The user also requests the performance of a task, for example, “Please invite my friends to my girlfriend’s birthday party next week.” In response, the digital assistant can acknowledge the request by saying “Yes, right away,” and then send a suitable calendar invite on behalf of the user to each of the user’s friends listed in the user’s electronic address book. During performance of a requested task, the digital assistant sometimes interacts with the user in a continuous dialogue involving multiple exchanges of information over an extended period of time. There are numerous other ways of interacting with a digital assistant to request information or performance of various tasks. In addition to providing verbal responses and taking programmed actions, the digital assistant also provides responses in other visual or audio forms, e.g., as text, alerts, music, videos, animations, etc.

As shown in FIG. 1, in some examples, a digital assistant is implemented according to a client-server model. The digital assistant includes client-side portion 102 (hereafter “DA client 102”) executed on user device 104 and server-side portion 106 (hereafter “DA server 106”) executed on server system 108. DA client 102 communicates with DA server 106 through one or more networks 110. DA client 102 provides client-side functionalities such as user-facing input and output processing and communication with DA server 106. DA server 106 provides server-side functionalities for any number of DA clients 102 each residing on a respective user device 104.

In some examples, DA server 106 includes client-facing I/O interface 112, one or more processing modules 114, data and models 116, and I/O interface to external services 118. The client-facing I/O interface 112 facilitates the client-facing input and output processing for DA server 106. One or more processing modules 114 utilize data and models 116 to process speech input and determine the user’s intent based on natural language input. Further, one or more processing modules 114 perform task execution based on inferred user intent. In some examples, DA server 106 communicates with external services 120 through network(s) 110 for task completion or information acquisition. I/O interface to external services 118 facilitates such communications.

User device 104 can be any suitable electronic device. In some examples, user device is a portable multifunctional device (e.g., device 200, described below with reference to FIG. 2A), a multifunctional device (e.g., device 400, described below with reference to FIG. 4), or a personal electronic device (e.g., device 600, described below with reference to FIG. 6A-B.) A portable multifunctional device is, for example, a mobile telephone that also contains other functions, such as PDA and/or music player functions. Specific examples of portable multifunction devices include the Apple Watch®, iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, Calif. Other examples of portable multifunction devices include, without limitation, earphones/headphones, speakers, and laptop or tablet computers. Further, in some examples, user device 104 is a non-portable multifunctional device. In particular, user device 104 is a desktop computer, a game console, a speaker, a television, or a television set-top box. In some examples,

user device **104** includes a touch-sensitive surface (e.g., touch screen displays and/or touchpads). Further, user device **104** optionally includes one or more other physical user-interface devices, such as a physical keyboard, a mouse, and/or a joystick. Various examples of electronic devices, such as multifunctional devices, are described below in greater detail.

Examples of communication network(s) **110** include local area networks (LAN) and wide area networks (WAN), e.g., the Internet. Communication network(s) **110** is implemented using any known network protocol, including various wired or wireless protocols, such as, for example, Ethernet, Universal Serial Bus (USB), FIREWIRE, Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wi-Fi, voice over Internet Protocol (VoIP), WiMAX, or any other suitable communication protocol.

Server system **108** is implemented on one or more standalone data processing apparatus or a distributed network of computers. In some examples, server system **108** also employs various virtual devices and/or services of third-party service providers (e.g., third-party cloud service providers) to provide the underlying computing resources and/or infrastructure resources of server system **108**.

In some examples, user device **104** communicates with DA server **106** via second user device **122**. Second user device **122** is similar or identical to user device **104**. For example, second user device **122** is similar to devices **200**, **400**, or **600** described below with reference to FIGS. 2A, 4, and 6A-B. User device **104** is configured to communicatively couple to second user device **122** via a direct communication connection, such as Bluetooth, NFC, BTLE, or the like, or via a wired or wireless network, such as a local Wi-Fi network. In some examples, second user device **122** is configured to act as a proxy between user device **104** and DA server **106**. For example, DA client **102** of user device **104** is configured to transmit information (e.g., a user request received at user device **104**) to DA server **106** via second user device **122**. DA server **106** processes the information and return relevant data (e.g., data content responsive to the user request) to user device **104** via second user device **122**.

In some examples, user device **104** is configured to communicate abbreviated requests for data to second user device **122** to reduce the amount of information transmitted from user device **104**. Second user device **122** is configured to determine supplemental information to add to the abbreviated request to generate a complete request to transmit to DA server **106**. This system architecture can advantageously allow user device **104** having limited communication capabilities and/or limited battery power (e.g., a watch or a similar compact electronic device) to access services provided by DA server **106** by using second user device **122**, having greater communication capabilities and/or battery power (e.g., a mobile phone, laptop computer, tablet computer, or the like), as a proxy to DA server **106**. While only two user devices **104** and **122** are shown in FIG. 1, it should be appreciated that system **100**, in some examples, includes any number and type of user devices configured in this proxy configuration to communicate with DA server system **106**.

Although the digital assistant shown in FIG. 1 includes both a client-side portion (e.g., DA client **102**) and a server-side portion (e.g., DA server **106**), in some examples, the functions of a digital assistant are implemented as a standalone application installed on a user device. In addition, the divisions of functionalities between the client and

server portions of the digital assistant can vary in different implementations. For instance, in some examples, the DA client is a thin-client that provides only user-facing input and output processing functions, and delegates all other functionalities of the digital assistant to a backend server.

2. Electronic Devices

Attention is now directed toward embodiments of electronic devices for implementing the client-side portion of a digital assistant. FIG. 2A is a block diagram illustrating portable multifunction device **200** with touch-sensitive display system **212** in accordance with some embodiments. Touch-sensitive display **212** is sometimes called a “touch screen” for convenience and is sometimes known as or called a “touch-sensitive display system.” Device **200** includes memory **202** (which optionally includes one or more computer-readable storage mediums), memory controller **222**, one or more processing units (CPUs) **220**, peripherals interface **218**, RF circuitry **208**, audio circuitry **210**, speaker **211**, microphone **213**, input/output (I/O) subsystem **206**, other input control devices **216**, and external port **224**. Device **200** optionally includes one or more optical sensors **264**. Device **200** optionally includes one or more contact intensity sensors **265** for detecting intensity of contacts on device **200** (e.g., a touch-sensitive surface such as touch-sensitive display system **212** of device **200**). Device **200** optionally includes one or more tactile output generators **267** for generating tactile outputs on device **200** (e.g., generating tactile outputs on a touch-sensitive surface such as touch-sensitive display system **212** of device **200** or touchpad **455** of device **400**). These components optionally communicate over one or more communication buses or signal lines **203**.

As used in the specification and claims, the term “intensity” of a contact on a touch-sensitive surface refers to the force or pressure (force per unit area) of a contact (e.g., a finger contact) on the touch-sensitive surface, or to a substitute (proxy) for the force or pressure of a contact on the touch-sensitive surface. The intensity of a contact has a range of values that includes at least four distinct values and more typically includes hundreds of distinct values (e.g., at least 256). Intensity of a contact is, optionally, determined (or measured) using various approaches and various sensors or combinations of sensors. For example, one or more force sensors underneath or adjacent to the touch-sensitive surface are, optionally, used to measure force at various points on the touch-sensitive surface. In some implementations, force measurements from multiple force sensors are combined (e.g., a weighted average) to determine an estimated force of a contact. Similarly, a pressure-sensitive tip of a stylus is, optionally, used to determine a pressure of the stylus on the touch-sensitive surface. Alternatively, the size of the contact area detected on the touch-sensitive surface and/or changes thereto, the capacitance of the touch-sensitive surface proximate to the contact and/or changes thereto, and/or the resistance of the touch-sensitive surface proximate to the contact and/or changes thereto are, optionally, used as a substitute for the force or pressure of the contact on the touch-sensitive surface. In some implementations, the substitute measurements for contact force or pressure are used directly to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is described in units corresponding to the substitute measurements). In some implementations, the substitute measurements for contact force or pressure are converted to an estimated force or pressure, and the estimated force or pressure is used to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is a pressure threshold mea-

sured in units of pressure). Using the intensity of a contact as an attribute of a user input allows for user access to additional device functionality that may otherwise not be accessible by the user on a reduced-size device with limited real estate for displaying affordances (e.g., on a touch-sensitive display) and/or receiving user input (e.g., via a touch-sensitive display, a touch-sensitive surface, or a physical/mechanical control such as a knob or a button).

As used in the specification and claims, the term “tactile output” refers to physical displacement of a device relative to a previous position of the device, physical displacement of a component (e.g., a touch-sensitive surface) of a device relative to another component (e.g., housing) of the device, or displacement of the component relative to a center of mass of the device that will be detected by a user with the user’s sense of touch. For example, in situations where the device or the component of the device is in contact with a surface of a user that is sensitive to touch (e.g., a finger, palm, or other part of a user’s hand), the tactile output generated by the physical displacement will be interpreted by the user as a tactile sensation corresponding to a perceived change in physical characteristics of the device or the component of the device. For example, movement of a touch-sensitive surface (e.g., a touch-sensitive display or trackpad) is, optionally, interpreted by the user as a “down click” or “up click” of a physical actuator button. In some cases, a user will feel a tactile sensation such as an “down click” or “up click” even when there is no movement of a physical actuator button associated with the touch-sensitive surface that is physically pressed (e.g., displaced) by the user’s movements. As another example, movement of the touch-sensitive surface is, optionally, interpreted or sensed by the user as “roughness” of the touch-sensitive surface, even when there is no change in smoothness of the touch-sensitive surface. While such interpretations of touch by a user will be subject to the individualized sensory perceptions of the user, there are many sensory perceptions of touch that are common to a large majority of users. Thus, when a tactile output is described as corresponding to a particular sensory perception of a user (e.g., an “up click,” a “down click,” “roughness”), unless otherwise stated, the generated tactile output corresponds to physical displacement of the device or a component thereof that will generate the described sensory perception for a typical (or average) user.

It should be appreciated that device **200** is only one example of a portable multifunction device, and that device **200** optionally has more or fewer components than shown, optionally combines two or more components, or optionally has a different configuration or arrangement of the components. The various components shown in FIG. **2A** are implemented in hardware, software, or a combination of both hardware and software, including one or more signal processing and/or application-specific integrated circuits.

Memory **202** includes one or more computer-readable storage mediums. The computer-readable storage mediums are, for example, tangible and non-transitory. Memory **202** includes high-speed random access memory and also includes non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Memory controller **222** controls access to memory **202** by other components of device **200**.

In some examples, a non-transitory computer-readable storage medium of memory **202** is used to store instructions (e.g., for performing aspects of processes described below) for use by or in connection with an instruction execution system, apparatus, or device, such as a computer-based

system, processor-containing system, or other system that can fetch the instructions from the instruction execution system, apparatus, or device and execute the instructions. In other examples, the instructions (e.g., for performing aspects of the processes described below) are stored on a non-transitory computer-readable storage medium (not shown) of the server system **108** or are divided between the non-transitory computer-readable storage medium of memory **202** and the non-transitory computer-readable storage medium of server system **108**.

Peripherals interface **218** is used to couple input and output peripherals of the device to CPU **220** and memory **202**. The one or more processors **220** run or execute various software programs and/or sets of instructions stored in memory **202** to perform various functions for device **200** and to process data. In some embodiments, peripherals interface **218**, CPU **220**, and memory controller **222** are implemented on a single chip, such as chip **204**. In some other embodiments, they are implemented on separate chips.

RF (radio frequency) circuitry **208** receives and sends RF signals, also called electromagnetic signals. RF circuitry **208** converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **208** optionally includes well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **208** optionally communicates with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The RF circuitry **208** optionally includes well-known circuitry for detecting near field communication (NFC) fields, such as by a short-range communication radio. The wireless communication optionally uses any of a plurality of communications standards, protocols, and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSUPA), Evolution, Data-Only (EV-DO), HSPA, HSPA+, Dual-Cell HSPA (DC-HSPDA), long term evolution (LTE), near field communication (NFC), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Bluetooth Low Energy (BLE), Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, and/or IEEE 802.11ac), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for e mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

Audio circuitry **210**, speaker **211**, and microphone **212** provide an audio interface between a user and device **200**. Audio circuitry **210** receives audio data from peripherals interface **218**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **211**. Speaker **211** converts the electrical signal to human-audible sound

waves. Audio circuitry **210** also receives electrical signals converted by microphone **213** from sound waves. Audio circuitry **210** converts the electrical signal to audio data and transmits the audio data to peripherals interface **218** for processing. Audio data are retrieved from and/or transmitted to memory **202** and/or RF circuitry **208** by peripherals interface **218**. In some embodiments, audio circuitry **210** also includes a headset jack (e.g., **312**, FIG. 3). The headset jack provides an interface between audio circuitry **210** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

I/O subsystem **206** couples input/output peripherals on device **200**, such as touch screen **212** and other input control devices **216**, to peripherals interface **218**. I/O subsystem **206** optionally includes display controller **256**, optical sensor controller **258**, intensity sensor controller **259**, haptic feedback controller **261**, and one or more input controllers **260** for other input or control devices. The one or more input controllers **260** receive/send electrical signals from/to other input control devices **216**. The other input control devices **216** optionally include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) **260** are, optionally, coupled to any (or none) of the following: a keyboard, an infrared port, a USB port, and a pointer device such as a mouse. The one or more buttons (e.g., **308**, FIG. 3) optionally include an up/down button for volume control of speaker **211** and/or microphone **213**. The one or more buttons optionally include a push button (e.g., **306**, FIG. 3).

A quick press of the push button disengages a lock of touch screen **212** or begin a process that uses gestures on the touch screen to unlock the device, as described in U.S. patent application Ser. No. 11/322,549, "Unlocking a Device by Performing Gestures on an Unlock Image," filed Dec. 23, 2005, U.S. Pat. No. 7,657,849, which is hereby incorporated by reference in its entirety. A longer press of the push button (e.g., **306**) turns power to device **200** on or off. The user is able to customize a functionality of one or more of the buttons. Touch screen **212** is used to implement virtual or soft buttons and one or more soft keyboards.

Touch-sensitive display **212** provides an input interface and an output interface between the device and a user. Display controller **256** receives and/or sends electrical signals from/to touch screen **212**. Touch screen **212** displays visual output to the user. The visual output includes graphics, text, icons, video, and any combination thereof (collectively termed "graphics"). In some embodiments, some or all of the visual output correspond to user-interface objects.

Touch screen **212** has a touch-sensitive surface, sensor, or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch screen **212** and display controller **256** (along with any associated modules and/or sets of instructions in memory **202**) detect contact (and any movement or breaking of the contact) on touch screen **212** and convert the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages, or images) that are displayed on touch screen **212**. In an exemplary embodiment, a point of contact between touch screen **212** and the user corresponds to a finger of the user.

Touch screen **212** uses LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies may be used in other embodiments. Touch screen **212** and display controller **256** detect

contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch screen **212**. In an exemplary embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone® and iPod Touch® from Apple Inc. of Cupertino, Calif.

A touch-sensitive display in some embodiments of touch screen **212** is analogous to the multi-touch sensitive touchpads described in the following U.S. Pat. No. 6,323,846 (Westerman et al.), U.S. Pat. No. 6,570,557 (Westerman et al.), and/or U.S. Pat. No. 6,677,932 (Westerman), and/or U.S. Patent Publication 2002/0015024A1, each of which is hereby incorporated by reference in its entirety. However, touch screen **212** displays visual output from device **200**, whereas touch-sensitive touchpads do not provide visual output.

A touch-sensitive display in some embodiments of touch screen **212** is as described in the following applications: (1) U.S. patent application Ser. No. 11/381,313, "Multipoint Touch Surface Controller," filed May 2, 2006; (2) U.S. patent application Ser. No. 10/840,862, "Multipoint Touchscreen," filed May 6, 2004; (3) U.S. patent application Ser. No. 10/903,964, "Gestures For Touch Sensitive Input Devices," filed Jul. 30, 2004; (4) U.S. patent application Ser. No. 11/048,264, "Gestures For Touch Sensitive input Devices," filed Jan. 31, 2005; (5) U.S. patent application Ser. No. 11/038,590, "Mode-Based Graphical User Interfaces For Touch Sensitive Input Devices," filed Jan. 18, 2005; (6) U.S. patent application Ser. No. 11/228,758, "Virtual Input Device Placement On A Touch Screen User Interface," filed Sep. 16, 2005; (7) U.S. patent application Ser. No. 11/228,700, "Operation Of A Computer With A Touch Screen Interface," filed Sep. 16, 2005; (8) U.S. patent application Ser. No. 11/228,737, "Activating Virtual Keys Of A Touch-Screen Virtual Keyboard," filed Sep. 16, 2005; and (9) U.S. patent application Ser. No. 11/367,749, "Multi-Functional Hand-Held Device," filed Mar. 3, 2006. All of these applications are incorporated by reference herein in their entirety.

Touch screen **212** has, for example, a video resolution in excess of 100 dpi. In some embodiments, the touch screen has a video resolution of approximately 160 dpi. The user makes contact with touch screen **212** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

In some embodiments, in addition to the touch screen, device **200** includes a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad is a touch-sensitive surface that is separate from touch screen **212** or an extension of the touch-sensitive surface formed by the touch screen.

Device **200** also includes power system **262** for powering the various components. Power system **262** includes a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or

inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

Device **200** also includes one or more optical sensors **264**. FIG. **2A** shows an optical sensor coupled to optical sensor controller **258** in I/O subsystem **206**. Optical sensor **264** includes charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. Optical sensor **264** receives light from the environment, projected through one or more lenses, and converts the light to data representing an image. In conjunction with imaging module **243** (also called a camera module), optical sensor **264** captures still images or video. In some embodiments, an optical sensor is located on the back of device **200**, opposite touch screen display **212** on the front of the device so that the touch screen display is used as a viewfinder for still and/or video image acquisition. In some embodiments, an optical sensor is located on the front of the device so that the user's image is obtained for video conferencing while the user views the other video conference participants on the touch screen display. In some embodiments, the position of optical sensor **264** can be changed by the user (e.g., by rotating the lens and the sensor in the device housing) so that a single optical sensor **264** is used along with the touch screen display for both video conferencing and still and/or video image acquisition.

Device **200** optionally also includes one or more contact intensity sensors **265**. FIG. **2A** shows a contact intensity sensor coupled to intensity sensor controller **259** in I/O subsystem **206**. Contact intensity sensor **265** optionally includes one or more piezoresistive strain gauges, capacitive force sensors, electric force sensors, piezoelectric force sensors, optical force sensors, capacitive touch-sensitive surfaces, or other intensity sensors (e.g., sensors used to measure the force (or pressure) of a contact on a touch-sensitive surface). Contact intensity sensor **265** receives contact intensity information (e.g., pressure information or a proxy for pressure information) from the environment. In some embodiments, at least one contact intensity sensor is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **212**). In some embodiments, at least one contact intensity sensor is located on the back of device **200**, opposite touch screen display **212**, which is located on the front of device **200**.

Device **200** also includes one or more proximity sensors **266**. FIG. **2A** shows proximity sensor **266** coupled to peripherals interface **218**. Alternately, proximity sensor **266** is coupled to input controller **260** in I/O subsystem **206**. Proximity sensor **266** is performed as described in U.S. patent application Ser. No. 11/241,839, "Proximity Detector In Handheld Device"; Ser. No. 11/240,788, "Proximity Detector In Handheld Device"; Ser. No. 11/620,702, "Using Ambient Light Sensor To Augment Proximity Sensor Output"; Ser. No. 11/586,862, "Automated Response To And Sensing Of User Activity In Portable Devices"; and Ser. No. 11/638,251, "Methods And Systems For Automatic Configuration Of Peripherals," which are hereby incorporated by reference in their entirety. In some embodiments, the proximity sensor turns off and disables touch screen **212** when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call).

Device **200** optionally also includes one or more tactile output generators **267**. FIG. **2A** shows a tactile output generator coupled to haptic feedback controller **261** in I/O subsystem **206**. Tactile output generator **267** optionally includes one or more electroacoustic devices such as speak-

ers or other audio components and/or electromechanical devices that convert energy into linear motion such as a motor, solenoid, electroactive polymer, piezoelectric actuator, electrostatic actuator, or other tactile output generating component (e.g., a component that converts electrical signals into tactile outputs on the device). Contact intensity sensor **265** receives tactile feedback generation instructions from haptic feedback module **233** and generates tactile outputs on device **200** that are capable of being sensed by a user of device **200**. In some embodiments, at least one tactile output generator is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **212**) and, optionally, generates a tactile output by moving the touch-sensitive surface vertically (e.g., in/out of a surface of device **200**) or laterally (e.g., back and forth in the same plane as a surface of device **200**). In some embodiments, at least one tactile output generator sensor is located on the back of device **200**, opposite touch screen display **212**, which is located on the front of device **200**.

Device **200** also includes one or more accelerometers **268**. FIG. **2A** shows accelerometer **268** coupled to peripherals interface **218**. Alternately, accelerometer **268** is coupled to an input controller **260** in I/O subsystem **206**. Accelerometer **268** performs, for example, as described in U.S. Patent Publication No. 20050190059, "Acceleration-based Theft Detection System for Portable Electronic Devices," and U.S. Patent Publication No. 20060017692, "Methods And Apparatuses For Operating A Portable Device Based On An Accelerometer," both of which are incorporated by reference herein in their entirety. In some embodiments, information is displayed on the touch screen display in a portrait view or a landscape view based on an analysis of data received from the one or more accelerometers. Device **200** optionally includes, in addition to accelerometer(s) **268**, a magnetometer (not shown) and a GPS (or GLONASS or other global navigation system) receiver (not shown) for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **200**.

In some embodiments, the software components stored in memory **202** include operating system **226**, communication module (or set of instructions) **228**, contact/motion module (or set of instructions) **230**, graphics module (or set of instructions) **232**, text input module (or set of instructions) **234**, Global Positioning System (GPS) module (or set of instructions) **235**, Digital Assistant Client Module **229**, and applications (or sets of instructions) **236**. Further, memory **202** stores data and models, such as user data and models **231**. Furthermore, in some embodiments, memory **202** (FIG. **2A**) or **470** (FIG. **4**) stores device/global internal state **257**, as shown in FIGS. **2A** and **4**. Device/global internal state **257** includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch screen display **212**; sensor state, including information obtained from the device's various sensors and input control devices **216**; and location information concerning the device's location and/or attitude.

Operating system **226** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, iOS, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

Communication module **228** facilitates communication with other devices over one or more external ports **224** and also includes various software components for handling data

13

received by RF circuitry **208** and/or external port **224**. External port **224** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network. (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with, the 30-pin connector used on iPod® (trademark of Apple Inc.) devices.

Contact/motion module **230** optionally detects contact with touch screen **212** (in conjunction with display controller **256**) and other touch-sensitive devices (e.g., a touchpad or physical click wheel). Contact/motion module **230** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred (e.g., detecting a finger-down event), determining an intensity of the contact (e.g., the force or pressure of the contact or a substitute for the force or pressure of the contact), determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **230** receives contact data from the touch-sensitive surface. Determining movement of the point of contact, which is represented by a series of contact data, optionally includes determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations are, optionally, applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., “multitouch”/multiple finger contacts). In some embodiments, contact/motion module **230** and display controller **256** detect contact on a touchpad.

In some embodiments, contact/motion module **230** uses a set of one or more intensity thresholds to determine whether an operation has been performed by a user to determine whether a user has “clicked” on an icon). In some embodiments, at least a subset of the intensity thresholds are determined in accordance with software parameters (e.g., the intensity thresholds are not determined by the activation thresholds of particular physical actuators and can be adjusted without changing the physical hardware of device **200**). For example, a mouse “click” threshold of a trackpad or touch screen display can be set to any of a large range of predefined threshold values without changing the trackpad or touch screen display hardware. Additionally, in some implementations, a user of the device is provided with software settings for adjusting one or more of the set of intensity thresholds (e.g., by adjusting individual intensity thresholds and/or by adjusting a plurality of intensity thresholds at once with a system-level click “intensity” parameter).

Contact/motion module **230** optionally detects a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns (e.g., different motions, timings, and/or intensities of detected contacts). Thus, a gesture is, optionally, detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (liftoff) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (liftoff) event.

Graphics module **232** includes various known software components for rendering and displaying graphics on touch

14

screen **212** or other display, including components for changing the visual impact (e.g., brightness, transparency, saturation, contrast, or other visual property) of graphics that are displayed. As used herein, the term “graphics” includes any object that can be displayed to a user, including, without limitation, text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations, and the like.

In some embodiments, graphics module **232** stores data representing graphics to be used. Each graphic is, optionally, assigned a corresponding code. Graphics module **232** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **256**.

Haptic feedback module **233** includes various software components for generating instructions used by tactile output generator(s) **267** to produce tactile outputs at one or more locations on device **200** in response to user interactions with device **200**.

Text input module **234**, which is, in some examples, a component of graphics module **232**, provides soft keyboards for entering text in various applications (e.g., contacts **237**, email **240**, IM **241**, browser **247**, and any other application that needs text input).

GPS module **235** determines the location of the device and provides this information for use in various applications (e.g., to telephone **238** for use in location-based dialing; to camera **243** as picture/video metadata; and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

Digital assistant client module **229** includes various client-side digital assistant instructions to provide the client-side functionalities of the digital assistant. For example, digital assistant client module **229** is capable of accepting voice input (e.g., speech input), text input, touch input, and/or gestural input through various user interfaces (e.g., microphone **213**, accelerometer(s) **268**, touch-sensitive display system **212**, optical sensor(s) **229**, other input control devices **216**, etc.) of portable multifunction device **200**. Digital assistant client module **229** is also capable of providing output in audio (e.g., speech output), visual, and/or tactile forms through various output interfaces (e.g., speaker **211**, touch-sensitive display system **212**, tactile output generator(s) **267**, etc.) of portable multifunction device **200**. For example, output is provided as voice, sound, alerts, text messages, menus, graphics, videos, animations, vibrations, and/or combinations of two or more of the above. During operation, digital assistant client module **229** communicates with DA server **106** using RF circuitry **208**.

User data and models **231** include various data associated with the user (e.g., user-specific vocabulary data, user preference data, user-specified name pronunciations, data from the user’s electronic address book, to-do lists, shopping lists, etc.) to provide the client-side functionalities of the digital assistant. Further, user data and models **231** include various models (e.g., speech recognition models, statistical language models, natural language processing models, ontology, task flow models, service models, etc.) for processing user input and determining user intent.

In some examples, digital assistant client module **229** utilizes the various sensors, subsystems, and peripheral devices of portable multifunction device **200** to gather additional information from the surrounding environment of the portable multifunction device **200** to establish a context

associated with a user, the current user interaction, and/or the current user input. In some examples, digital assistant client module 229 provides the contextual information or a subset thereof with the user input to DA server 106 to help infer the user's intent. In some examples, the digital assistant also uses the contextual information to determine how to prepare and deliver outputs to the user. Contextual information is referred to as context data.

In some examples, the contextual information that accompanies the user input includes sensor information, e.g., lighting, ambient noise, ambient temperature, images or videos of the surrounding environment, etc. In some examples, the contextual information can also include the physical state of the device, e.g., device orientation, device location, device temperature, power level, speed, acceleration, motion patterns, cellular signals strength, etc. In some examples, information related to the software state of DA server 106, e.g., running processes, installed programs, past and present network activities, background services, error logs, resources usage, etc., and of portable multifunction device 200 is provided to DA server 106 as contextual information associated with a user input.

In some examples, the digital assistant client module 229 selectively provides information (e.g., user data 231) stored on the portable multifunction device 200 in response to requests from DA server 106. In some examples, digital assistant client module 229 also elicits additional input from the user via a natural language dialogue or other user interfaces upon request by DA server 106. Digital assistant client module 229 passes the additional input to DA server 106 to help DA server 106 in intent deduction and/or fulfillment of the user's intent expressed in the user request.

A more detailed description of a digital assistant is described below with reference to FIGS. 7A-C. It should be recognized that digital assistant client module 229 can include any number of the sub-modules of digital assistant module 726 described below.

Applications 236 include the following modules (or sets of instructions), or a subset or superset thereof:

Contacts module 237 (sometimes called an address book or contact list);

Telephone module 238;

Video conference module 239;

E-mail client module 240;

Instant messaging (IM) module 241,

Workout support module 242;

Camera module 243 for still and/or video images;

Image management module 244;

Video player module;

Music player module;

Browser module 247;

Calendar module 248;

Widget modules 249, which includes, in some examples, one or more of: weather widget 249-1, stocks widget 249-2, calculator widget 249-3, alarm clock widget 249-4, dictionary widget 249-5, and other widgets obtained by the user, as well as user-created widgets 249-6;

Widget creator module 250 for making user-created widgets 249-6;

Search module 251;

Video and music player module 252, which merges video player module and music player module;

Notes module 253;

Map module 254; and/or

Online video module 255.

Examples of other applications 236 that are stored in memory 202 include other word processing applications, other image editing applications, drawing applications, presentation applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

In conjunction with touch screen 212, display controller 256, contact/motion module 230, graphics module 232, and text input module 234, contacts module 237 are used to manage an address book or contact list (e.g., stored in application internal state 292 of contacts module 237 in memory 202 or memory 470), including: adding name(s) to the address book; deleting name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers or e-mail addresses to initiate and/or facilitate communications by telephone 238, video conference module 239, e-mail 240, or IM 241; and so forth.

In conjunction with RF circuitry 208, audio circuitry 210, speaker 211, microphone 213, touch screen 212, display controller 256, contact/motion module 230, graphics module 232, and text input module 234, telephone module 238 are used to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in contacts module 237, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation, and disconnect or hang up when the conversation is completed. As noted above, the wireless communication uses any of a plurality of communications standards, protocols, and technologies.

In conjunction with RF circuitry 208, audio circuitry 210, speaker 211, microphone 213, touch screen 212, display controller 256, optical sensor 264, optical sensor controller 258, contact/motion module 230, graphics module 232, text input module 234, contacts module 237, and telephone module 238, video conference module 239 includes executable instructions to initiate, conduct, and terminate a video conference between a user and one or more other participants in accordance with user instructions.

In conjunction with RF circuitry 208, touch screen 212, display controller 256, contact/motion module 230, graphics module 232, and text input module 234, e-mail client module 240 includes executable instructions to create, send, receive, and manage e-mail in response to user instructions. In conjunction with image management module 244, e-mail client module 240 makes it very easy to create and send e-mails with still or video images taken with camera module 243.

In conjunction with RF circuitry 208, touch screen 212, display controller 256, contact/motion module 230, graphics module 232, and text input module 234, the instant messaging module 241 includes executable instructions to enter a sequence of characters corresponding to an instant message, to modify previously entered characters, to transmit a respective instant message (for example, using a Short Message Service (SMS) or Multimedia Message Service (MMS) protocol for telephony-based instant messages or using XMPP, SIMPLE, or IMPS for Internet-based instant messages), to receive instant messages, and to view received instant messages. In some embodiments, transmitted and/or received instant messages include graphics, photos, audio files, video files and/or other attachments as are supported in an MMS and/or an Enhanced Messaging Service (EMS). As used herein, "instant messaging" refers to both telephony-

based messages (e.g., messages sent using SMS or MMS) and Internet-based messages (e.g., messages sent using XMPP, SIMPLE, or IMPS).

In conjunction with RF circuitry 208, touch screen 212, display controller 256, contact/motion module 230, graphics module 232, text input module 234, GPS module 235, map module 254, and music player module, workout support module 242 includes executable instructions to create workouts (e.g., with time, distance, and/or calorie burning goals); communicate with workout sensors (sports devices); receive workout sensor data; calibrate sensors used to monitor a workout; select and play music for a workout; and display, store, and transmit workout data.

In conjunction with touch screen 212, display controller 256, optical sensor(s) 264, optical sensor controller 258, contact/motion module 230, graphics module 232, and image management module 244, camera module 243 includes executable instructions to capture still images or video (including a video stream) and store them into memory 202, modify characteristics of a still image or video, or delete a still image or video from memory 202.

In conjunction with touch screen 212, display controller 256, contact/motion module 230, graphics module 232, text input module 234, and camera module 243, image management module 244 includes executable instructions to arrange, modify (e.g., edit), or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

In conjunction with RF circuitry 208, touch screen 212, display controller 256, contact/motion module 230, graphics module 232, and text input module 234, browser module 247 includes executable instructions to browse the Internet in accordance with user instructions, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

In conjunction with RF circuitry 208, touch screen 212, display controller 256, contact/motion module 230, graphics module 232, text input module 234, e-mail client module 240, and browser module 247, calendar module 248 includes executable instructions to create, display, modify, and store calendars and data associated with calendars (e.g., calendar entries, to-do lists, etc.) in accordance with user instructions.

In conjunction with RF circuitry 208, touch screen 212, display controller 256, contact/motion module 230, graphics module 232, text input module 234, and browser module 247, widget modules 249 are mini-applications that can be downloaded and used by a user (e.g., weather widget 249-1, stocks widget 249-2, calculator widget 249-3, alarm clock widget 249-4, and dictionary widget 249-5) or created by the user (e.g., user-created widget 249-6). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

In conjunction with RF circuitry 208, touch screen 212, display controller 256, contact/motion module 230, graphics module 232, text input module 234, and browser module 247, the widget creator module 250 are used by a user to create widgets (e.g., turning a user-specified portion of a web page into a widget).

In conjunction with touch screen 212, display controller 256, contact/motion module 230, graphics module 232, and text input module 234, search module 251 includes executable instructions to search for text, music, sound, image, video, and/or other files in memory 202 that match one or

more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

In conjunction with touch screen 212, display controller 256, contact/motion module 230, graphics module 232, audio circuitry 210, speaker 211, RF circuitry 208, and browser module 247, video and music player module 252 includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files, and executable instructions to display, present, or otherwise play back videos (e.g., on touch screen 212 or on an external, connected display via external port 224). In some embodiments, device 200 optionally includes the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

In conjunction with touch screen 212, display controller 256, contact/motion module 230, graphics module 232, and text input module 234, notes module 253 includes executable instructions to create and manage notes, to-do lists, and the like in accordance with user instructions.

In conjunction with RF circuitry 208, touch screen 212, display controller 256, contact/motion module 230, graphics module 232, text input module 234, GPS module 235, and browser module 247, map module 254 are used to receive, display, modify, and store maps and data associated with maps (e.g., driving directions, data on stores and other points of interest at or near a particular location, and other location-based data) in accordance with user instructions.

In conjunction with touch screen 212, display controller 256, contact/motion module 230, graphics module 232, audio circuitry 210, speaker 211, RF circuitry 208, text input module 234, e-mail client module 240, and browser module 247, online video module 255 includes instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen or on an external, connected display via external port 224), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module 241, rather than e-mail client module 240, is used to send a link to a particular online video. Additional description of the online video application can be found in U.S. Provisional Patent Application No. 60/936,562, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Jun. 20, 2007, and U.S. patent application Ser. No. 11/968,067, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Dec. 31, 2007, the contents of which are hereby incorporated by reference in their entirety.

Each of the above-identified modules and applications corresponds to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (e.g., sets of instructions) need not be implemented as separate software programs, procedures, or modules, and thus various subsets of these modules can be combined or otherwise rearranged in various embodiments. For example, video player module can be combined with music player module into a single module (e.g., video and music player module 252, FIG. 2A). In some embodiments, memory 202 stores a subset of the modules and data structures identified above. Furthermore, memory 202 stores additional modules and data structures not described above.

In some embodiments, device 200 is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a

touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device **200**, the number of physical input control devices (such as push buttons, dials, and the like) on device **200** is reduced.

The predefined set of functions that are performed exclusively through a touch screen and/or a touchpad optionally include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device **200** to a main, home, or root menu from any user interface that is displayed on device **200**. In such embodiments, a “menu button” is implemented using a touchpad. In some other embodiments, the menu button is a physical push button or other physical input control device instead of a touchpad.

FIG. **2B** is a block diagram illustrating exemplary components for event handling in accordance with some embodiments. In some embodiments, memory **202** (FIG. **2A**) or **470** (FIG. **4**) includes event sorter **270** (e.g., in operating system **226**) and a respective application **236-1** (e.g., any of the aforementioned applications **237-251**, **255**, **480-490**).

Event sorter **270** receives event information and determines the application **236-1** and application view **291** of application **236-1** to which to deliver the event information. Event sorter **270** includes event monitor **271** and event dispatcher module **274**. In some embodiments, application **236-1** includes application internal state **292**, which indicates the current application view(s) displayed on touch-sensitive display **212** when the application is active or executing. In some embodiments, device/global internal state **257** is used by event sorter **270** to determine which application(s) is (are) currently active, and application internal state **292** is used by event sorter **270** to determine application views **291** to which to deliver event information.

In some embodiments, application internal state **292** includes additional information, such as one or more of: resume information to be used when application **236-1** resumes execution, user interface state information that indicates information being displayed or that is ready for display by application **236-1**, a state queue for enabling the user to go back to a prior state or view of application **236-1**, and a redo/undo queue of previous actions taken by the user.

Event monitor **271** receives event information from peripherals interface **218**. Event information includes information about a sub-event (e.g., a user touch on touch-sensitive display **212**, as part of a multi-touch gesture). Peripherals interface **218** transmits information it receives from I/O subsystem **206** or a sensor, such as proximity sensor **266**, accelerometer(s) **268**, and/or microphone **213** (through audio circuitry **210**). Information that peripherals interface **218** receives from I/O subsystem **206** includes information from touch-sensitive display **212** or a touch-sensitive surface.

In some embodiments, event monitor **271** sends requests to the peripherals interface **218** at predetermined intervals. In response, peripherals interface **218** transmits event information. In other embodiments, peripherals interface **218** transmits event information only when there is a significant event (e.g., receiving an input above a predetermined noise threshold and/or for more than a predetermined duration).

In some embodiments, event sorter **270** also includes a hit view determination module **272** and/or an active event recognizer determination module **273**.

Hit view determination module **272** provides software procedures for determining where a sub-event has taken place within one or more views when touch-sensitive dis-

play **212** displays more than one view. Views are made up of controls and other elements that a user can see on the display.

Another aspect of the user interface associated with an application is a set of views, sometimes herein called application views or user interface windows, in which information is displayed and touch-based gestures occur. The application views (of a respective application) in which a touch is detected correspond to programmatic levels within a programmatic or view hierarchy of the application. For example, the lowest level view in which a touch is detected is called the hit view, and the set of events that are recognized as proper inputs is determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

Hit view determination module **272** receives information related to sub events of a touch-based gesture. When an application has multiple views organized in a hierarchy, hit view determination module **272** identifies a hit view as the lowest view in the hierarchy which should handle the sub-event. In most circumstances, the hit view is the lowest level view in which an initiating sub-event occurs (e.g., the first sub-event in the sequence of sub-events that form an event or potential event). Once the hit view is identified by the hit view determination module **272**, the hit view typically receives all sub-events related to the same touch or input source for which it was identified as the hit view.

Active event recognizer determination module **273** determines which view or views within a view hierarchy should receive a particular sequence of sub-events. In some embodiments, active event recognizer determination module **273** determines that only the hit view should receive a particular sequence of sub-events. In other embodiments, active event recognizer determination module **273** determines that all views that include the physical location of a sub-event are actively involved views, and therefore determines that all actively involved views should receive a particular sequence of sub-events. In other embodiments, even if touch sub-events were entirely confined to the area associated with one particular view, views higher in the hierarchy would still remain as actively involved views.

Event dispatcher module **274** dispatches the event information to an event recognizer (e.g., event recognizer **280**). In embodiments including active event recognizer determination module **273**, event dispatcher module **274** delivers the event information to an event recognizer determined by active event recognizer determination module **273**. In some embodiments, event dispatcher module **274** stores in an event queue the event information, which is retrieved by a respective event receiver **282**.

In some embodiments, operating system **226** includes event sorter **270**. Alternatively, application **236-1** includes event sorter **270**. In yet other embodiments, event sorter **270** is a stand-alone module, or a part of another module stored in memory **202**, such as contact/motion module **230**.

In some embodiments, application **236-1** includes a plurality of event handlers **290** and one or more application views **291**, each of which includes instructions for handling touch events that occur within a respective view of the application’s user interface. Each application view **291** of the application **236-1** includes one or more event recognizers **280**. Typically, a respective application view **291** includes a plurality of event recognizers **280**. In other embodiments, one or more of event recognizers **280** are part of a separate module, such as a user interface kit (not shown) or a higher level object from which application **236-1** inherits methods and other properties. In some embodi-

ments, a respective event handler **290** includes one or more of: data updater **276**, object updater **277**, GUI updater **278**, and/or event data **279** received from event sorter **270**. Event handler **290** utilizes or calls data updater **276**, object updater **277**, or GUI updater **278** to update the application internal state **292**. Alternatively, one or more of the application views **291** include one or more respective event handlers **290**. Also, in some embodiments, one or more of data updater **276**, object updater **277**, and GUI updater **278** are included in a respective application view **291**.

A respective event recognizer **280** receives event information (e.g., event data **279**) from event sorter **270** and identifies an event from the event information. Event recognizer **280** includes event receiver **282** and event comparator **284**. In some embodiments, event recognizer **280** also includes at least a subset of: metadata **283**, and event delivery instructions **288** (which include sub-event delivery instructions).

Event receiver **282** receives event information from event sorter **270**. The event information includes information about a sub-event, for example, a touch or a touch movement. Depending on the sub-event, the event information also includes additional information, such as location of the sub-event. When the sub-event concerns motion of a touch, the event information also includes speed and direction of the sub-event. In some embodiments, events include rotation of the device from one orientation to another (e.g., from a portrait orientation to a landscape orientation, or vice versa), and the event information includes corresponding information about the current orientation (also called device attitude) of the device.

Event comparator **284** compares the event information to predefined event or sub-event definitions and, based on the comparison, determines an event or sub event, or determines or updates the state of an event or sub-event. In some embodiments, event comparator **284** includes event definitions **286**. Event definitions **286** contain definitions of events (e.g., predefined sequences of sub-events), for example, event **1** (**287-1**), event **2** (**287-2**), and others. In some embodiments, sub-events in an event (**287**) include, for example, touch begin, touch end, touch movement, touch cancellation, and multiple touching. In one example, the definition for event **1** (**287-1**) is a double tap on a displayed object. The double tap, for example, comprises a first touch (touch begin) on the displayed object for a predetermined phase, a first liftoff (touch end) for a predetermined phase, a second touch (touch begin) on the displayed object for a predetermined phase, and a second liftoff (touch end) for a predetermined phase. In another example, the definition for event **2** (**287-2**) is a dragging on a displayed object. The dragging, for example, comprises a touch (or contact) on the displayed object for a predetermined phase, a movement of the touch across touch-sensitive display **212**, and liftoff of the touch (touch end). In some embodiments, the event also includes information for one or more associated event handlers **290**.

In some embodiments, event definition **287** includes a definition of an event for a respective user-interface object. In some embodiments, event comparator **284** performs a hit test to determine which user-interface object is associated with a sub-event. For example, in an application view in which three user-interface objects are displayed on touch-sensitive display **212**, when a touch is detected on touch-sensitive display **212**, event comparator **284** performs a hit test to determine which of the three user-interface objects is associated with the touch (sub-event). If each displayed object is associated with a respective event handler **290**, the

event comparator uses the result of the hit test to determine which event handler **290** should be activated. For example, event comparator **284** selects an event handler associated with the sub-event and the object triggering the hit test.

In some embodiments, the definition for a respective event (**287**) also includes delayed actions that delay delivery of the event information until after it has been determined whether the sequence of sub-events does or does not correspond to the event recognizer's event type.

When a respective event recognizer **280** determines that the series of sub-events do not match any of the events in event definitions **286**, the respective event recognizer **280** enters an event impossible, event failed, or event ended state, after which it disregards subsequent sub-events of the touch-based gesture. In this situation, other event recognizers, if any, that remain active for the hit view continue to track and process sub-events of an ongoing touch-based gesture.

In some embodiments, a respective event recognizer **280** includes metadata **283** with configurable properties, flags, and/or lists that indicate how the event delivery system should perform sub-event delivery to actively involved event recognizers. In some embodiments, metadata **283** includes configurable properties, flags, and/or lists that indicate how event recognizers interact, or are enabled to interact, with one another. In some embodiments, metadata **283** includes configurable properties, flags, and/or lists that indicate whether sub-events are delivered to varying levels in the view or programmatic hierarchy.

In some embodiments, a respective event recognizer **280** activates event handler **290** associated with an event when one or more particular sub-events of an event are recognized. In some embodiments, a respective event recognizer **280** delivers event information associated with the event to event handler **290**. Activating an event handler **290** is distinct from sending (and deferred sending) sub-events to a respective hit view. In some embodiments, event recognizer **280** throws a flag associated with the recognized event, and event handler **290** associated with the flag catches the flag and performs a predefined process.

In some embodiments, event delivery instructions **288** include sub-event delivery instructions that deliver event information about a sub-event without activating an event handler. Instead, the sub-event delivery instructions deliver event information to event handlers associated with the series of sub-events or to actively involved views. Event handlers associated with the series of sub-events or with actively involved views receive the event information and perform a predetermined process.

In some embodiments, data updater **276** creates and updates data used in application **236-1**. For example, data updater **276** updates the telephone number used in contacts module **237**, or stores a video file used in video player module. In some embodiments, object updater **277** creates and updates objects used in application **236-1**. For example, object updater **277** creates a new user-interface object or updates the position of a user-interface object. GUI updater **278** updates the GUI. For example, GUI updater **278** prepares display information and sends it to graphics module **232** for display on a touch-sensitive display.

In some embodiments, event handler(s) **290** includes or has access to data updater **276**, object updater **277**, and GUI updater **278**. In some embodiments, data updater **276**, object updater **277**, and GUI updater **278** are included in a single module of a respective application **236-1** or application view **291**. In other embodiments, they are included in two or more software modules.

It shall be understood that the foregoing discussion regarding event handling of user touches on touch-sensitive displays also applies to other forms of user inputs to operate multifunction devices 200 with input devices, not all of which are initiated on touch screens. For example, mouse movement and mouse button presses, optionally coordinated with single or multiple keyboard presses or holds; contact movements such as taps, drags, scrolls, etc. on touchpads; pen stylus inputs; movement of the device; oral instructions; detected eye movements; biometric inputs; and/or any combination thereof are optionally utilized as inputs corresponding to sub-events which define an event to be recognized.

FIG. 3 illustrates a portable multifunction device 200 having a touch screen 212 in accordance with some embodiments. The touch screen optionally displays one or more graphics within user interface (UI) 300. In this embodiment, as well as others described below, a user is enabled to select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers 302 (not drawn to scale in the figure) or one or more styluses 303 (not drawn to scale in the figure). In some embodiments, selection of one or more graphics occurs when the user breaks contact with the one or more graphics. In some embodiments, the gesture optionally includes one or more taps, one or more swipes (from left to right, right to left, upward and/or downward), and/or a rolling of a finger (from right to left, left to right, upward and/or downward) that has made contact with device 200. In some implementations or circumstances, inadvertent contact with a graphic does not select the graphic. For example, a swipe gesture that sweeps over an application icon optionally does not select the corresponding application when the gesture corresponding to selection is a tap.

Device 200 also includes one or more physical buttons, such as “home” or menu button 304. As described previously, menu button 304 is used to navigate to any application 236 in a set of applications that is executed on device 200. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI displayed on touch screen 212.

In one embodiment, device 200 includes touch screen 212, menu button 304, push button 306 for powering the device on/off and locking the device, volume adjustment button(s) 308, subscriber identity module (SIM) card slot 310, headset jack 312, and docking/charging external port 224. Push button 306 is, optionally, used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In an alternative embodiment, device 200 also accepts verbal input for activation or deactivation of some functions through microphone 213. Device 200 also, optionally, includes one or more contact intensity sensors 265 for detecting intensity of contacts on touch screen 212 and/or one or more tactile output generators 267 for generating tactile outputs for a user of device 200.

FIG. 4 is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments. Device 400 need not be portable. In some embodiments, device 400 is a laptop computer, a desktop computer, a tablet computer, a multimedia player device, a navigation device, an educational device (such as a child’s learning toy), a gaming system, or a control device (e.g., a home or industrial controller). Device 400 typically includes one or more processing units

(CPUs) 410, one or more network or other communications interfaces 460, memory 470, and one or more communication buses 420 for interconnecting these components. Communication buses 420 optionally include circuitry (sometimes called a chipset) that interconnects and controls communications between system components. Device 400 includes input/output (I/O) interface 430 comprising display 440, which is typically a touch screen display. I/O interface 430 also optionally includes a keyboard and/or mouse (or other pointing device) 450 and touchpad 455, tactile output generator 457 for generating tactile outputs on device 400 (e.g., similar to tactile output generator(s) 267 described above with reference to FIG. 2A), sensors 459 (e.g., optical, acceleration, proximity, touch-sensitive, and/or contact intensity sensors similar to contact intensity sensor(s) 265 described above with reference to FIG. 2A). Memory 470 includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid state memory devices; and optionally includes non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid state storage devices. Memory 470 optionally includes one or more storage devices remotely located from CPU(s) 410. In some embodiments, memory 470 stores programs, modules, and data structures analogous to the programs, modules, and data structures stored in memory 202 of portable multifunction device 200 (FIG. 2A), or a subset thereof. Furthermore, memory 470 optionally stores additional programs, modules, and data structures not present in memory 202 of portable multifunction device 200. For example, memory 470 of device 400 optionally stores drawing module 480, presentation module 482, word processing module 484, website creation module 486, disk authoring module 488, and/or spreadsheet module 490, while memory 202 of portable multifunction device 200 (FIG. 2A) optionally does not store these modules.

Each of the above-identified elements in FIG. 4 is, in some examples, stored in one or more of the previously mentioned memory devices. Each of the above-identified modules corresponds to a set of instructions for performing a function described above. The above-identified modules or programs (e.g., sets of instruction(s) need not be implemented as separate software programs, procedures, or modules, and thus various subsets of these modules are combined or otherwise rearranged in various embodiments. In some embodiments, memory 470 stores a subset of the modules and data structures identified above. Furthermore, memory 470 stores additional modules and data structures not described above.

Attention is now directed towards embodiments of user interfaces that can be implemented on, for example, portable multifunction device 200.

FIG. 5A illustrates an exemplary user interface for a menu of applications on portable multifunction device 200 in accordance with some embodiments. Similar user interfaces are implemented on device 400. In some embodiments, user interface 500 includes the following elements, or a subset or superset thereof:

- Signal strength indicator(s) 502 for wireless communication(s), such as cellular and Wi-Fi signals;
- Time 504;
- Bluetooth indicator 505;
- Battery status indicator 506;
- Tray 508 with icons for frequently used applications, such as:

25

Icon **516** for telephone module **238**, labeled “Phone,” which optionally includes an indicator **514** of the number of missed calls or voicemail messages;

Icon **518** for e-mail client module **240**, labeled “Mail,” which optionally includes an indicator **510** of the number of unread e-mails;

Icon **520** for browser module **247**, labeled “Browser;” and

Icon **522** for video and music player module **252**, also referred to as iPod (trademark of Apple Inc.) module **252**, labeled “iPod;” and

Icons for other applications, such as:

Icon **524** for IM module **241**, labeled “Messages;”

Icon **526** for calendar module **248**, labeled “Calendar;”

Icon **528** for image management module **244**, labeled “Photos;”

Icon **530** for camera module **243**, labeled “Camera;”

Icon **532** for online video module **255**, labeled “Online Video;”

Icon **534** for stocks widget **249-2**, labeled “Stocks;”

Icon **536** for map module **254**, labeled “Maps;”

Icon **538** for weather widget **249-1**, labeled “Weather;”

Icon **540** for alarm clock widget **249-4**, labeled “Clock;”

Icon **542** for workout support module **242**, labeled “Workout Support;”

Icon **544** for notes module **253**, labeled “Notes;” and

Icon **546** for a settings application or module, labeled “Settings,” which provides access to settings for device **200** and its various applications **236**.

It should be noted that the icon labels illustrated in FIG. 5A are merely exemplary. For example, icon **522** for video and music player module **252** is optionally labeled “Music” or “Music Player.” Other labels are, optionally, used for various application icons. In some embodiments, a label for a respective application icon includes a name of an application corresponding to the respective application icon. In some embodiments, a label for a particular application icon is distinct from a name of an application corresponding to the particular application icon.

FIG. 5B illustrates an exemplary user interface on a device (e.g., device **400**, FIG. 4) with a touch-sensitive surface **551** (e.g., a tablet or touchpad **455**, FIG. 4) that is separate from the display **550** (e.g., touch screen display **212**). Device **400** also, optionally, includes one or more contact intensity sensors (e.g., one or more of sensors **457**) for detecting intensity of contacts on touch-sensitive surface **551** and/or one or more tactile output generators **459** for generating tactile outputs for a user of device **400**.

Although some of the examples which follow will be given with reference to inputs on touch screen display **212** (where the touch-sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface that is separate from the display, as shown in FIG. 5B. In some embodiments, the touch-sensitive surface (e.g., **551** in FIG. 5B) has a primary axis (e.g., **552** in FIG. 5B) that corresponds to a primary axis (e.g., **553** in FIG. 5B) on the display (e.g., **550**). In accordance with these embodiments, the device detects contacts (e.g., **560** and **562** in FIG. 5B) with the touch-sensitive surface **551** at locations that correspond to respective locations on the display (e.g., in FIG. 5B, **560** corresponds to **568** and **562** corresponds to **570**). In this way, user inputs (e.g., contacts **560** and **562**, and movements thereof) detected by the device on the touch-sensitive surface (e.g., **551** in FIG. 5B) are used by the device to manipulate the user interface on the display (e.g., **550** in FIG. 5B) of the multifunction device when the

26

touch-sensitive surface is separate from the display. It should be understood that similar methods are, optionally, used for other user interfaces described herein.

Additionally, while the following examples are given primarily with reference to finger inputs (e.g., finger contacts, finger tap gestures, finger swipe gestures), it should be understood that, in some embodiments, one or more of the finger inputs are replaced with input from another input device (e.g., a mouse-based input or stylus input). For example, a swipe gesture is, optionally, replaced with a mouse click (e.g., instead of a contact) followed by movement of the cursor along the path of the swipe (e.g., instead of movement of the contact). As another example, a tap gesture is, optionally, replaced with a mouse click while the cursor is located over the location of the tap gesture (e.g., instead of detection of the contact followed by ceasing to detect the contact). Similarly, when multiple user inputs are simultaneously detected, it should be understood that multiple computer mice are, optionally, used simultaneously, or a mouse and finger contacts are, optionally, used simultaneously.

FIG. 6A illustrates exemplary personal electronic device **600**. Device **600** includes body **602**. In some embodiments, device **600** includes some or all of the features described with respect to devices **200** and **400** (e.g., FIGS. 2A-4). In some embodiments, device **600** has touch-sensitive display screen **604**, hereafter touch screen **604**. Alternatively, or in addition to touch screen **604**, device **600** has a display and a touch-sensitive surface. As with devices **200** and **400**, in some embodiments, touch screen **604** (or the touch-sensitive surface) has one or more intensity sensors for detecting intensity of contacts (e.g., touches) being applied. The one or more intensity sensors of touch screen **604** (or the touch-sensitive surface) provide output data that represents the intensity of touches. The user interface of device **600** responds to touches based on their intensity, meaning that touches of different intensities can invoke different user interface operations on device **600**.

Techniques for detecting and processing touch intensity are found, for example, in related applications: International Patent Application Serial No. PCT/US2013/040061, titled “Device, Method, and Graphical User Interface for Displaying User Interface Objects Corresponding to an Application,” filed May 8, 2013, and International Patent Application Serial No. PCT/US2013/069483, titled “Device, Method, and Graphical User Interface for Transitioning Between Touch Input to Display Output Relationships,” filed Nov. 11, 2013, each of which is hereby incorporated by reference in their entirety.

In some embodiments, device **600** has one or more input mechanisms **606** and **608**. Input mechanisms **606** and **608**, if included, are physical. Examples of physical input mechanisms include push buttons and rotatable mechanisms. In some embodiments, device **600** has one or more attachment mechanisms. Such attachment mechanisms, if included, can permit attachment of device **600** with, for example, hats, eyewear, earrings, necklaces, shirts, jackets, bracelets, watch straps, chains, trousers, belts, shoes, purses, backpacks, and so forth. These attachment mechanisms permit device **600** to be worn by a user.

FIG. 6B depicts exemplary personal electronic device **600**. In some embodiments, device **600** includes some or all of the components described with respect to FIGS. 2A, 2B, and 4. Device **600** has bus **612** that operatively couples I/O section **614** with one or more computer processors **616** and memory **618**. I/O section **614** is connected to display **604**, which can have touch-sensitive component **622** and, option-

ally, touch-intensity sensitive component **624**. In addition, I/O section **614** is connected with communication unit **630** for receiving application and operating system data, using Wi-Fi, Bluetooth, near field communication (NFC), cellular, and/or other wireless communication techniques. Device **600** includes input mechanisms **606** and/or **608**. Input mechanism **606** is a rotatable input device or a depressible and rotatable input device, for example. Input mechanism **608** is a button, in some examples.

Input mechanism **608** is a microphone, in some examples. Personal electronic device **600** includes, for example, various sensors, such as GPS sensor **632**, accelerometer **634**, directional sensor **640** (e.g., compass), gyroscope **636**, motion sensor **638**, and/or a combination thereof, all of which are operatively connected to I/O section **614**.

Memory **618** of personal electronic device **600** is a non-transitory computer-readable storage medium, for storing computer-executable instructions, which, when executed by one or more computer processors **616**, for example, cause the computer processors to perform the techniques and processes described below. The computer-executable instructions, for example, are also stored and/or transported within any non-transitory computer-readable storage medium for use by or in connection with an instruction execution system, apparatus, or device, such as a computer-based system, processor-containing system, or other system that can fetch the instructions from the instruction execution system, apparatus, or device and execute the instructions. Personal electronic device **600** is not limited to the components and configuration of FIG. **6B**, but can include other or additional components in multiple configurations.

As used here, the term “affordance” refers to a user-interactive graphical user interface object that is, for example, displayed on the display screen of devices **200**, **400**, and/or **600** (FIGS. **2A**, **3**, **4**, and **6A-6B**). For example, an image (e.g., icon), a button, and text (e.g., hyperlink) each constitutes an affordance.

As used herein, the term “focus selector” refers to an input element that indicates a current part of a user interface with which a user is interacting. In some implementations that include a cursor or other location marker, the cursor acts as a “focus selector” so that when an input (e.g., a press input) is detected on a touch-sensitive surface (e.g., touchpad **455** in FIG. **4** or touch-sensitive surface **551** in FIG. **5B**) while the cursor is over a particular user interface element (e.g., a button, window, slider or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations that include a touch screen display (e.g., touch-sensitive display system **212** in FIG. **2A** or touch screen **212** in FIG. **5A**) that enables direct interaction with user interface elements on the touch screen display, a detected contact on the touch screen acts as a “focus selector” so that when an input (e.g., a press input by the contact) is detected on the touch screen display at a location of a particular user interface element (e.g., a button, window, slider, or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations, focus is moved from one region of a user interface to another region of the user interface without corresponding movement of a cursor or movement of a contact on a touch screen display (e.g., by using a tab key or arrow keys to move focus from one button to another button); in these implementations, the focus selector moves in accordance with movement of focus between different regions of the user interface. Without regard to the specific form taken by the focus selector, the focus selector is generally the user interface element (or

contact on a touch screen display) that is controlled by the user so as to communicate the user’s intended interaction with the user interface by indicating, to the device, the element of the user interface with which the user is intending to interact). For example, the location of a focus selector (e.g., a cursor, a contact, or a selection box) over a respective button while a press input is detected on the touch-sensitive surface (e.g., a touchpad or touch screen) will indicate that the user is intending to activate the respective button (as opposed to other user interface elements shown on a display of the device).

As used in the specification and claims, the term “characteristic intensity” of a contact refers to a characteristic of the contact based on one or more intensities of the contact. In some embodiments, the characteristic intensity is based on multiple intensity samples. The characteristic intensity is, optionally, based on a predefined number of intensity samples, or a set of intensity samples collected during a predetermined time period (e.g., 0.05, 0.1, 0.2, 0.5, 1, 2, 5, 10 seconds) relative to a predefined event (e.g., after detecting the contact, prior to detecting liftoff of the contact, before or after detecting a start of movement of the contact, prior to detecting an end of the contact, before or after detecting an increase in intensity of the contact, and/or before or after detecting a decrease in intensity of the contact). A characteristic intensity of a contact is, optionally based on one or more of: a maximum value of the intensities of the contact, a mean value of the intensities of the contact, an average value of the intensities of the contact, a top 10 percentile value of the intensities of the contact, a value at the half maximum of the intensities of the contact, a value at the 90 percent maximum of the intensities of the contact, or the like. In some embodiments, the duration of the contact is used in determining the characteristic intensity (e.g., when the characteristic intensity is an average of the intensity of the contact over time). In some embodiments, the characteristic intensity is compared to a set of one or more intensity thresholds to determine whether an operation has been performed by a user. For example, the set of one or more intensity thresholds includes a first intensity threshold and a second intensity threshold. In this example, a contact with a characteristic intensity that does not exceed the first threshold results in a first operation, a contact with a characteristic intensity that exceeds the first intensity threshold and does not exceed the second intensity threshold results in a second operation, and a contact with a characteristic intensity that exceeds the second threshold results in a third operation. In some embodiments, a comparison between the characteristic intensity and one or more thresholds is used to determine whether or not to perform one or more operations (e.g., whether to perform a respective operation or forgo performing the respective operation) rather than being used to determine whether to perform a first operation or a second operation.

In some embodiments, a portion of a gesture is identified for purposes of determining a characteristic intensity. For example, a touch-sensitive surface receives a continuous swipe contact transitioning from a start location and reaching an end location, at which point the intensity of the contact increases. In this example, the characteristic intensity of the contact at the end location is based on only a portion of the continuous swipe contact, and not the entire swipe contact (e.g., only the portion of the swipe contact at the end location). In some embodiments, a smoothing algorithm is applied to the intensities of the swipe contact prior to determining the characteristic intensity of the contact. For example, the smoothing algorithm optionally includes one

or more of: an unweighted sliding-average smoothing algorithm, a triangular smoothing algorithm, a median filter smoothing algorithm, and/or an exponential smoothing algorithm. In some circumstances, these smoothing algorithms eliminate narrow spikes or dips in the intensities of the swipe contact for purposes of determining a characteristic intensity.

The intensity of a contact on the touch-sensitive surface is characterized relative to one or more intensity thresholds, such as a contact-detection intensity threshold, a light press intensity threshold, a deep press intensity threshold, and/or one or more other intensity thresholds. In some embodiments, the light press intensity threshold corresponds to an intensity at which the device will perform operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, the deep press intensity threshold corresponds to an intensity at which the device will perform operations that are different from operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, when a contact is detected with a characteristic intensity below the light press intensity threshold (e.g., and above a nominal contact-detection intensity threshold below which the contact is no longer detected), the device will move a focus selector in accordance with movement of the contact on the touch-sensitive surface without performing an operation associated with the light press intensity threshold or the deep press intensity threshold. Generally, unless otherwise stated, these intensity thresholds are consistent between different sets of user interface figures.

An increase of characteristic intensity of the contact from an intensity below the light press intensity threshold to an intensity between the light press intensity threshold and the deep press intensity threshold is sometimes referred to as a “light press” input. An increase of characteristic intensity of the contact from an intensity below the deep press intensity threshold to an intensity above the deep press intensity threshold is sometimes referred to as a “deep press” input. An increase of characteristic intensity of the contact from an intensity below the contact-detection intensity threshold to an intensity between the contact-detection intensity threshold and the light press intensity threshold is sometimes referred to as detecting the contact on the touch-surface. A decrease of characteristic intensity of the contact from an intensity above the contact-detection intensity threshold to an intensity below the contact-detection intensity threshold is sometimes referred to as detecting liftoff of the contact from the touch-surface. In some embodiments, the contact-detection intensity threshold is zero. In some embodiments, the contact-detection intensity threshold is greater than zero.

In some embodiments described herein, one or more operations are performed in response to detecting a gesture that includes a respective press input or in response to detecting the respective press input performed with a respective contact (or a plurality of contacts), where the respective press input is detected based at least in part on detecting an increase in intensity of the contact (or plurality of contacts) above a press-input intensity threshold. In some embodiments, the respective operation is performed in response to detecting the increase in intensity of the respective contact above the press-input intensity threshold (e.g., a “down stroke” of the respective press input). In some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent

decrease in intensity of the respective contact below the press-input threshold (e.g., an “up stroke” of the respective press input).

In some embodiments, the device employs intensity hysteresis to avoid accidental inputs sometimes termed “jitter,” where the device defines or selects a hysteresis intensity threshold with a predefined relationship to the press-input intensity threshold (e.g., the hysteresis intensity threshold is X intensity units lower than the press-input intensity threshold or the hysteresis intensity threshold is 75%, 90%, or some reasonable proportion of the press-input intensity threshold). Thus, in some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the hysteresis intensity threshold that corresponds to the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the hysteresis intensity threshold (e.g., an “up stroke” of the respective press input). Similarly, in some embodiments, the press input is detected only when the device detects an increase in intensity of the contact from an intensity at or below the hysteresis intensity threshold to an intensity at or above the press-input intensity threshold and, optionally, a subsequent decrease in intensity of the contact to an intensity at or below the hysteresis intensity, and the respective operation is performed in response to detecting the press input (e.g., the increase in intensity of the contact or the decrease in intensity of the contact, depending on the circumstances).

For ease of explanation, the descriptions of operations performed in response to a press input associated with a press-input intensity threshold or in response to a gesture including the press input are, optionally, triggered in response to detecting either: an increase in intensity of a contact above the press-input intensity threshold, an increase in intensity of a contact from an intensity below the hysteresis intensity threshold to an intensity above the press-input intensity threshold, a decrease in intensity of the contact below the press-input intensity threshold, and/or a decrease in intensity of the contact below the hysteresis intensity threshold corresponding to the press-input intensity threshold. Additionally, in examples where an operation is described as being performed in response to detecting a decrease in intensity of a contact below the press-input intensity threshold, the operation is, optionally, performed in response to detecting a decrease in intensity of the contact below a hysteresis intensity threshold corresponding to, and lower than, the press-input intensity threshold.

Digital Assistant System

FIG. 7A illustrates a block diagram of digital assistant system 700 in accordance with various examples. In some examples, digital assistant system 700 is implemented on a standalone computer system. In some examples, digital assistant system 700 is distributed across multiple computers. In some examples, some of the modules and functions of the digital assistant are divided into a server portion and a client portion, where the client portion resides on one or more user devices (e.g., devices 104, 122, 200, 400, or 600) and communicates with the server portion (e.g., server system 108) through one or more networks, e.g., as shown in FIG. 1. In some examples, digital assistant system 700 is an implementation of server system 108 (and/or DA server 106) shown in FIG. 1. It should be noted that digital assistant system 700 is only one example of a digital assistant system, and that digital assistant system 700 can have more or fewer components than shown, can combine two or more compo-

nents, or can have a different configuration or arrangement of the components. The various components shown in FIG. 7A are implemented in hardware, software instructions for execution by one or more processors, firmware, including one or more signal processing and/or application specific integrated circuits, or a combination thereof.

Digital assistant system 700 includes memory 702, one or more processors 704, input/output (I/O) interface 706, and network communications interface 708. These components can communicate with one another over one or more communication buses or signal lines 710.

In some examples, memory 702 includes a non-transitory computer-readable medium, such as high-speed random access memory and/or a non-volatile computer-readable storage medium (e.g., one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices).

In some examples, I/O interface 706 couples input/output devices 716 of digital assistant system 700, such as displays, keyboards, touch screens, and microphones, to user interface module 722. I/O interface 706, in conjunction with user interface module 722, receives user inputs (e.g., voice input, keyboard inputs, touch inputs, etc.) and processes them accordingly. In some examples, e.g., when the digital assistant is implemented on a standalone user device, digital assistant system 700 includes any of the components and I/O communication interfaces described with respect to devices 200, 400, or 600 in FIGS. 2A, 4, 6A-B, respectively. In some examples, digital assistant system 700 represents the server portion of a digital assistant implementation, and can interact with the user through a client-side portion residing on a user device (e.g., devices 104, 200, 400, or 600).

In some examples, the network communications interface 708 includes wired communication port(s) 712 and/or wireless transmission and reception circuitry 714. The wired communication port(s) receives and send communication signals via one or more wired interfaces, e.g., Ethernet, Universal Serial Bus (USB), FIREWIRE, etc. The wireless circuitry 714 receives and sends RF signals and/or optical signals from/to communications networks and other communications devices. The wireless communications use any of a plurality of communications standards, protocols, and technologies, such as GSM, EDGE, CDMA, TDMA, Bluetooth, VoIP, Wi-MAX, or any other suitable communication protocol. Network communications interface 708 enables communication between digital assistant system 700 with networks, such as the Internet, an intranet, and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN), and/or a metropolitan area network (MAN), and other devices.

In some examples, memory 702, or the computer-readable storage media of memory 702, stores programs, modules, instructions, and data structures including all or a subset of: operating system 718, communications module 720, user interface module 722, one or more applications 724, and digital assistant module 726. In particular, memory 702, or the computer-readable storage media of memory 702, stores instructions for performing the processes described below. One or more processors 704 execute these programs, modules, and instructions, and reads/writes from/to the data structures.

Operating system 718 (e.g., Darwin, RTXC, LINUX, UNIX, iOS, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device

control, power management, etc.) and facilitates communications between various hardware, firmware, and software components.

Communications module 720 facilitates communications between digital assistant system 700 with other devices over network communications interface 708. For example, communications module 720 communicates with RF circuitry 208 of electronic devices such as devices 200, 400, and 600 shown in FIG. 2A, 4, 6A-B, respectively. Communications module 720 also includes various components for handling data received by wireless circuitry 714 and/or wired communications port 712.

User interface module 722 receives commands and/or inputs from a user via I/O interface 706 (e.g., from a keyboard, touch screen, pointing device, controller, and/or microphone), and generate user interface objects on a display. User interface module 722 also prepares and delivers outputs (e.g., speech, sound, animation, text, icons, vibrations, haptic feedback, light, etc.) to the user via the I/O interface 706 (e.g., through displays, audio channels, speakers, touch-pads, etc.).

Applications 724 include programs and/or modules that are configured to be executed by one or more processors 704. For example, if the digital assistant system is implemented on a standalone user device, applications 724 include user applications, such as games, a calendar application, a navigation application, or an email application. If digital assistant system 700 is implemented on a server, applications 724 include resource management applications, diagnostic applications, or scheduling applications, for example.

Memory 702 also stores digital assistant module 726 (or the server portion of a digital assistant). In some examples, digital assistant module 726 includes the following sub-modules, or a subset or superset thereof: input/output processing module 728, speech-to-text (STT) processing module 730, natural language processing module 732, dialogue flow processing module 734, task flow processing module 736, service processing module 738, and speech synthesis processing module 740. Each of these modules has access to one or more of the following systems or data and models of the digital assistant module 726, or a subset or superset thereof: ontology 760, vocabulary index 744, user data 748, task flow models 754, service models 756, and ASR systems 758.

In some examples, using the processing modules, data, and models implemented in digital assistant module 726, the digital assistant can perform at least some of the following: converting speech input into text; identifying a user's intent expressed in a natural language input received from the user; actively eliciting and obtaining information needed to fully infer the user's intent (e.g., by disambiguating words, games, intentions, etc.); determining the task flow for fulfilling the inferred intent; and executing the task flow to fulfill the inferred intent.

In some examples, as shown in FIG. 7B, I/O processing module 728 interacts with the user through I/O devices 716 in FIG. 7A or with a user device (e.g., devices 104, 200, 400, or 600) through network communications interface 708 in FIG. 7A to obtain user input (e.g., a speech input) and to provide responses (e.g., as speech outputs) to the user input. I/O processing module 728 optionally obtains contextual information associated with the user input from the user device, along with or shortly after the receipt of the user input. The contextual information includes user-specific data, vocabulary, and/or preferences relevant to the user input. In some examples, the contextual information also

includes software and hardware states of the user device at the time the user request is received, and/or information related to the surrounding environment of the user at the time that the user request was received. In some examples, I/O processing module 728 also sends follow-up questions to, and receive answers from, the user regarding the user request. When a user request is received by I/O processing module 728 and the user request includes speech input, I/O processing module 728 forwards the speech input to STT processing module 730 (or speech recognizer) for speech-to-text conversions.

STT processing module 730 includes one or more ASR systems 758. The one or more ASR systems 758 can process the speech input that is received through I/O processing module 728 to produce a recognition result. Each ASR system 758 includes a front-end speech pre-processor. The front-end speech pre-processor extracts representative features from the speech input. For example, the front-end speech pre-processor performs a Fourier transform on the speech input to extract spectral features that characterize the speech input as a sequence of representative multi-dimensional vectors. Further, each ASR system 758 includes one or more speech recognition models (e.g., acoustic models and/or language models) and implements one or more speech recognition engines. Examples of speech recognition models include I-hidden Markov Models, Gaussian-Mixture Models, Deep Neural Network Models, n-gram language models, and other statistical models. Examples of speech recognition engines include the dynamic time warping based engines and weighted finite-state transducers (WFST) based engines. The one or more speech recognition models and the one or more speech recognition engines are used to process the extracted representative features of the front-end speech pre-processor to produce intermediate recognitions results (e.g., phonemes, phonemic strings, and sub-words), and ultimately, text recognition results (e.g., words, word strings, or sequence of tokens). In some examples, the speech input is processed at least partially by a third-party service or on the user's device (e.g., device 104, 200, 400, or 600) to produce the recognition result. Once STT processing module 730 produces recognition results containing a text string (e.g., words, or sequence of words, or sequence of tokens), the recognition result is passed to natural language processing module 732 for intent deduction. In some examples, STT processing module 730 produces multiple candidate text representations of the speech input. Each candidate text representation is a sequence of words or tokens corresponding to the speech input. In some examples, each candidate text representation is associated with a speech recognition confidence score. Based on the speech recognition confidence scores, STT processing module 730 ranks the candidate text representations and provides the n-best (e.g., n highest ranked) candidate text representation(s) to natural language processing module 732 for intent deduction, where n is a predetermined integer greater than zero. For example, in one example, only the highest ranked (n=1) candidate text representation is passed to natural language processing module 732 for intent deduction. In another example, the five highest ranked (n=5) candidate text representations are passed to natural language processing module 732 for intent deduction.

More details on the speech-to-text processing are described in U.S. Utility application Ser. No. 13/236,942 for "Consolidating Speech Recognition Results," filed on Sep. 20, 2011, the entire disclosure of which is incorporated herein by reference.

In some examples, STT processing module 730 includes and/or accesses a vocabulary of recognizable words via phonetic alphabet conversion module 731. Each vocabulary word is associated with one or more candidate pronunciations of the word represented in a speech recognition phonetic alphabet. In particular, the vocabulary of recognizable words includes a word that is associated with a plurality of candidate pronunciations. For example, the vocabulary includes the word "tomato" that is associated with the candidate pronunciations of /tə'meɪroʊ/ and t/tə'matoʊ/. Further, vocabulary words are associated with custom candidate pronunciations that are based on previous speech inputs from the user. Such custom candidate pronunciations are stored in STT processing module 730 and are associated with a particular user via the user's profile on the device. In some examples, the candidate pronunciations for words are determined based on the spelling of the word and one or more linguistic and/or phonetic rules. In some examples, the candidate pronunciations are manually generated, e.g., based on known canonical pronunciations.

In some examples, the candidate pronunciations are ranked based on the commonness of the candidate pronunciation. For example, the candidate pronunciation t/tə'meɪroʊ/ is ranked higher than t/tə'matoʊ/, because the former is a more commonly used pronunciation (e.g., among all users, for users in a particular geographical region, or for any other appropriate subset of users). In some examples, candidate pronunciations are ranked based on whether the candidate pronunciation is a custom candidate pronunciation associated with the user. For example, custom candidate pronunciations are ranked higher than canonical candidate pronunciations. This can be useful for recognizing proper nouns having a unique pronunciation that deviates from canonical pronunciation. In some examples, candidate pronunciations are associated with one or more speech characteristics, such as geographic origin, nationality, or ethnicity. For example, the candidate pronunciation t/tə'meɪroʊ/ is associated with the United States, whereas the candidate pronunciation t/tə'matoʊ/ is associated with Great Britain. Further, the rank of the candidate pronunciation is based on one or more characteristics geographic origin, nationality, ethnicity, etc.) of the user stored in the user's profile on the device. For example, it can be determined from the user's profile that the user is associated with the United States. Based on the user being associated with the United States, the candidate pronunciation t/tə'meɪroʊ/ (associated with the United States) is ranked higher than the candidate pronunciation t/tə'matoʊ/ (associated with Great Britain). In some examples, one of the ranked candidate pronunciations is selected as a predicted pronunciation (e.g., the most likely pronunciation).

When a speech input is received, STT processing module 730 is used to determine the phonemes corresponding to the speech input (e.g., using an acoustic model), and then attempt to determine words that match the phonemes (e.g., using a language model). For example, if STT processing module 730 first identifies the sequence of phonemes t/tə'meɪroʊ/ corresponding to a portion of the speech input, it can then determine, based on vocabulary index 744, that this sequence corresponds to the word "tomato."

In some examples, STT processing module 730 uses approximate matching techniques to determine words in an utterance. Thus, for example, the STT processing module 730 determines that the sequence of phonemes t/tə'meɪroʊ/ corresponds to the word "tomato," even if that

particular sequence of phonemes is not one of the candidate sequence of phonemes for that word.

Natural language processing module 732 ("natural language processor") of the digital assistant takes the n-best candidate text representation(s) ("word sequence(s)" or "token sequence(s)") generated by STT processing module 730, and attempts to associate each of the candidate text representations with one or more "actionable intents" recognized by the digital assistant. An "actionable intent" (or "user intent") represents a task that can be performed by the digital assistant, and can have an associated task flow implemented in task flow models 754. The associated task flow is a series of programmed actions and steps that the digital assistant takes in order to perform the task. The scope of a digital assistant's capabilities is dependent on the number and variety of task flows that have been implemented and stored in task flow models 754, or in other words, on the number and variety of "actionable intents" that the digital assistant recognizes. The effectiveness of the digital assistant, however, also depends on the assistant's ability to infer the correct "actionable intent(s)" from the user request expressed in natural language.

In some examples, in addition to the sequence of words or tokens obtained from STT processing module 730, natural language processing module 732 also receives contextual information associated with the user request, e.g., from I/O processing module 728. The natural language processing module 732 optionally uses the contextual information to clarify, supplement, and/or further define the information contained in the candidate text representations received from STT processing module 730. The contextual information includes, for example, user preferences, hardware, and/or software states of the user device, sensor information collected before, during, or shortly after the user request, prior interactions (e.g., dialogue) between the digital assistant and the user, and the like. As described herein, contextual information is, in some examples, dynamic, and changes with time, location, content of the dialogue, and other factors.

In some examples, the natural language processing is based on, e.g., ontology 760. Ontology 760 is a hierarchical structure containing many nodes, each node representing either an "actionable intent" or a "property" relevant to one or more of the "actionable intents" or other "properties." As noted above, an "actionable intent" represents a task that the digital assistant is capable of performing, i.e., it is "actionable" or can be acted on. A "property" represents a parameter associated with an actionable intent or a sub-aspect of another property. A linkage between an actionable intent node and a property node in ontology 760 defines how a parameter represented by the property node pertains to the task represented by the actionable intent node.

In some examples, ontology 760 is made up of actionable intent nodes and property nodes. Within ontology 760, each actionable intent node is linked to one or more property nodes either directly or through one or more intermediate property nodes. Similarly, each property node is linked to one or more actionable intent nodes either directly or through one or more intermediate property nodes. For example, as shown in FIG. 7C, ontology 760 includes a "restaurant reservation" node (i.e., an actionable intent node). Property nodes "restaurant," "date/time" (for the reservation), and "party size" are each directly linked to the actionable intent node (i.e., the "restaurant reservation" node).

In addition, property nodes "cuisine," "price range," "phone number," and "location" are sub-nodes of the prop-

erty node "restaurant," and are each linked to the "restaurant reservation" node (i.e., the actionable intent node) through the intermediate property node "restaurant." For another example, as shown in FIG. 7C, ontology 760 also includes a "set reminder" node (i.e., another actionable intent node). Property nodes "date/time" (for setting the reminder) and "subject" (for the reminder) are each linked to the "set reminder" node. Since the property "date/time" is relevant to both the task of making a restaurant reservation and the task of setting a reminder, the property node "date/time" is linked to both the "restaurant reservation" node and the "set reminder" node in ontology 760.

An actionable intent node, along with its linked property nodes, is described as a "domain." In the present discussion, each domain is associated with a respective actionable intent, and refers to the group of nodes (and the relationships there between) associated with the particular actionable intent. For example, ontology 760 shown in FIG. 7C includes an example of restaurant reservation domain 762 and an example of reminder domain 764 within ontology 760. The restaurant reservation domain includes the actionable intent node "restaurant reservation," property nodes "restaurant," "date/time," and "party size," and sub-property nodes "cuisine," "price range," "phone number," and "location." Reminder domain 764 includes the actionable intent node "set reminder," and property nodes "subject" and "date/time." In some examples, ontology 760 is made up of many domains. Each domain shares one or more property nodes with one or more other domains. For example, the "date/time" property node is associated with many different domains (e.g., a scheduling domain, a travel reservation domain, a movie ticket domain, etc.), in addition to restaurant reservation domain 762 and reminder domain 764.

While FIG. 7C illustrates two example domains within ontology 760, other domains include, for example, "find a movie," "initiate a phone call," "find directions," "schedule a meeting," "send a message," and "provide an answer to a question," "read a list," "providing navigation instructions," "provide instructions for a task" and so on. A "send a message" domain is associated with a "send a message" actionable intent node, and further includes property nodes such as "recipient(s)," "message type," and "message body." The property node "recipient" is further defined, for example, by the sub-property nodes such as "recipient name" and "message address."

In some examples, ontology 760 includes all the domains (and hence actionable intents) that the digital assistant is capable of understanding and acting upon. In some examples, ontology 760 is modified, such as by adding or removing entire domains or nodes, or by modifying relationships between the nodes within the ontology 760.

In some examples, nodes associated with multiple related actionable intents are clustered under a "super domain" in ontology 760. For example, a "travel" super-domain includes a cluster of property nodes and actionable intent nodes related to travel. The actionable intent nodes related to travel includes "airline reservation," "hotel reservation," "car rental," "get directions," "find points of interest," and so on. The actionable intent nodes under the same super domain (e.g., the "travel" super domain) have many property nodes in common. For example, the actionable intent nodes for "airline reservation," "hotel reservation," "car rental," "get directions," and "find points of interest" share one or more of the property nodes "start location," "destination," "departure date/time," "arrival date/time," and "party size."

In some examples, each node in ontology **760** is associated with a set of words and/or phrases that are relevant to the property or actionable intent represented by the node. The respective set of words and/or phrases associated with each node are the so-called “vocabulary” associated with the node. The respective set of words and/or phrases associated with each node are stored in vocabulary index **744** in association with the property or actionable intent represented by the node. For example, returning to FIG. 7B, the vocabulary associated with the node for the property of “restaurant” includes words such as “food,” “drinks,” “cuisine,” “hungry,” “eat,” “pizza,” “fast food,” “meal,” and so on. For another example, the vocabulary associated with the node for the actionable intent of “initiate a phone call” includes words and phrases such as “call,” “phone,” “dial,” “ring,” “call this number,” “make a call to,” and so on. The vocabulary index **744** optionally includes words and phrases in different languages.

Natural language processing module **732** receives the candidate text representations (e.g., text string(s) or token sequence(s)) from STT processing module **730**, and for each candidate representation, determines what nodes are implicated by the words in the candidate text representation. In some examples, if a word or phrase in the candidate text representation is found to be associated with one or more nodes in ontology **760** (via vocabulary index **744**), the word or phrase “triggers” or “activates” those nodes. Based on the quantity and/or relative importance of the activated nodes, natural language processing module **732** selects one of the actionable intents as the task that the user intended the digital assistant to perform. In some examples, the domain that has the most “triggered” nodes is selected. In some examples, the domain having the highest confidence value (e.g., based on the relative importance of its various triggered nodes) is selected. In some examples, the domain is selected based on a combination of the number and the importance of the triggered nodes. In some examples, additional factors are considered in selecting the node as well, such as whether the digital assistant has previously correctly interpreted a similar request from a user.

User data **748** includes user-specific information, such as user-specific vocabulary, user preferences, user address, user’s default and secondary languages, user’s contact list, and other short-term or long-term information for each user. In some examples, natural language processing module **732** uses the user-specific information to supplement the information contained in the user input to further define the user intent. For example, for a user request “invite my friends to my birthday party,” natural language processing module **732** is able to access user data **748** to determine who the “friends” are and when and where the “birthday party” would be held, rather than requiring the user to provide such information explicitly in his/her request.

It should be recognized that in some examples, natural language processing module **732** is implemented using one or more machine learning mechanisms (e.g., neural networks). In particular, the one or more machine learning mechanisms are configured to receive a candidate text representation and contextual information associated with the candidate text representation. Based on the candidate text representation and the associated contextual information, the one or more machine learning mechanisms are configured to determine intent confidence scores over a set of candidate actionable intents. Natural language processing module **732** can select one or more candidate actionable intents from the set of candidate actionable intents based on the determined intent confidence scores. In some examples,

an ontology (e.g., ontology **760**) is also used to select the one or more candidate actionable intents from the set of candidate actionable intents.

Other details of searching an ontology based on a token string are described in U.S. Utility application Ser. No. 12/341,743 for “Method and Apparatus for Searching Using An Active Ontology,” filed Dec. 22, 2008, the entire disclosure of which is incorporated herein by reference.

In some examples, once natural language processing module **732** identifies an actionable intent (or domain) based on the user request, natural language processing module **732** generates a structured query to represent the identified actionable intent. In some examples, the structured query includes parameters for one or more nodes within the domain for the actionable intent, and at least some of the parameters are populated with the specific information and requirements specified in the user request. For example, the user says “Make me a dinner reservation at a sushi place at 7.” In this case, natural language processing module **732** is able to correctly identify the actionable intent to be “restaurant reservation” based on the user input. According to the ontology, a structured query for a “restaurant reservation” domain includes parameters such as {Cuisine}, {Time}, {Date}, {Party Size}, and the like. In some examples, based on the speech input and the text derived from the speech input using STT processing module **730**, natural language processing module **732** generates a partial structured query for the restaurant reservation domain, where the partial structured query includes the parameters {Cuisine=“Sushi”} and {Time=“7 pm”}. However, in this example, the user’s utterance contains insufficient information to complete the structured query associated with the domain. Therefore, other necessary parameters such as {Party Size} and {Date} are not specified in the structured query based on the information currently available. In some examples, natural language processing module **732** populates some parameters of the structured query with received contextual information. For example, in some examples, if the user requested a sushi restaurant “near me,” natural language processing module **732** populates a {location} parameter in the structured query with GPS coordinates from the user device.

In some examples, natural language processing module **732** identifies multiple candidate actionable intents for each candidate text representation received from STT processing module **730**. Further, in some examples, a respective structured query (partial or complete) is generated for each identified candidate actionable intent. Natural language processing module **732** determines an intent confidence score for each candidate actionable intent and ranks the candidate actionable intents based on the intent confidence scores. In some examples, natural language processing module **732** passes the generated structured query (or queries), including any completed parameters, to task flow processing module **736** (“task flow processor”). In some examples, the structured query (or queries) for the m-best (e.g., m highest ranked) candidate actionable intents are provided to task flow processing module **736**, where m is a predetermined integer greater than zero. In some examples, the structured query (or queries) for the m-best candidate actionable intents are provided to task flow processing module **736** with the corresponding candidate text representation(s).

Other details of inferring a user intent based on multiple candidate actionable intents determined from multiple candidate text representations of a speech input are described in U.S. Utility application Ser. No. 14/298,725 for “System and

Method for Inferring User Intent From Speech Inputs,” filed Jun. 6, 2014, the entire disclosure of which is incorporated herein by reference.

Task flow processing module 736 is configured to receive the structured query (or queries) from natural language processing module 732, complete the structured query, if necessary, and perform the actions required to “complete” the user’s ultimate request. In some examples, the various procedures necessary to complete these tasks are provided in task flow models 754. In some examples, task flow models 754 include procedures for obtaining additional information from the user and task flows for performing actions associated with the actionable intent.

As described above, in order to complete a structured query, task flow processing module 736 needs to initiate additional dialogue with the user in order to obtain additional information, and/or disambiguate potentially ambiguous utterances. When such interactions are necessary, task flow processing module 736 invokes dialogue flow processing module 734 to engage in a dialogue with the user. In some examples, dialogue flow processing module 734 determines how (and/or when) to ask the user for the additional information and receives and processes the user responses. The questions are provided to and answers are received from the users through I/O processing module 728. In some examples, dialogue flow processing module 734 presents dialogue output to the user via audio and/or visual output, and receives input from the user via spoken or physical (e.g., clicking) responses. Continuing with the example above, when task flow processing module 736 invokes dialogue flow processing module 734 to determine the “party size” and “date” information for the structured query associated with the domain “restaurant reservation,” dialogue flow processing module 734 generates questions such as “For how many people?” and “On which day?” to pass to the user. Once answers are received from the user, dialogue flow processing module 734 then populates the structured query with the missing information, or pass the information to task flow processing module 736 to complete the missing information from the structured query.

Once task flow processing module 736 has completed the structured query for an actionable intent, task flow processing module 736 proceeds to perform the ultimate task associated with the actionable intent. Accordingly, task flow processing module 736 executes the steps and instructions in the task flow model according to the specific parameters contained in the structured query. For example, the task flow model for the actionable intent of “restaurant reservation” includes steps and instructions for contacting a restaurant and actually requesting a reservation for a particular party size at a particular time. For example, using a structured query such as: {restaurant reservation, restaurant=ABC Café, date=Mar. 12, 2012, time=7 pm, party size=5}, task flow processing module 736 performs the steps of: (1) logging onto a server of the ABC Café or a restaurant reservation system such as OPENTABLE®, (2) entering the date, time, and party size information in a form on the website, (3) submitting the form, and (4) making a calendar entry for the reservation in the user’s calendar.

In some examples, task flow processing module 736 employs the assistance of service processing module 738 (“service processing module”) to complete a task requested in the user input or to provide an informational answer requested in the user input. For example, service processing module 738 acts on behalf of task flow processing module 736 to make a phone call, set a calendar entry, invoke a map search, invoke or interact with other user applications

installed on the user device, and invoke or interact with third-party services (e.g., a restaurant reservation portal, a social networking website, a banking portal, etc.). In some examples, the protocols and application programming interfaces (API) required by each service are specified by a respective service model among service models 756. Service processing module 738 accesses the appropriate service model for a service and generates requests for the service in accordance with the protocols and APIs required by the service according to the service model.

For example, if a restaurant has enabled an online reservation service, the restaurant submits a service model specifying the necessary parameters for making a reservation and the APIs for communicating the values of the necessary parameter to the online reservation service. When requested by task flow processing module 736, service processing module 738 establishes a network connection with the online reservation service using the web address stored in the service model, and sends the necessary parameters of the reservation (e.g., time, date, party size) to the online reservation interface in a format according to the API of the online reservation service.

In some examples, natural language processing module 732, dialogue flow processing module 734, and task flow processing module 736 are used collectively and iteratively to infer and define the user’s intent, obtain information to further clarify and refine the user intent, and finally generate a response (i.e., an output to the user, or the completion of a task) to fulfill the user’s intent. The generated response is a dialogue response to the speech input that at least partially fulfills the user’s intent. Further, in some examples, the generated response is output as a speech output. In these examples, the generated response is sent to speech synthesis processing module 740 (e.g., speech synthesizer) where it can be processed to synthesize the dialogue response in speech form. In yet other examples, the generated response is data content relevant to satisfying a user request in the speech input.

In examples where task flow processing module 736 receives multiple structured queries from natural language processing module 732, task flow processing module 736 initially processes the first structured query of the received structured queries to attempt to complete the first structured query and/or execute one or more tasks or actions represented by the first structured query. In some examples, the first structured query corresponds to the highest ranked actionable intent. In other examples, the first structured query is selected from the received structured queries based on a combination of the corresponding speech recognition confidence scores and the corresponding intent confidence scores. In some examples, if task flow processing module 736 encounters an error during processing of the first structured query (e.g., due to an inability to determine a necessary parameter), the task flow processing module 736 can proceed to select and process a second structured query of the received structured queries that corresponds to a lower ranked actionable intent. The second structured query is selected, for example, based on the speech recognition confidence score of the corresponding candidate text representation, the intent confidence score of the corresponding candidate actionable intent, a missing necessary parameter in the first structured query, or any combination thereof.

Speech synthesis processing module 740 is configured to synthesize speech outputs for presentation to the user. Speech synthesis processing module 740 synthesizes speech outputs based on text provided by the digital assistant. For example, the generated dialogue response is in the form of

a text string. Speech synthesis processing module **740** converts the text string to an audible speech output. Speech synthesis processing module **740** uses any appropriate speech synthesis technique in order to generate speech outputs from text, including, but not limited to, concatenative synthesis, unit selection synthesis, diphone synthesis, domain-specific synthesis, formant synthesis, articulatory synthesis, hidden Markov model (HMM) based synthesis, and sinewave synthesis. In some examples, speech synthesis processing module **740** is configured to synthesize individual words based on phonemic strings corresponding to the words. For example, a phonemic string is associated with a word in the generated dialogue response. The phonemic string is stored in metadata associated with the word. Speech synthesis processing module **740** is configured to directly process the phonemic string in the metadata to synthesize the word in speech form.

In some examples, instead of (or in addition to) using speech synthesis processing module **740**, speech synthesis is performed on a remote device (e.g., the server system **108**), and the synthesized speech is sent to the user device for output to the user. For example, this can occur in some implementations where outputs for a digital assistant are generated at a server system. And because server systems generally have more processing power or resources than a user device, it is possible to obtain higher quality speech outputs than would be practical with client-side synthesis.

Additional details on digital assistants can be found in the U.S. Utility application Ser. No. 12/987,982, entitled "Intelligent Automated Assistant," filed Jan. 10, 2011, and U.S. Utility application Ser. No. 13/251,088, entitled "Generating and Processing Task Items That Represent Tasks to Perform," filed Sep. 30, 2011, the entire disclosures of which are incorporated herein by reference.

4. Process for Providing Multi-Directional Dialog

FIG. **8** illustrates process **800** for providing multi-directional dialog, according to various examples. Process **800** is performed, for example, using one or more electronic devices implementing a digital assistant. In some examples, process **800** is performed using a client-server system (e.g., system **100**), and the blocks of process **800** are divided up in any manner between the server (e.g., DA server **106**) and a client device. In other examples, the blocks of process **800** are divided up between the server and multiple client devices (e.g., a mobile phone and a smart watch). Thus, while portions of process **800** are described herein as being performed by particular devices of a client-server system, it will be appreciated that process **800** is not so limited. In other examples, process **800** is performed using only a client device (e.g., user device **104**) or only multiple client devices. In process **800**, some blocks are, optionally, combined, the order of some blocks is, optionally, changed, and some blocks are, optionally, omitted. In some examples, additional steps may be performed in combination with the process **800**.

Generally, the process **800** may be implemented to provide multi-directional dialog, for instance, using an electronic device. In accordance with examples of the present disclosure, multi-directional dialog is a dialog exchanged between a user and an electronic device, and in some examples, between a user and a digital assistant of the electronic device. In some examples, multi-directional dialog is employed using one or more dialog flows. In some examples, a dialog flow may be a set of predetermined states between which the electronic device transitions to exchange dialog with a user. As will be explained in more detail below, each state of a dialog flow may specify criteria for transi-

tioning to a new state (different criteria may be associated with transitions to different states)

By way of example, in response to an initial user input, an electronic device selects a dialog flow. The dialog flow may be selected based on an intent associated with the input, for instance. The electronic device then responds to the user input in a manner specified by the dialog flow. The dialog flow may, for instance, specify that the electronic device perform one or more tasks and/or provide a particular natural-language output to the user. Thereafter, the electronic device exchanges dialog with the user according to the dialog flow and/or context of the electronic device.

In some examples, in implementing a dialog flow, the electronic device transitions between a respective set of states. In this manner, the electronic device transitions to a new state after each iteration of dialog exchanged between the user and the electronic device. As will be described, the manner in which the electronic device transitions states is based on whether various sets of criteria are satisfied.

In an example operation, an electronic device receives a first natural-language input from a user of the electronic device and determines a first intent based on the first natural-language input. The electronic device then identifies a first dialog flow based on the first intent and provides (e.g., outputs) a natural-language output associated with the first dialog flow. The electronic device further receives a second natural-language input and if the second natural-language input satisfies dialog criteria associated with the first dialog flow, the electronic device provides a second natural-language output associated with the first dialog flow. If the second natural-language input does not satisfy the dialog criteria, the electronic device provides a third natural-language output associated with the first dialog flow, or provides a natural-language output associated with a second dialog flow.

At block **805**, the electronic device receives a natural-language input. In some examples, the electronic device is electronic device **104** (FIG. **1**). The natural-language input can include a speech input (e.g., spoken utterance) or a text input. In some examples, the natural-language input includes a request for the electronic device and/or another device to perform a task. For instance, in an example where a users states "I want to buy an iPhone X," the natural-language input includes a request for an electronic device, and optionally, for a digital assistant of the electronic device, to assist a user in purchasing a device. In some examples, the natural-language input may further specify one or more parameters for the requested task. The recited portion of the natural-language input "iPhone X", for instance, may specify a model of the device. Whether the natural-language input is directed to a particular task may in some cases be determined by the electronic device, for instance, by disambiguating the parameter based on another input and/or based on context information of the electronic device.

At block **810**, the electronic device determines an intent based on the natural-language input. In some examples, the electronic device determines the intent using a machine-learned system. The machine-learned system may, for instance, include a neural network, such as a classification network, which may be trained using supervised and/or unsupervised training.

In some examples, the machine-learned system receives the natural-language input and determines a confidence score for each of a plurality of intents based on the natural-language input. Each of the confidence scores indicates a likelihood that a respective intent associated with the confidence score corresponds to the natural-language input. The

intent associated with the highest confidence score is returned as the intent determined based on the natural-language input. In some examples, the machine-learned system further corrects one or more aspects of the natural-language input. The machine-learned system corrects, for instance, spelling mistakes, emojis, and other spurious portions of the NL input, such as words identified as improperly translated from text. By way of example, the input “I want to be an iPhone ☺” may be modified to “I want to buy an iPhone,” prior to determining an intent based on the input.

At block 815, the electronic device identifies a first dialog flow based on the determined intent. In some examples, each intent is associated with a respective dialog flow and, the electronic device identifies the dialog flow associated with the intent determined at block 810.

In other examples, multiple dialog flows are associated with each intent and the electronic device selects a dialog flow based on the natural-language input and/or context of the electronic device. By way of example, based on the natural-language input “I want to buy an iPhone X,” the electronic device may determine that the intent associated with the natural-language input is “Product Purchase”. If multiple dialog flows are associated with the intent “Product Purchase” (e.g., one dialog flow for each product available for purchase), the electronic device identifies a “Product Purchase” dialog flow associated with the “iPhone X” product. As another example, based on the natural-language input, “I want to repair my phone”, the electronic device may determine that the intent associated with the natural-language input is “Product Repair”. If multiple dialog flows are associated with the intent “Product Repair”, the electronic device identifies a model of the user’s phone and a “Product Repair” dialog flow associated with the model of the user’s phone.

At block 820, the electronic device outputs a natural-language output associated with the first dialog flow. In some examples, the natural-language output is a visual output (e.g., displayed on a display of the electronic device) and/or an auditory output.

As described, in some examples, a dialog flow dictates the manner in which the electronic device responds. Accordingly, the electronic device provides a natural-language output specified by the first dialog flow. By way of example, in response to the natural-language input “I want to repair my phone”, the selected dialog flow may cause the electronic device to provide the natural-language output “Okay. What would you like to repair?”

At block 825, the electronic device receives another (e.g., second) natural-language input. The natural-language input can include a speech input or a text input. In some examples, the natural-language input includes a request for the electronic device and/or another device to perform a task.

At block 830, the electronic device determines whether the second natural-language input satisfies dialog criteria associated with the selected dialog flow. In some examples, determining whether the second natural-language input satisfies dialog criteria includes determining whether an intent associated with the second natural-language input matches the intent associated with the first natural-language input (recall that an intent is determined at block 810).

If the electronic device determines that the second natural-language input satisfies the dialog criteria, at block 835, the electronic device outputs a second natural-language output associated with the first dialog flow, and optionally, performs one or more tasks specified by the dialog flow. Consider for instance, the following dialog exchange:

User: “I want to repair my phone”

Electronic device: “Okay. What would you like to repair?”

User: “My display is cracked.”

Based on this exchange, the electronic device determines the input “My display is cracked” is associated with a same intent as the input “I want to repair my phone” (i.e., “Product Repair” intent). Accordingly, the electronic device responds as specified by the selected dialog flow, and optionally, transitions to a next state specified the dialog flow. The electronic device may reply, for instance, “Would you like to repair or replace your display?” and/or perform one or more tasks, such as retrieving the respective costs of repairing a display of the user’s phone and replacing a display of the user’s phone.

If the electronic device determines that the second natural-language input does not satisfy the dialog criteria, the electronic device forgoes outputting the second natural-language output associated with the first dialog flow. Consider for instance, the following dialog exchange:

User: “I want to repair my phone”

Electronic device: “Okay. What would you like to repair?”

User: “I changed my mind. I want to buy a new phone.”

Based on this exchange, the electronic device determines whether the input “I want to repair my phone” is associated with a same intent as the input “I changed my mind. I want to buy a new phone.” Because the input “I want to repair my phone” is associated with the intent “Product Repair” and the input “I changed my mind. I want to buy a new phone.” is associated with the intent “Product Purchase”, the electronic device determines that the inputs are associated with different respective intents. As a result, the electronic device determines that the dialog criteria are not satisfied and forgoes providing the second natural-language output.

Optionally, in response to determining that dialog criteria are not satisfied, the electronic device further determines whether dialog context criteria are met. If the dialog context criteria is satisfied, the electronic device provides a third natural-language output associated with the dialog flow. In some examples, determining whether dialog context criteria are met includes determining whether the second natural-language input is associated with a particular intent specified by the dialog flow. By way of example, while employing a dialog flow for “Product Repair”, a user may provide an input associated with an intent to purchase a new product (e.g., “I changed my mind. I want to buy a new phone”). The dialog flow for “Product Repair” may specify that if the electronic device receives an input associated with the intent “Product Purchase”, the electronic device is to provide a particular natural-language output to the user, such as “Are you sure? Repairing your device would be cheaper than purchasing a new device. Would you still like to purchase a new phone?” In some examples, if dialog context criteria is satisfied, the dialog flow may further cause the electronic device to perform one or more tasks. The dialog flow may cause the electronic device to retrieve costs of repair of a device and the purchase price of a new device and/or present (e.g., display) the costs to a user, for instance.

In some examples, dialog context criteria is state-specific (e.g., context-specific). For example, whether dialog context criteria is satisfied may be based on whether the electronic device is currently in a particular state of the dialog flow. Consider the following dialog exchanges:

45

First Dialog Exchange:

User: "I want to repair my phone"

Electronic device: "Okay. What would you like to repair?"

User: My display is cracked.

Electronic device: "Would you like to repair or replace your display?"

User: "I changed my mind. I want to buy a new phone."

Electronic Device: "Are you sure? Repairing your device would be cheaper than purchasing a new device. Would you still like to purchase a new phone?"

Second Dialog Exchange:

User: "I want to repair my phone"

Electronic device: "Okay. What would you like to repair?"

User: "I changed my mind. I want to buy a new phone."

Electronic Device: "Okay. What type of phone would you like to purchase?"

In the first dialog exchange, the dialog context criteria is satisfied. As a result, the electronic device provides the natural-language output "Are you sure? Repairing your device would be cheaper than purchasing a new device. Would you still like to purchase a new phone?", associated with the dialog flow. In the second dialog exchange, the dialog context criteria is not satisfied. As a result, the electronic device provides the natural-language output "Okay. What type of phone would you like to purchase?", which may, for instance, be a natural-language output associated with a different dialog flow, as described in further detail below.

In some examples, in response to determining that dialog criteria are not satisfied (and optionally, further in response to determining the dialog context criteria are not satisfied), the electronic device selects a dialog flow associated with the intent of the second natural-language input. By way of example, the electronic device selects a dialog flow associated with the "Product Purchase" intent in response to the input "I changed my mind. I want to buy a new phone" and responds to the input according to the "Product Purchase" dialog flow. For example, the electronic device provides the natural-language output "Okay. What type of phone would you like to purchase?" Operation may thereafter continue according to the newly selected dialog flow.

In this manner, the electronic device may transition between dialog flows in response to provide a user with a more flexible and intuitive dialog framework. In some examples, parameters provided by the user and/or context of the electronic device may be applied to newly selected dialog flows. As an example, a user may indicate a desire to repair his or her device and in doing so indicate a model of the device to be repaired. If the user subsequently indicates a desire to instead replace the device, the electronic device may not need to query the user as to a model of the device to be replaced.

While description is made herein to dialog criteria being satisfied in response to intents of natural-language inputs matching, in some examples dialog criteria further includes a requirement that one or more parameters have been fulfilled such that the electronic device can transition to a next state in the dialog flow. As an example, a user may indicate a desire to purchase a product and the electronic device may in turn require product information to proceed with the sale. Accordingly, during operation, the electronic device may invoke one or more collect functions. A collect function may be a function that determines whether an input includes any of the information required by the electronic device. In some examples, a collect function determines

46

whether an input includes required information using pattern matching. Accordingly, the electronic device may identify both entity names and any known synonyms, allowing for a more flexible and accurate dialog framework that avoids strict adherence to specific terms or names.

In an example in which a user provides the input "I want to buy a new 64 GB iPhone 8S", the electronic device selects the "Product Purchase" dialog flow, as described. The electronic device then invokes one or more collect functions to determine that the user has specified a type (phone), model (iPhone 8S), and storage capacity (64 GB), but that the user has not provided a color of the device. Accordingly, the electronic device may query the user for the required parameter (e.g., color).

Generally, operation of the electronic device, in accordance with one or more dialog flows, may rely on predetermined (e.g., canned) natural-language expressions for exchanging dialog with a user. In some examples, however, a user may be better served by communicating with a live agent. Accordingly, in some examples, the electronic device determines whether service criteria has been satisfied, and if so, connects to a remote service (e.g., using one or more API calls) such that the user is able to communicate with a live agent. By way of example, the service criteria is satisfied if a user invokes a "Product Purchase" dialog flow and the user indicates that he or she wants assistance in choosing a product (e.g., "Should I buy the 32 GB phone or 64 GB phone?"). In another example, the service criteria is satisfied if a user invokes a "Product Purchase" dialog flow and the electronic device is unable to understand one or more natural-language inputs provided by the user.

In some examples, the electronic device receives information associated with a user, such as the user's appearance and/or voice. In at least one embodiment, this information, or sentiment data, can be used to determine a mood of the user. A voice of a user, for instance, can indicate whether a user is angry or anxious. In some examples, the electronic device can customize natural-language outputs based on the sentiment data. If a user is determined to be angry or frustrated, for instance, the electronic device may provide natural-language outputs that are more apologetic to the user. If a user is determined to be confused, the electronic device may provide shorter and/or simplified natural-language outputs.

The operations described above with reference to FIG. 8 are optionally implemented by components depicted in FIGS. 1-4, 6A-B, and 7A-C. For example, the operations of process 800 may be implemented by any device (or component thereof) described herein, including but not limited to, devices 104, 200, 400, and 600. It would be clear to a person having ordinary skill in the art how other processes are implemented based on the components depicted in FIGS. 1-4, 6A-B, and 7A-C.

In accordance with some implementations, a computer-readable storage medium (e.g., a non-transitory computer readable storage medium) is provided, the computer-readable storage medium storing one or more programs for execution by one or more processors of an electronic device, the one or more programs including instructions for performing any of the methods or processes described herein.

In accordance with some implementations, an electronic device e.g., a portable electronic device) is provided that comprises means for performing any of the methods or processes described herein.

In accordance with some implementations, an electronic device (e.g., a portable electronic device) is provided that

comprises a processing unit configured to perform any of the methods or processes described herein.

In accordance with some implementations, an electronic device (e.g., a portable electronic device) is provided that comprises one or more processors and memory storing one or more programs for execution by the one or more processors, the one or more programs including instructions for performing any of the methods or processes described herein.

The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the techniques and their practical applications. Others skilled in the art are thereby enabled to best utilize the techniques and various embodiments with various modifications as are suited to the particular use contemplated.

Although the disclosure and examples have been fully described with reference to the accompanying drawings, it is to be noted that various changes and modifications will become apparent to those skilled in the art. Such changes and modifications are to be understood as being included within the scope of the disclosure and examples as defined by the claims.

As described above, one aspect of the present technology is the gathering and use of data available from various sources to improve the delivery to users of invitational content or any other content that may be of interest to them. The present disclosure contemplates that in some instances, this gathered data may include personal information data that uniquely identifies or can be used to contact or locate a specific person. Such personal information data can include demographic data, location-based data, telephone numbers, email addresses, home addresses, or any other identifying information.

The present disclosure recognizes that the use of such personal information data, in the present technology, can be used to the benefit of users. For example, the personal information data can be used to deliver targeted content that is of greater interest to the user. Accordingly, use of such personal information data enables calculated control of the delivered content. Further, other uses for personal information data that benefit the user are also contemplated by the present disclosure.

The present disclosure further contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal information data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. For example, personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection should occur only after receiving the informed consent of the users. Additionally, such entities would take any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices.

Despite the foregoing, the present disclosure also contemplates embodiments in which users selectively block the use of, or access to, personal information data. That is, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to such personal information data. For example, in the case of advertisement delivery services, the present technology can be configured to allow users to select to “opt in” or “opt out” of participation in the collection of personal information data during registration for services. In another example, users can select not to provide location information for targeted content delivery services. In yet another example, users can select to not provide precise location information, but permit the transfer of location zone information.

Therefore, although the present disclosure broadly covers use of personal information data to implement one or more various disclosed embodiments, the present disclosure also contemplates that the various embodiments can also be implemented without the need for accessing such personal information data. That is, the various embodiments of the present technology are not rendered inoperable due to the lack of all or a portion of such personal information data. For example, content can be selected and delivered to users by inferring preferences based on non-personal information data or a bare minimum amount of personal information, such as the content being requested by the device associated with a user, other non-personal information available to the content delivery services, or publically available information.

What is claimed is:

1. A non-transitory computer-readable storage medium storing one or more programs, the one or more programs comprising instructions, which when executed by one or more processors of a first electronic device, cause the first electronic device to:

- receive a first natural-language input;
- determine a first intent based on the first natural-language input;
- identify a first dialog flow based on the first intent;
- output a natural-language output associated with the first dialog flow;
- receive a second natural-language input;
- determine whether the second natural-language input satisfies dialog criteria associated with the first dialog flow, wherein determining whether the second natural-language input satisfies dialog criteria associated with the first dialog flow includes:
 - determining a second intent based on the second natural-language input; and
 - determining whether the first intent matches the second intent; and

- in accordance with a determination that the second natural-language input satisfies the dialog criteria, output a second natural-language output associated with the first dialog flow.

2. The non-transitory computer-readable storage medium of claim 1, wherein the one or more programs further include instructions, which when executed by the one or more processors of the first electronic device, cause the first electronic device to:

- in accordance with a determination that the second natural-language input does not satisfy the dialog criteria, output a natural-language output associated with a second dialog flow.

3. The non-transitory computer-readable storage medium of claim 2, wherein outputting a natural-language output associated with a second dialog flow includes:

49

identifying the second dialog flow based on the second natural-language input.

4. The non-transitory computer-readable storage medium of claim 1, wherein the one or more programs further include instructions, which when executed by the one or more processors of the first electronic device, cause the first electronic device to:

in accordance with a determination that the second natural-language input does not satisfy the dialog criteria: in accordance with a determination that dialog context criteria is met, output a third natural-language output associated with the first dialog flow.

5. The non-transitory computer-readable storage medium of claim 4, wherein outputting a third natural-language output associated with the first dialog flow includes:

obtaining sentiment data associated with a user of the electronic device; and
outputting the third natural-language output based on the sentiment data.

6. The non-transitory computer-readable storage medium of claim 1, wherein determining whether the second natural-language input satisfies dialog criteria associated with the first dialog flow includes:

determining whether a pattern of the second natural-language input matches a pattern specified by the first dialog flow.

7. The non-transitory computer-readable storage medium of claim 1, wherein the one or more programs further include instructions, which when executed by the one or more processors of the first electronic device, cause the first electronic device to:

determine whether service criteria is satisfied; in accordance with a determination that the service criteria has been met, initiate a connection between the electronic device and a remote service.

8. The non-transitory computer-readable storage medium of claim 1, wherein determining a first intent based on the first natural-language input includes:

determining the first intent using a machine-learned system.

9. The non-transitory computer-readable storage medium of claim 8, wherein the machine learned system includes a classification network and wherein determining the first intent using a machine-learned system includes:

receiving, with the classification network, the first natural-language input; determining, based on the first natural-language input, a confidence score for each of a plurality of intents; and selecting the intent associated with the highest confidence score.

10. The non-transitory computer-readable storage medium of claim 1, wherein the natural-language output associated with the first dialog flow and the second natural-language output associated with the first dialog flow are predetermined natural-language outputs specified by the first dialog flow.

11. A method, comprising:

at an electronic device with one or more processors:

receiving a first natural-language input; determining a first intent based on the first natural-language input; identifying a first dialog flow based on the first intent; outputting a natural-language output associated with the first dialog flow; receiving a second natural-language input; determining whether the second natural-language input satisfies dialog criteria associated with the first dia-

50

log flow, wherein determining whether the second natural-language input satisfies dialog criteria associated with the first dialog flow includes:

determining a second intent based on the second natural-language input; and
determining whether the first intent matches the second intent; and

in accordance with a determination that the second natural-language input satisfies the dialog criteria, outputting a second natural-language output associated with the first dialog flow.

12. The method of claim 11, further comprising:

in accordance with a determination that the second natural-language input does not satisfy the dialog criteria, outputting a natural-language output associated with a second dialog flow.

13. The method of claim 12, wherein outputting a natural-language output associated with a second dialog flow includes:

identifying the second dialog flow based on the second natural-language input.

14. The method of claim 11, further comprising:

in accordance with a determination that the second natural-language input does not satisfy the dialog criteria: in accordance with a determination that dialog context criteria is met, outputting a third natural-language output associated with the first dialog flow.

15. The method of claim 14, wherein outputting a third natural-language output associated with the first dialog flow includes:

obtaining sentiment data associated with a user of the electronic device; and
outputting the third natural-language output based on the sentiment data.

16. The method of claim 11, wherein determining whether the second natural-language input satisfies dialog criteria associated with the first dialog flow includes:

determining whether a pattern of the second natural-language input matches a pattern specified by the first dialog flow.

17. The method of claim 11, further comprising:

determining whether service criteria is satisfied; in accordance with a determination that the service criteria has been met, initiating a connection between the electronic device and a remote service.

18. The method of claim 11, wherein determining a first intent based on the first natural-language input includes: determining the first intent using a machine-learned system.

19. The method of claim 18, wherein the machine learned system includes a classification network and wherein determining the first intent using a machine-learned system includes:

receiving, with the classification network, the first natural-language input; determining, based on the first natural-language input, a confidence score for each of a plurality of intents; and selecting the intent associated with the highest confidence score.

20. An electronic device, comprising:

one or more processors;
a memory; and
one or more programs, wherein the one or more programs are stored in the memory and configured to be executed by the one or more processors, the one or more programs including instructions for:

51

receiving a first natural-language input;
determining a first intent based on the first natural-language input;
identifying a first dialog flow based on the first intent;
outputting a natural-language output associated with the first dialog flow;
receiving a second natural-language input;
determining whether the second natural-language input satisfies dialog criteria associated with the first dialog flow, wherein determining whether the second natural-language input satisfies dialog criteria associated with the first dialog flow includes:
determining a second intent based on the second natural-language input; and
determining whether the first intent matches the second intent; and
in accordance with a determination that the second natural-language input satisfies the dialog criteria, outputting a second natural-language output associated with the first dialog flow.

21. The electronic device claim 20, wherein the one or more programs further include instructions for:
in accordance with a determination that the second natural-language input does not satisfy the dialog criteria, outputting a natural-language output associated with a second dialog flow.

22. The electronic device of claim 21, wherein outputting a natural-language output associated with a second dialog flow includes:
identifying the second dialog flow based on the second natural-language input.

23. The electronic device of claim 20, wherein the one or more programs further include instructions for:
in accordance with a determination that the second natural-language input does not satisfy the dialog criteria:
in accordance with a determination that dialog context criteria is met, outputting a third natural-language output associated with the first dialog flow.

52

24. The electronic device of claim 23, wherein outputting a third natural-language output associated with the first dialog flow includes:
obtaining sentiment data associated with a user of the electronic device; and
outputting the third natural-language output based on the sentiment data.

25. The electronic device of claim 20, wherein determining whether the second natural-language input satisfies dialog criteria associated with the first dialog flow includes:
determining whether a pattern of the second natural-language input matches a pattern specified by the first dialog flow.

26. The electronic device of claim 20, wherein the one or more programs further include instructions for:
determining whether service criteria is satisfied;
in accordance with a determination that the service criteria has been met, initiating a connection between the electronic device and a remote service.

27. The electronic device of claim 20, wherein determining a first intent based on the first natural-language input includes:
determining the first intent using a machine-learned system.

28. The electronic device of claim 27, wherein the machine learned system includes a classification network and wherein determining the first intent using a machine-learned system includes:
receiving, with the classification network, the first natural-language input;
determining, based on the first natural-language input, a confidence score for each of a plurality of intents; and
selecting the intent associated with the highest confidence score.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 10,733,982 B2
APPLICATION NO. : 15/946517
DATED : August 4, 2020
INVENTOR(S) : Nicholas A. Grupen et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

In Claim 9, Column 49, Line 42, delete “machine learned” insert -- machine-learned --.

In Claim 19, Column 50, Line 51, delete “machine learned” insert -- machine-learned --.

In Claim 21, Column 51, Line 21, after “device” insert -- of --.

In Claim 28, Column 52, Line 28, delete “machine learned” insert -- machine-learned --.

Signed and Sealed this
Fourth Day of May, 2021



Drew Hirshfeld
*Performing the Functions and Duties of the
Under Secretary of Commerce for Intellectual Property and
Director of the United States Patent and Trademark Office*